

State of Montana
Department of Environmental Quality
Helena, Montana 59620

AIR QUALITY OPERATING PERMIT NUMBER OP2965-01

Renewal Application Received: **October 10, 2003**
Application Deemed Administratively Complete: **October 15, 2003**
Application Deemed Technically Complete: **October 17, 2003**
AFS Number: **030-063-0004A**

Draft Issue Date: **December 29, 2004**
Proposed Issue Date: **April 1, 2005**
End of EPA 45-day Review: **May 19, 2005**
Date of Decision: **May 20, 2005**
Effective Date: **June 21, 2005**
Expiration Date: **June 21, 2010**

In accordance with the Montana Code Annotated sections 75-2-217 and 218, and Administrative Rules of Montana (ARM), Title 17, Chapter 8, Subchapter 12, Operating Permit Program, ARM 17.8.1201, *et seq.*,

Pyramid Mountain Lumber, Inc.
SE ¼ of Section 3, Township 15 North, Range 15 West, Missoula County, Montana
P.O. Box 549
Seeley Lake, MT 59868

hereinafter referred to as "Pyramid," is authorized to operate a stationary source of air contaminants consisting of the emission units described in this permit. Until this permit expires, is modified, or revoked, the permittee is allowed to discharge air pollutants in accordance with the conditions of this permit. All conditions in this permit are federally and state enforceable, unless otherwise specified. Requirements that are only state enforceable are identified in the permit. A copy of this permit must be kept on site at the above-named facility.

Issued by the Department of Environmental Quality

_____/_____/_____
Signature Date

Permit Issuance and Appeal Process: In accordance with ARM 17.8.1210(j), the Department of Environmental Quality's (Department) decision regarding issuance of an operating permit is not effective until 30 days have elapsed from the date of the decision issued May 20, 2005. The decision may be appealed to the Board of Environmental Review by filing a request for a hearing within 30 days after the date of decision. If no appeal is filed then the Department will send notification and a final permit cover page to be attached to this document stating that the permit is final. In addition, ARM 17.8.1233 allows for any person to petition the Environmental Protection Agency (EPA) within 60 days after the expiration of EPA's 45-day review period to object to issuance of this operating permit. If EPA objects to the operating permit as a result of a petition prior to the Department's notification of a final permit, Pyramid and all affected parties will be informed of the stay of a final permit. If the Department has already notified Pyramid and all affected parties, the Department shall issue a revised permit according to ARM 17.8.1231. Questions regarding the final issuance date and status of appeals should be directed to the Department at (406) 444-3490.

Montana Air Quality Operating Permit
Department of Environmental Quality

SECTION I. GENERAL INFORMATION	1
SECTION II. SUMMARY OF EMISSION UNITS	2
SECTION III. PERMIT CONDITIONS	3
A. FACILITY-WIDE	3
B. EU001: WELLONS HOG FUEL BOILER (18,000 LB)	6
C. EU002: YORK/SHIPLEY HOG FUEL BOILER (6,000 LB)	8
D. EU003: (6) DRY KILNS.....	9
E. CYCLONES:EU008 – A63 PLANER SHAVINGS CYCLONE.....	11
EU009 – A62 PLANER SHAVINGS CYCLONE	11
EU013 – SHAVINGS BIN CYCLONE	11
F. EU025: UNPAVED ROAD DUST EMISSIONS.....	13
G. EU031: YORK/SHIPLEY HOG FUEL BOILER (12,000 LB).....	15
SECTION IV. NON-APPLICABLE REQUIREMENTS	17
A. FACILITY-WIDE	17
B. EMISSION UNITS.....	19
SECTION V. GENERAL PERMIT CONDITIONS.....	20
A. COMPLIANCE REQUIREMENTS.....	20
B. CERTIFICATION REQUIREMENTS	20
C. PERMIT SHIELD.....	21
D. MONITORING, RECORDKEEPING, AND REPORTING REQUIREMENTS.....	22
E. PROMPT DEVIATION REPORTING.....	23
F. EMERGENCY PROVISIONS	23
G. INSPECTION AND ENTRY	24
H. FEE PAYMENT.....	24
I. MINOR PERMIT MODIFICATIONS	25
J. CHANGES NOT REQUIRING PERMIT REVISION	25
K. SIGNIFICANT PERMIT MODIFICATIONS.....	26
L. REOPENING FOR CAUSE	26
M. PERMIT EXPIRATION AND RENEWAL.....	27
N. SEVERABILITY CLAUSE	27
O. TRANSFER OR ASSIGNMENT OF OWNERSHIP.....	27
P. EMISSIONS TRADING, MARKETABLE PERMITS, ECONOMIC INCENTIVES	28
Q. NO PROPERTY RIGHTS CONVEYED.....	28
R. TESTING REQUIREMENTS.....	28
S. SOURCE TESTING PROTOCOL	28
T. MALFUNCTIONS	28
U. CIRCUMVENTION	28
V. MOTOR VEHICLES	28
W. ANNUAL EMISSIONS INVENTORY	28
X. OPEN BURNING.....	29
Y. MONTANA AIR QUALITY PERMITS	29
Z. NATIONAL EMISSION STANDARD FOR ASBESTOS	29
AA. ASBESTOS	30

BB. STRATOSPHERIC OZONE PROTECTION – SERVICING OF MOTOR VEHICLE AIR	
CONDITIONERS	30
CC. STRATOSPHERIC OZONE PROTECTION – RECYCLING AND EMISSION REDUCTIONS	30
DD. EMERGENCY EPISODE PLAN	30
EE. DEFINITIONS	30
APPENDIX A INSIGNIFICANT EMISSION UNITS	A-1
APPENDIX B DEFINITIONS AND ABBREVIATIONS	B-1
APPENDIX C NOTIFICATION ADDRESSES	C-1
APPENDIX D AIR QUALITY INSPECTOR INFORMATION	D-1

Terms not otherwise defined in this permit or in the Definitions and Abbreviations Appendix of this permit have the meaning assigned to them in the referenced regulations.

SECTION I. GENERAL INFORMATION

The following general information is provided pursuant to ARM 17.8.1210(1).

Company Name: **Pyramid Mountain Lumber, Inc.**

Mailing Address: **P.O. Box 549**

City: **Seeley**

State: **MT**

Zip: **59868**

Plant Location: **SE ¼ of Section 3, Township 15 North, Range 15 West, Missoula County, Montana**

Responsible Official: **Roger Johnson**

Phone: **(406) 677-2201**

Facility Contact Person: **Todd Johnson**

Phone: **(406) 677-2201**

Primary SIC Code: **2421**

Nature of Business: **Sawmill**

Description of Process:

Pyramid operates a sawmill that produces planed, dimension lumber. Logs from on-site storage decks are debarked, cut into rough sizes, dried, planed to proper dimension, and stacked in bundles for shipment. Currently, two hog fuel fired boilers provide heat for the drying process. Once the 12,000 lb York/Shiplely Boiler is installed, there will be three boilers providing heat for the drying process.

Hogged bark is chain conveyed to a storage pile. From the storage pile the bark is loaded onto a chain conveyor that transfers the bark to a fuel storage silo located above the Wellons Boiler. The hogged bark is also loaded into trucks and transferred to the York/Shiplely Boiler building where the bark is metered into the boiler from the truck. Excess hogged bark is sold and trucked off site.

Sawdust is chain conveyed into a storage pile. The sawdust is then loaded into trucks and transferred off-site. Planer shaving and chips are pneumatically conveyed and collected in an enclosed storage bin where they can be transported by truck off-site and sold for other purposes.

Pyramid also operates a moulder to produce tongue and groove lumber at the facility.

SECTION II. SUMMARY OF EMISSION UNITS

The emission units regulated by this permit are the following (ARM 17.8.1211):

Emissions Unit ID	Description	Pollution Control Device/Practice
EU001	Wellons Boiler (18,000 lb/hr)	Multiclone
EU002	York/Shiplely Boiler (6,000 lb/hr)	Cyclone
EU003	(6) Dry Kilns	None
EU004	Planer Blow Hog	None
EU005	Chip Bin #1 Cyclone	Cyclone is Control Device
EU006	Chip Silo Cyclone	Cyclone is Control Device
EU007	Chip Bin #2 Cyclone	Cyclone is Control Device
EU008	A-63 Planer Shavings Cyclone	Cyclone is Control Device
EU009	A-62 Planer Shavings Cyclone	Cyclone is Control Device
EU010	Blow Hog Sawdust Cyclone	Cyclone is Control Device
EU011	Moulder Surge Bin Cyclone	Cyclone is Control Device
EU012	Moulder Shavings Bin Cyclone	Cyclone is Control Device
EU013	Shavings Bin Cyclone	Cyclone is Control Device
EU014	Debarker	None
EU015	Bark Handling Fugitives	None
EU016	Chips Handling Fugitives	None
EU017	Shavings Loadout Fugitives	None
EU018	Hog Fuel Handling Fugitives	None
EU019	Sawdust Handling Fugitives	None
EU020	Sawmill Chippers	Cyclone
EU021	Cut off Saws	None
EU022	Building Vents	None
EU023	Sawdust Storage Pile Fugitives	None
EU024	Hog Fuel Storage Pile Fugitives	None
EU025	Unpaved Road Dust Emissions	Water and/or Chemical Dust Suppressant
EU026	Plant-wide Diesel Combustion	None
EU027	Plant-wide Gasoline Combustion	None
EU028	Plant-wide Propane Combustion	None
EU029	Gasoline Fuel Tank Fugitives	None
EU030	Diesel Fuel Tank Fugitives	None
EU031	York/Shiplely Boiler (12,000 lb/hr) – Has not been installed	None

SECTION III. PERMIT CONDITIONS

The following requirements and conditions are applicable to the facility or to specific emission units located at the facility (ARM 17.8.1211, 1212, and 1213).

A. Facility-Wide

Conditions	Rule Citation	Rule Description	Pollutant/Parameter	Limit
A.1	ARM 17.8.105, APCP 5.102	Testing Requirements	Testing Requirements	-----
A.2	ARM 17.8.304(1), APCP 6.504 (1)	Visible Air Contaminants	Opacity	40%
A.3	ARM 17.8.304(2), APCP 6.504(2)	Visible Air Contaminants	Opacity	20%
A.4	ARM 17.8.308(1), APCP 6.504(2)	Particulate Matter, Airborne	Fugitive Opacity	20%
A.5	ARM 17.8.308(2), APCP 8.102(3)	Particulate Matter, Airborne	Reasonable Precautions	-----
A.6	ARM 17.8.308, APCP 8.102(3)	Particulate Matter, Airborne	Reasonable Precaution, Construction	20%
A.7	ARM 17.8.309, APCP 6.502	Particulate Matter, Fuel Burning Equipment	Particulate Matter	$E = 0.882 * H^{-0.1664}$ Or $E = 1.026 * H^{-0.233}$
A.8	ARM 17.8.310, APCP 6.503	Particulate Matter, Industrial Processes	Particulate Matter	$E = 4.10 * P^{0.67}$ or $E = 55 * P^{0.11} - 40$
A.9	ARM 17.8.322(4), APCP 10.201	Sulfur Oxide Emissions, Sulfur in Fuel	Sulfur in Fuel (liquid or solid fuels)	1 lb/MMBtu fired
A.10	ARM 17.8.322(5), APCP 10.201(2)	Sulfur Oxide Emissions, Sulfur in Fuel	Sulfur in Fuel (gaseous)	50 gr/100 CF
A.11	ARM 17.8.324(3), APCP 10.303(1)	Hydrocarbon Emissions, Petroleum Products	Gasoline Storage Tanks	-----
A.12	ARM 17.8.324, APCP 10.301(1)	Hydrocarbon Emissions, Petroleum Products	65,000 Gallon Capacity	-----
A.13	ARM 17.8.324, APCP 10.302	Hydrocarbon Emissions, Petroleum Products	Oil-effluent Water Separator	-----
A.14	ARM 17.8.342, APCP 6.508	NESHAPs General Provisions	SSM Plans	Submittal
A.15	ARM 17.8.1212	Reporting Requirements	Compliance Monitoring	-----
A.16	ARM 17.8.1207	Reporting Requirements	Annual Certification	-----

Conditions

A.1. Pursuant to ARM 17.8.105 and Missoula City-County Air Pollution Control Program (APCP) 5.102, any person or persons responsible for the emission of any air contaminant into the outdoor atmosphere shall, upon written request of the Department, provide the facilities and necessary equipment (including instruments and sensing devices) and shall conduct tests, emission or ambient, for such periods of time as may be necessary using methods approved by the Department.

Compliance demonstration frequencies that list “as required by the Department” refer to ARM 17.8.105. In addition, for such sources, compliance with limits and conditions listing “as required by the Department” as the frequency, is verified annually using emission factors and engineering calculations by the Department’s compliance inspectors during the annual emission inventory review; in the case of Method 9 tests, compliance is monitored during the annual inspection by the compliance inspector.

- A.2. Pursuant to ARM 17.8.304(1) and APCP 6.504(1), Pyramid shall not cause or authorize emissions to be discharged into the outdoor atmosphere from any source installed on or before November 23, 1968, that exhibit an opacity of 40% or greater averaged over 6 consecutive minutes, unless otherwise specified by rule or in this permit.
- A.3. Pursuant to ARM 17.8.304(2) and APCP 6.504(2), Pyramid shall not cause or authorize emissions to be discharged into the outdoor atmosphere from any source installed after November 23, 1968, that exhibit an opacity of 20% or greater averaged over 6 consecutive minutes, unless otherwise specified by rule or in this permit.
- A.4. Pursuant to ARM 17.8.308(1) and APCP 6.504(2), Pyramid shall not cause or authorize the production, handling, transportation, or storage of any material unless reasonable precautions to control emissions of particulate matter are taken. Such emissions of airborne particulate matter from any stationary source shall not exhibit an opacity of 20% or greater averaged over 6 consecutive minutes, unless otherwise specified by rule or in this permit.
- A.5. Pursuant to ARM 17.8.308(2) and APCP 8.102(3), Pyramid shall not cause or authorize the use of any street, road, or parking lot without taking reasonable precautions to control emissions of airborne particulate matter, unless otherwise specified by rule or in this permit.
- A.6. Pursuant to ARM 17.8.308 and APCP 8.102(3), Pyramid shall not operate a construction site or demolition project unless reasonable precautions are taken to control emissions of airborne particulate matter. Such emissions of airborne particulate matter from any stationary source shall not exhibit an opacity of 20% or greater averaged over 6 consecutive minutes, unless otherwise specified by rule or in this permit.
- A.7. Pursuant to ARM 17.8.309 and APCP 6.502, unless otherwise specified by rule or in this permit, Pyramid shall not cause or authorize particulate matter caused by the combustion of fuel to be discharged from any stack or chimney into the outdoor atmosphere in excess of the maximum allowable emissions of particulate matter for existing fuel burning equipment and new fuel burning equipment calculated using the following equations:

For existing fuel burning equipment (installed before November 23, 1968):

$$E = 0.882 * H^{-0.1664}$$

For new fuel burning equipment (installed on or after November 23, 1968):

$$E = 1.026 * H^{-0.233}$$

Where H is the heat input capacity in million BTU (MMBtu) per hour and E is the maximum allowable particulate emissions rate in pounds per MMBtu.

- A.8. Pursuant to ARM 17.8.310 and APCP 6.503, unless otherwise specified by rule or in this permit, Pyramid shall not cause or authorize particulate matter to be discharged from any operation, process, or activity into the outdoor atmosphere in excess of the maximum hourly allowable emissions of particulate matter calculated using the following equations:

For process weight rates up to 30 tons per hour:	$E = 4.10 * P^{0.67}$
For process weight rates in excess of 30 tons per hour:	$E = 55.0 * P^{0.11} - 40$

Where E = rate of emissions in pounds per hour and p = process weight rate in tons per hour.

- A.9. Pursuant to ARM 17.8.322(4) and APCP 10.201, Pyramid shall not burn liquid or solid fuels containing sulfur in excess of 1 pound per million BTU (lb/MMBtu) fired, unless otherwise specified by rule or in this permit.
- A.10. Pursuant to ARM 17.8.322(5) and APCP 10.201(2), Pyramid shall not burn any gaseous fuel containing sulfur compounds in excess of 50 grains per 100 cubic feet of gaseous fuel, calculated as hydrogen sulfide at standard conditions, unless otherwise specified by rule or in this permit.
- A.11. Pursuant to ARM 17.8.324(3) and APCP 10.303(1), Pyramid shall not load or permit the loading of gasoline into any stationary tank with a capacity of 250 gallons or more from any tank truck or trailer, except through a permanent submerged fill pipe, unless such tank is equipped with a vapor loss control device or is a pressure tank as described in ARM 17.8.324(1), unless otherwise specified by rule or in this permit.
- A.12. Pursuant to ARM 17.8.324 and APCP 10.301(1), unless otherwise specified by rule or in this permit, Pyramid shall not place, store, or hold in any stationary tank, reservoir, or other container of more than 65,000 gallon capacity any crude oil, gasoline, or petroleum distillate having a vapor pressure of 2.5 pounds per square inch absolute or greater under actual storage conditions, unless such tank, reservoir, or other container is a pressure tank maintaining working pressure sufficient at all times to prevent hydrocarbon vapor or gas loss to the atmosphere, or is designed and equipped with a vapor loss control device, properly installed, in good working order, and in operation.
- A.13. Pursuant to ARM 17.8.324 and APCP 10.302, unless otherwise specified by rule or in this permit, Pyramid shall not use any compartment of any single or multiple-compartment oil-effluent water separator, which compartment receives effluent water containing 200 gallons a day or more of any petroleum product from any equipment processing, refining, treating, storing, or handling kerosene or other petroleum product of equal or greater volatility than kerosene, unless such compartment is equipped with a vapor loss control device, constructed so as to prevent emission of hydrocarbon vapors to the atmosphere, properly installed, in good working order, and in operation.
- A.14. Pursuant to ARM 17.8.342, APCP 6.508, and 40 CFR 63.6, Pyramid shall submit to the Department a copy of any startup, shutdown, and malfunction (SSM) plan required under 40 CFR 63.6(e)(3) within 30 days of the effective date of this operating permit (if not previously submitted), within 30 days of the compliance date of any new National Emission Standard for Hazardous Air Pollutants (NESHAPs) or Maximum Achievable Control Technology (MACT) standard, and within 30 days of the revision of any such SSM plan, when applicable. The Department requests submittal of such plans in electronic form, when possible.
- A.15. On or before February 15 and August 15 of each year, Pyramid shall submit to the Department the compliance monitoring reports required by Section V.D. These reports must contain all information required by Section V.D, as well as the information required by each individual emissions unit. For the reports due by February 15 of each year, Pyramid may submit a single report, provided that it contains all the information required by Section V.B & V.D. Per ARM 17.8.1207,

any application form, report, or compliance certification submitted pursuant to ARM Title 17, Chapter 8, Subchapter 12 (including semiannual monitoring reports), shall contain certification by a responsible official of truth, accuracy, and completeness. This

certification and any other certification required under ARM Title 17, Chapter 8, Subchapter 12, shall state that, “based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.”

A.16. By February 15 of each year, Pyramid shall submit to the Department the compliance certification report required by Section V.B. The annual certification report required by Section V.B must include a statement of compliance based on the information available, which identifies any observed, documented, or otherwise known instance of noncompliance for each applicable requirement. Per ARM 17.8.1207,

any application form, report, or compliance certification submitted pursuant to ARM Title 17, Chapter 8, Subchapter 12 (including annual certifications), shall contain certification by a responsible official of truth, accuracy, and completeness. This certification and any other certification required under ARM Title 17, Chapter 8, Subchapter 12, shall state that, “based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.”

B. EU001: Wellons Hog Fuel Boiler (18,000 lbs of steam/hour)

Condition(s)	Pollutant/Parameter	Permit Limit	Compliance Demonstration Method Frequency		Reporting Requirements
B.1, B.2, B.6, B.7, B.12, B.13, B.14, B.15	Opacity	20%	Method 9	As Required by the Department and Section III.A.1	Semi-Annual
			Multiclone	Whenever Boiler is Operated	
B.3, B.6, B.8, B.10, B.12, B.13, B.14, B.15	Particulate Matter	0.2 lb/MMBtu of hog fuel	Method 5	As Required by the Department and Section III.A.1	Semi-Annual
B.4, B.9, B.11, B.15	Sulfur in Fuel	1lb/MMBtu fired	Recordkeeping	Ongoing	Semi-Annual
B.5, B.10, B.13, B.14, B.15	CO	24.0 lb/hr	Method 10	As Required by the Department and Section III.A.1	Semi-Annual

Conditions

- B.1. Pyramid shall not cause or authorize emissions to be discharged into the outdoor atmosphere from any source that exhibit an opacity of 20% or greater averaged over six consecutive minutes (ARM 17.8.304(2) and APCP 6.504(2)).
- B.2. During the building of new fires, cleaning of grates, or soot blowing, ARM 17.8.304(2) applies except that a maximum average opacity of 60% is permissible for not more than one 4-minute period in any 60 consecutive minutes (ARM 17.8.304(3) and APCP 6.504(3)).
- B.3. Particulate emissions from the Wellons Boiler shall not exceed 0.2 lb/MMBtu fired (ARM 17.8.749 and APCP 6.502(2)).

- B.4. Pyramid shall not burn liquid or solid fuels containing sulfur in excess of 1 lb/MMBtu fired (ARM 17.8.322(4) and APCP 10.201).
- B.5. Carbon monoxide (CO) emissions from the Wellons Boiler shall not exceed 24.0 lb/hr (ARM 17.8.749 and APCP 6.103(1)).

Compliance Demonstration

- B.6. Pyramid shall verify weekly that the multiclone is being operated in good working order and that the multiclone is operated whenever the Wellons Boiler is fired (17.8.1213).
- B.7. As required by the Department and Section III.A.1, Pyramid shall perform a Method 9 test in accordance with the Montana Source Test Protocol and Procedures Manual. The Method 9 test or other Department approved method test must be used to monitor compliance with the 20% opacity limit. Each observation period shall be a minimum of 6 minutes or until a violation of the standard has been documented, whichever is a shorter period of time (ARM 17.8.106, ARM 17.8.1213, and APCP 5.102).
- B.8. As required by the Department and Section III.A.1, Pyramid shall perform a Method 5 test or other approved test in accordance with the Montana Source Test Protocol and Procedures Manual when requested by the Department to monitor compliance with Section III.B.3 (ARM 17.8.106, ARM 17.8.1213, and APCP 5.102).
- B.9. Pyramid may combust only wood waste in the boiler, except for boiler start-up, when a flame accelerant or oil may be utilized (ARM 17.8.1213).
- B.10. As required by the Department and Section III.A.1, Pyramid shall perform a Method 10 test or other approved test in accordance with the Montana Source Test Protocol and Procedures Manual to monitor compliance with the CO limit contained in Section III.B.5 (ARM 17.8.106, ARM 17.8.749, ARM 17.8.1213, APCP 5.102, and APCP 6.103(1)).

Recordkeeping

- B.11. Pyramid shall maintain, on site, a log of any material combusted in the boiler other than wood waste. The log must include the date, time, material, and quantity combusted in the boiler (ARM 17.8.1212).
- B.12. Pyramid shall maintain, on site, a log regarding the operating status of the multiclone, as required by Section III.B.6. The log shall also contain the date and time of any maintenance activities performed on the multiclone including the maintenance procedure performed (ARM 17.8.1212).
- B.13. All compliance source test recordkeeping shall be performed in accordance with the test method used and the Montana Source Test Protocol and Procedures Manual, and shall be maintained on site (ARM 17.8.106, ARM 17.8.1212, and APCP 5.102).

Reporting

- B.14. Any compliance source test reports must be submitted in accordance with the Montana Source Test Protocol and Procedures Manual (ARM 17.8.106, ARM 17.8.1212, and APCP 5.102).

B.15. The annual compliance certification report required by Section V.B must contain a certification statement for the above applicable requirements. The semiannual reporting shall provide (ARM 17.81212):

- a. A summary of results of the last source testing that was performed;
- b. Verification that the log required by Section III.B.11 was maintained; and
- c. Verification that the log required by Section III.B.12 was maintained.

C. EU002: York/Shipley Hog Fuel Boiler (6,000 lbs of steam/hour)

Condition(s)	Pollutant/Parameter	Permit Limit	Compliance Demonstration		Reporting Requirements
			Method	Frequency	
C.1, C.2, C.6, C.11, C.12, C.13	Opacity	20%	Method 9	As Required by the Department and Section III.A.1	Semi-Annual
C.3, C.7, C.11, C.12, C.13	Particulate Matter	$E = 0.882 * H^{-0.1664}$	Method 5	As Required by the Department and Section III.A.1	Semi-Annual
C.4, C.8, C.10, C.13	Sulfur in Fuel	1lb/MMBtu fired	Recordkeeping	Ongoing	Semi-Annual
C.5, C.9, C.11, C.12, C.13	CO	6.0 lb/hr	Method 10	As Required by the Department and Section III.A.1	Semi-Annual

Conditions

- C.1. Pyramid shall not cause or authorize emissions to be discharged into the outdoor atmosphere from any source that exhibits an opacity of 20% or greater averaged over six consecutive minutes (ARM 17.8.304(2) and APCP 6.504(2)).
- C.2. During the building of new fires, cleaning of grates, or soot blowing, ARM 17.8.304(2) applies except that a maximum average opacity of 60% is permissible for not more than one 4-minute period in any 60 consecutive minutes (ARM 17.8.304(3) and APCP 6.504(3)).
- C.3. Pyramid shall not cause or authorize to be discharged into the atmosphere from the York/Shipley Boiler particulate matter in excess of that allowed by $E = 0.882 * H^{-0.1664}$, where H is the heat input capacity in MMBtu per hour and E is the maximum allowable particulate emission rate in pounds per MMBtu (ARM 17.8.309 and APCP 6.502).
- C.4. Pyramid shall not burn liquid or solid fuels containing sulfur in excess of 1 lb/MMBtu fired (ARM 17.8.322(4) and APCP 10.201).
- C.5. CO emissions from the York/Shipley Boiler shall not exceed 6.0 lb/hr (ARM 17.8.749 and APCP 6.103(1)).

Compliance Demonstration

- C.6. As required by the Department and Section III.A.1, Pyramid shall perform a Method 9 test in accordance with the Montana Source Test Protocol and Procedures Manual. The Method 9 test or other Department approved method test must be used to monitor compliance with the 20% opacity

limit. Each observation period shall be a minimum of 6 minutes or until a violation of the standard has been documented, whichever is a shorter period of time (ARM 17.8.106, ARM 17.8.1213, and APCP 5.102).

- C.7. As required by the Department and Section III.A.1, Pyramid shall perform a Method 5 test or other approved test in accordance with the Montana Source Test Protocol and Procedures Manual when requested by the Department to monitor compliance with Section III.C.3 (ARM 17.8.106, ARM 17.8.1213, and APCP 5.102).
- C.8. Pyramid may combust only wood waste in the boiler, except for boiler start-up, when a flame accelerant or oil may be utilized (ARM 17.8.1213).
- C.9. When requested by the Department and Section III.A.1, Pyramid shall perform a Method 10 test or other approved test in accordance with the Montana Source Test Protocol and Procedures Manual to monitor compliance with the CO limit contained in Section III.C.5 (ARM 17.8.106, ARM 17.8.749, ARM 17.8.1213, APCP 5.102, and APCP 6.103(1)).

Recordkeeping

- C.10. Pyramid shall maintain, on site, a log of any material combusted in the boiler other than wood waste. The log must include the date, time, material, and quantity combusted in the boiler (ARM 17.8.1212).
- C.11. All compliance source test recordkeeping shall be performed in accordance with the test method used and the Montana Source Test Protocol and Procedures Manual, and shall be maintained on site (ARM 17.8.106 and ARM 17.8.1212).

Reporting

- C.12. Any compliance source test reports must be submitted in accordance with the Montana Source Test Protocol and Procedures Manual (ARM 17.8.106, ARM 17.81212, and APCP 5.102).
- C.13. The annual compliance certification report required by Section V.B must contain a certification statement for the above applicable requirements. The semiannual reporting shall provide (ARM 17.81212):
 - a. A summary of results of the last source testing that was performed; and
 - b. Verification that the log required by Section III.C.10 was maintained.

D. EU003: (6) Dry Kilns

Condition(s)	Pollutant/Parameter	Permit Limit	Compliance Demonstration Method	Frequency	Reporting Requirements
D.1, D.3, D.5, D.7	Opacity	20%	Method 9	As Required by the Department and Section III.A.1	Semi-Annual
D.2, D.4, D.6, D.7	Particulate Matter	$E = 0.882 * H^{0.1664}$ $E = 55.0 * P^{0.11} - 40$	Normal Operations	Ongoing	Semi-Annual

Conditions

- D.1. Pyramid shall not cause or authorize emissions to be discharged into the outdoor atmosphere from any source that exhibits an opacity of 20% or greater averaged over six consecutive minutes (ARM 17.8.304(2) and APCP 6.504(2)).
- D.2. Pyramid shall not discharge into the atmosphere from the dry kilns particulate matter in excess of the amount allowed by ARM 17.8.310 and APCP 6.503. The following equations shall be used to calculate the values:

For process weight rates up to 30 tons per hour: $E = 4.10 * P^{0.67}$

For process weight rates in excess of 30 tons per hour: $E = 55.0 * P^{0.11} - 40$

Where E is the rate of emissions in pounds per hour and P is the process weight rate in tons per hour (ARM 17.8.310 and APCP 6.503).

Compliance Demonstration

- D.3. As required by the Department and Section III.A.1, a Method 9 test must be performed in accordance with the Montana Source Test Protocol and Procedures Manual. The Method 9 test or other Department approved method test must be used to monitor compliance with the 20% opacity limit. Each observation period shall be a minimum of 6 minutes or until a violation of the standard has been documented, whichever is a shorter period of time (ARM 17.8.106, ARM 17.8.1213, and APCP 5.102).
- D.4. The Dry Kilns shall be maintained and operated in accordance with proper operating procedures to minimize emissions and to monitor compliance with the particulate standard. A log of the following parameters shall be maintained on site and submitted to the Department upon request. Log entries shall occur weekly and during any maintenance on the equipment. All log entries shall include, but are not limited to the following (ARM 17.8.1213):
- a. Date of log entry;
 - b. Time of log entry;
 - c. Initials of individual entering information in the log;
 - d. List specific parameters checked to determine proper operation; and
 - e. Any maintenance activities occurring on the kilns.

Recordkeeping

- D.5. All compliance source test recordkeeping shall be performed in accordance with the test method used and the Montana Source Test Protocol and Procedures Manual, and shall be maintained on site (ARM 17.8.106, ARM 17.8.1212, and APCP 5.102).
- D.6. Pyramid shall maintain a log on site, as required by Section III.D.4, and submit it to the Department upon request (ARM 17.8.1212).

Reporting

D.7. The annual compliance certification report required by Section V.B must contain a certification statement for the above applicable requirements. The semiannual reporting shall provide a summary of results of any Method 9 test and verification that a log of corrective actions was maintained as specified by Section III.D.6. (ARM 17.8.1212).

**E. Cyclones: EU008 – A63 Planer Shavings Cyclone
EU009 – A62 Planer Shavings Cyclone
EU013 – Shavings Bin Cyclone**

Condition(s)	Pollutant/Parameter	Permit Limit	Compliance Demonstration		Reporting Requirements
			Method	Frequency	
E.1, E.3, E.5, E.6, E.7	Opacity	20%	Method 9	As Required by the Department and Section III.A.1	Semi-Annual
			Visual Surveys	Weekly	Semi-Annual
E.2, E.4, E.5, E.6, E.7	Particulate Matter	$E = 0.882 * H^{0.1664}$ $E = 55.0 * P^{0.11} - 40$	Method 5	As Required by the Department and Section III.A.1	Semi-Annual

Conditions

- E.1. Pyramid shall not cause or authorize emissions to be discharged into the outdoor atmosphere from any source that exhibits an opacity of 20% or greater averaged over six consecutive minutes (ARM 17.8.304(2) and APCP 6.504(2)).
- E.2. Pyramid shall not discharge into the atmosphere from the cyclones particulate matter in excess of the amount allowed by ARM 17.8.310 and APCP 6.503. The following equations shall be used to calculate the values.

For process weight rates up to 30 tons per hour: $E = 4.10 * P^{0.67}$

For process weight rates in excess of 30 tons per hour: $E = 55.0 * P^{0.11} - 40$

Where E is the rate of emissions in pounds per hour and P is the process weight rate in tons per hour (ARM 17.8.310 and APCP 6.503).

Compliance Demonstration

- E.3. Opacity is monitored in accordance with the requirements of 40 CFR Part 60, Appendix A, Method 9, or by an in-stack transmissometer complying with 40 CFR Part 60, Appendix B, Performance Specification 1. For purposes of compliance certification, Pyramid shall conduct either a semiannual Method 9 source test or a weekly visual survey of visible emissions on the A-63 Planer Shavings Cyclone, A-62 Planer Shavings Cyclone, and Shavings Bin Cyclone.

Under the visual survey option, once per calendar week, during daylight hours, Pyramid shall visually survey the A-63 Planer Shavings Cyclone, A-62 Planer Shavings Cyclone, and Shavings Bin Cyclone for sources of excessive emissions. For the purpose of this survey, excessive emissions are considered to be any visible emissions that meet or exceed 15% opacity. The person conducting the survey does not have to be an EPA Method 9 certified observer. However, the

individual must have been certified as a Method 9 observer within the previous 2 years of the visual survey being performed. If sources of excessive emissions are identified, Pyramid shall immediately conduct a Method 9 or take corrective action to contain or minimize the source of emissions. If corrective actions are taken, then Pyramid shall immediately conduct a subsequent visual survey to monitor compliance. The person conducting the visual survey shall record the results of the survey in a log, including any corrective action taken. Conducting a visual survey does not relieve Pyramid of a liability for a violation determined using Method 9 (ARM 17.8.101(27)).

If visual surveys are not conducted once per calendar week, as specified above during the reporting period, Pyramid shall perform Method 9 source tests for the A-63 Planer Shavings Cyclone, A-62 Planer Shavings Cyclone, and Shavings Bin Cyclone for that reporting period. Method 9 source tests must be performed in accordance with the Montana Source Test Protocol and Procedures Manual, except that prior notification of the test is not required. Each observation period must be a minimum of 6 minutes unless any one reading is 20% or greater, then the observation period must be a minimum of 20 minutes or until a violation of the standard has been documented, whichever is a shorter period of time (ARM 17.8.1213).

- E.4. As required by the Department and Section III.A.1, Pyramid shall perform a Method 5 test or other approved test in accordance with the Montana Source Test Protocol and Procedures Manual when requested by the Department to monitor compliance with Section III.E.2 (ARM 17.8.106, ARM 17.8.1213, and APCP 5.102).

Recordkeeping

- E.5. All source test recordkeeping shall be performed in accordance with the test method used and the Montana Source Test Protocol and Procedures Manual. If visual surveys are performed, Pyramid shall maintain a log to verify that the visual surveys were performed as specified in Section III.E.3. Each log entry must include the date, time, results of survey, and observer's initials. Whether visual surveys or Method 9 source tests are conducted, if any corrective action is required, the time, date, observer's initials, and any preventative or corrective action taken must be recorded in the log (ARM 17.8.106, ARM 17.8.1212, and APCP 5.102).

Reporting

- E.6. All source test reports must be submitted to the Department in accordance with the Montana Source Test Protocol and Procedures Manual (ARM 17.8.106, ARM 17.8.1212, and APCP 5.102).
- E.7. The annual compliance certification report required by Section V.B must contain a certification statement for the above applicable requirements. The semiannual reporting shall provide (ARM 17.8.1212):
- a. A summary of results of the last source testing that was performed;
 - b. Verification that the visual surveys were performed and logged as specified by Section III.E.5 or Method 9 source test results; and
 - c. Verification that a log of corrective actions was maintained as specified by Section III.E.5.

F. EU025: Unpaved Road Dust Emissions

Condition(s)	Pollutant/Parameter	Permit Limit	Compliance Demonstration Method Frequency		Reporting Requirements
F.1, F.2, F.3, F.4, F.5, F.6, F.7	Opacity	20% and Reasonable Precautions	Method 9	As Required by the Department and Section III.A.1	Semi-Annual
			Visual Surveys	Weekly	Semi-Annual
			Water/ Chemical Suppressants	As needed	Semiannually

Conditions

- F.1. Pyramid shall not cause or authorize the production, handling, transportation, or storage of any material unless reasonable precautions to control emissions of particulate matter are taken. Such emissions of airborne particulate from any stationary source shall not exhibit an opacity of 20% or greater averaged over 6 consecutive minutes (ARM 17.8.308 (1) and APCP 6.504(2)).
- F.2. Pyramid shall not cause or authorize the use of any street, road, or parking lot without taking reasonable precautions to control emissions of airborne particulate matter (ARM 17.8.308(2) and APCP 8.102(3)).

Compliance Demonstration

- F.3. Opacity is monitored in accordance with the requirements of 40 CFR Part 60, Appendix A, Method 9, or by an in-stack transmissometer complying with 40 CFR Part 60, Appendix B, Performance Specification 1. For purposes of compliance certification, Pyramid shall conduct either a semiannual Method 9 source test or a weekly visual survey of visible emissions on each significant stretch of unpaved road.

Under the visual survey option, once per calendar week, during daylight hours, Pyramid shall visually survey each stretch of unpaved road for any sources of excessive emissions. For the purpose of this survey, excessive emissions are considered to be any visible emissions that meet or exceed 15% opacity. The person conducting the survey does not have to be an EPA Method 9 certified observer. However, the individual must have been certified as a Method 9 observer within the previous 2 years of the visual survey being performed. If sources of excessive emissions are identified, Pyramid shall immediately conduct a Method 9 or take corrective action to contain or minimize the source of emissions. If corrective actions are taken, then Pyramid shall immediately conduct a subsequent visual survey to monitor compliance. The person conducting the visual survey shall record the results of the survey in a log, including any corrective action taken. Conducting a visual survey does not relieve Pyramid of the liability for a violation determined using Method 9 (ARM 17.8.101(27)).

If the visual surveys are not performed once per calendar week as specified above during the reporting period, then Pyramid shall perform the Method 9 source tests for vehicular traffic on each stretch of unpaved road for that reporting period. The Method 9 source tests must be performed in accordance with the Montana Source Test Protocol and Procedures Manual, except that prior notification of the test is not required. Each observation period must be a minimum of 6

minutes unless any one reading is 20% or greater, then the observation period must be a minimum of 20 minutes or until a violation of the standard has been documented, whichever is a shorter period of time (ARM 17.8.1213).

- F.4. Pyramid shall treat all unpaved portions of the haul roads, access roads, parking lots, and general plant area with water and/or chemical dust suppressants as necessary to maintain compliance with ARM 17.8.308 (ARM 17.8.1213).

Recordkeeping

- F.5. All source test recordkeeping shall be performed in accordance with the test method used and the Montana Source Test Protocol and Procedures Manual. If visual surveys are performed, Pyramid shall maintain a log to verify that the visual surveys were performed as specified in Section III.F.3. Each log entry must include the date, time, the results of the survey, and observer's initials. Whether visual surveys or Method 9 source tests are conducted, if any corrective action is required, the time, date, observer's initials, and any preventive or corrective action taken must be recorded in the log. When water and chemical dust suppressants are used to control fugitive dust emissions, the log must include what was applied, a description of the area of application, and the amount of application in gallons (ARM 17.8.106, ARM 17.8.1212, and APCP 5.102).

Reporting

- F.6. All source test reports must be submitted to the Department in accordance with the Montana Source Test Protocol and Procedures Manual (ARM 17.8.106, ARM 17.8.1212, and APCP 5.102).
- F.7. The annual compliance certification report required by Section V.B must contain a certification statement for the above applicable requirements. The semiannual reporting shall provide (ARM 17.8.1212):
- a. Verification that the visual surveys were performed and logged as specified by Section III.F.5 or Method 9 source test results;
 - b. Verification that corrective actions were performed and logged as specified by Section III.F.5; and
 - c. Verification that water and chemical dust suppressant information was recorded in the log as specified by Section III.F.5.

G. EU031: York/Shipley Hog Fuel Boiler (12,000 lbs of steam/hour)

Condition(s)	Pollutant/Parameter	Permit Limit	Compliance Demonstration		Reporting Requirements
			Method	Frequency	
G.1, G.2, G.6, G.11, G.12, G.13	Opacity	20%	Method 9	As Required by the Department and Section III.A.1	Semi-Annual
G.3, G.7, G.11, G.12, G.13	Particulate Matter	4.8 lb/hr	Method 5	Within 180 days of initial start-up and as required by the Department and Section III.A.1 thereafter	Semi-Annual
G.4, G.8, G.10, G.13	Sulfur in Fuel	1lb/MMBtu fired	Recordkeeping	Ongoing	Semi-Annual
G.5, G.9, G.11, G.12, G.13	CO	12.1 lb/hr	Method 10	Within 180 days of initial start-up and every 5 years thereafter	Semi-Annual

Conditions

- G.1. Pyramid shall not cause or authorize emissions to be discharged into the outdoor atmosphere from any source that exhibit an opacity of 20% or greater averaged over six consecutive minutes (ARM 17.8.304(2) and APCP 6.504(2)).
- G.2. During the building of new fires, cleaning of grates, or soot blowing, ARM 17.8.304(2) applies except that a maximum average opacity of 60% is permissible for not more than one 4-minute period in any 60 consecutive minutes (ARM 17.8.304(3) and APCP 6.504(3)).
- G.3. Particulate emissions from the York/Shipley Boiler shall not exceed 4.8 lb/hr (ARM 17.8.749, APCP 6.501(2), and APCP 6.501(3)).
- G.4. Pyramid shall not burn liquid or solid fuels containing sulfur in excess of 1 lb/MMBtu fired (ARM 17.8.322(4) and APCP 10.201).
- G.5. CO emissions from the York/Shipley Boiler shall not exceed 12.1 lb/hr (ARM 17.8.749, APCP 6.501(2), and APCP 6.103(1)).

Compliance Demonstration

- G.6. As required by the Department and Section III.A.1, a Method 9 test must be performed in accordance with the Montana Source Test Protocol and Procedures Manual. The Method 9 test or other Department approved method test must be used to monitor compliance with the 20% opacity limit. Each observation period shall be a minimum of 6 minutes or until a violation of the standard has been documented, whichever is a shorter period of time (ARM 17.8.106, ARM 17.8.1213, and APCP 5.102).
- G.7. Pyramid shall perform a Method 5 test or other approved test in accordance with the Montana Source Test Protocol and Procedures Manual to monitor compliance with the particulate limit contained in Section III.G.3. The initial Method 5 test shall be conducted within 180 days of start-up. Pyramid shall conduct subsequent Method 5 testing as required by the Department and Section III.A.1 (ARM 17.8.106, ARM 17.8.1213, and APCP 5.102).

- G.8. Pyramid may combust only wood waste in the boiler, except for boiler start-up, when a flame accelerant or oil may be utilized (ARM 17.8.1213).
- G.9. Pyramid shall perform a Method 10 test or other approved test in accordance with the Montana Source Test Protocol and Procedures Manual to monitor compliance with the CO limit contained in Section III.G.5. The initial Method 10 test shall be conducted within 180 days of start-up and continue on an every 5-year basis or according to another testing/monitoring schedule as may be approved by the Department (ARM 17.8.106, ARM 17.8.749, ARM 17.8.1213, APCP 5.102, and APCP 6.103(1)).

Recordkeeping

- G.10. Pyramid shall maintain, on site, a log of any material combusted in the boiler other than wood waste. The log must include the date, time, material, and quantity combusted in the boiler (ARM 17.8.1212).
- G.11. All compliance source test recordkeeping shall be performed in accordance with the test method used and the Montana Source Test Protocol and Procedures Manual, and shall be maintained on site (ARM 17.8.106, ARM 17.8.1212, and APCP 5.102).

Reporting

- G.12. Any compliance source test reports must be submitted in accordance with the Montana Source Test Protocol and Procedures Manual (ARM 17.8.106, ARM 17.8.1212, and APCP 5.102).
- G.13. The annual compliance certification report required by Section V.B must contain a certification statement for the above applicable requirements. The semiannual reporting shall provide (ARM 17.8.1212):
 - a. A summary of results of the last source testing that was performed; and
 - b. Verification that log required by Section III.G.10 was maintained.

SECTION IV. NON-APPLICABLE REQUIREMENTS

Air Quality Administrative Rules of Montana (ARM) and Federal Regulations identified as not applicable to the facility or to a specific emissions unit at the time of the permit issuance are listed below (ARM 17.8.1214). The following list does not preclude the need to comply with any new requirements that may become applicable during the permit term.

A. Facility-Wide

The following table contains non-applicable requirements that are administered by the Air Resources Management Bureau of the Department of Environmental Quality.

Rule Citation		Reason
State	Federal	
ARM 17.8.321 ARM 17.8.323 ARM 17.8.610		These rules are not applicable because the facility is not listed in the source category cited in the rules.
ARM 17.8.316 ARM 17.8.320		These rules are not applicable because this facility does not have these emission units.
ARM 17.8.1106 ARM 17.8.1110 ARM 17.8.1111		These rules are not applicable because the facility is not classified as a major stationary source.
ARM 17.8.1301 <i>et seq.</i> ARM 17.8.1401 <i>et seq.</i>		This section establishes rules between the Department and other state and federal agencies.
ARM 17.8.1504 - 1515		This facility is not required to perform any Compliance Assurance Monitoring because this facility does not contain: a pollutant-specific emissions unit whose uncontrolled emissions exceed 100 tons per year; contains an emission limit; and, uses an air pollution control device to meet that limit. Therefore, this regulation is not applicable.
	40 CFR 60.7, 8, 11, 13, 14, 15, & 18	This facility is not in this source category.

Rule Citation		Reason
State	Federal	
	40 CFR 60, Subparts C, Cb, Cc, Cd 40 CFR 60, Subparts D, Da, Db, Dc 40 CFR 60, Subparts E, Ea, Eb, Ec 40 CFR 60, Subparts F-J 40 CFR 60, Subparts K, Ka, Kb 40 CFR 60, Subparts L-Z 40 CFR 60, Subparts AA-EE 40 CFR 60, Subparts GG-HH 40 CFR 60, Subparts KK-NN 40 CFR 60, Subparts PP-XX 40 CFR 60, Subparts AAA-BBB 40 CFR 60, Subparts DDD 40 CFR 60, Subparts FFF-LLL 40 CFR 60, Subparts NNN-WWW 40 CFR 60, Subparts AAAA - DDDD 40 CFR 61, Subparts B-F 40 CFR 61, Subparts H-R 40 CFR 61, Subparts T, V, W, Y 40 CFR 61, Subparts BB and FF 40 CFR 63, Subparts A and B 40 CFR 63, Subparts F-I 40 CFR 63, Subparts L-U 40 CFR 63, Subparts W-Y 40 CFR 63, Subparts AA-EE 40 CFR 63, Subparts GG-MM 40 CFR 63, Subparts OO-WW 40 CFR 63, Subpart YY 40 CFR 63, Subparts CCC-EEE 40 CFR 63, Subparts GGG-JJJ 40 CFR 63, Subparts LLL-RRR 40 CFR 63, Subparts TTT-VVV 40 CFR 63, Subpart XXX 40 CFR 63, Subpart CCCC 40 CFR 63, Subparts GGGG-HHHH 40 CFR 63, Subparts SSSS-VVVV 40 CFR 64	This facility is not an “affected facility” as defined by this subpart.
	40 CFR 72 through 78	These requirements are not applicable because the facility is not an affected source as defined by the acid rain regulations.
	40 CFR 68	The following rule is not applicable because the facility does not meet the threshold quantity for any regulated substance.

B. Emission Units

The permit application identified applicable requirements: non-applicable requirements for individual or specific emission units were not listed. The Department has listed all non-applicable requirements in Section IV.A, these requirements relate to each specific unit, as well as facility wide.

SECTION V. GENERAL PERMIT CONDITIONS

A. Compliance Requirements

ARM 17.8, Subchapter 12, Operating Permit Program §1210(2)(a)-(c)&(e), §1206(6)(c)&(b)

1. The permittee must comply with all conditions of the permit. Any noncompliance with the terms or conditions of the permit constitutes a violation of the Montana Clean Air Act, and may result in enforcement action, permit modification, revocation and reissuance, or termination, or denial of a permit renewal application under ARM Title 17, Chapter 8, Subchapter 12.
2. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition.
3. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. If appropriate, this factor may be considered as a mitigating factor in assessing a penalty for noncompliance with an applicable requirement if the source demonstrates that both the health, safety or environmental impacts of halting or reducing operations would be more serious than the impacts of continuing operations, and that such health, safety or environmental impacts were unforeseeable and could not have otherwise been avoided.
4. The permittee shall furnish to the Department, within a reasonable time set by the Department (not to be less than 15 days), any information that the Department may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit, or to determine compliance with the permit. Upon request, the permittee shall also furnish to the Department copies of those records that are required to be kept pursuant to the terms of the permit. This subsection does not impair or otherwise limit the right of the permittee to assert the confidentiality of the information requested by the Department, as provided in 75-2-105, MCA.
5. Any schedule of compliance for applicable requirements with which the source is not in compliance with at the time of permit issuance shall be supplemental to, and shall not sanction noncompliance with, the applicable requirements on which it was based.
6. For applicable requirements that will become effective during the permit term, the source shall meet such requirements on a timely basis unless a more detailed plan or schedule is required by the applicable requirement or the Department.

B. Certification Requirements

ARM 17.8, Subchapter 12, Operating Permit Program §1207 and §1213(7)(a)&(c)-(d)

1. Any application form, report, or compliance certification submitted pursuant to ARM Title 17, Chapter 8, Subchapter 12, shall contain certification by a responsible official of truth, accuracy and completeness. This certification and any other certification required under ARM Title 17, Chapter 8, Subchapter 12, shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate and complete.

2. Compliance certifications shall be submitted by February 15 of each year, or more frequently if otherwise specified in an applicable requirement or elsewhere in the permit. Each certification must include the required information for the previous calendar year (i.e., January 1 – December 31).
3. Compliance certifications shall include the following:
 - a. The identification of each term or condition of the permit that is the basis of the certification;
 - b. The identification of the method(s) or other means used by the owner or operator for determining the status of compliance with each term and condition during the certification period, consistent with ARM 17.8.1212;
 - c. The status of compliance with each term and condition for the period covered by the certification, *including whether compliance during the period was continuous or intermittent* (based on the method or means identified in ARM 17.8.1213(7)(c)(ii), as described above); and
 - d. Such other facts as the Department may require to determine the compliance status of the source.
4. All compliance certifications must be submitted to the Environmental Protection Agency, as well as to the Department, at the addresses listed in the Notification Addresses Appendix of this permit.

C. Permit Shield

ARM 17.8, Subchapter 12, Operating Permit Program §1214(1)-(4)

1. The applicable requirements and non-federally enforceable requirements are included and specifically identified in this permit and the permit includes a precise summary of the requirements not applicable to the source. Compliance with the conditions of the permit shall be deemed compliance with any applicable requirements and any non-federally enforceable requirements as of the date of permit issuance.
2. The permit shield described in 1 above shall remain in effect during the appeal of any permit action (renewal, revision, reopening, or revocation and reissuance) to the Board of Environmental Review (Board), until such time as the Board renders its final decision.
3. Nothing in this permit alters or affects the following:
 - a. The provisions of Sec. 7603 of the FCAA, including the authority of the administrator under that section;
 - b. The liability of an owner or operator of a source for any violation of applicable requirements prior to or at the time of permit issuance;
 - c. The applicable requirements of the Acid Rain Program, consistent with Sec. 7651g(a) of the FCAA;

- d. The ability of the administrator to obtain information from a source pursuant to Sec. 7414 of the FCAA;
 - e. The ability of the Department to obtain information from a source pursuant to the Montana Clean Air Act, Title 75, Chapter 2, MCA;
 - f. The emergency powers of the Department under the Montana Clean Air Act, Title 75, Chapter 2, MCA; and
 - g. The ability of the Department to establish or revise requirements for the use of Reasonably Available Control Technology (RACT) as defined in ARM Title 17, Chapter 8. However, if the inclusion of a RACT into the permit pursuant to ARM Title 17, Chapter 8, Subchapter 12, is appealed to the Board, the permit shield, as it applies to the source's existing permit, shall remain in effect until such time as the Board has rendered its final decision.
4. Nothing in this permit alters or affects the ability of the Department to take enforcement action for a violation of an applicable requirement or permit term demonstrated pursuant to ARM 17.8.106, Source Testing Protocol.
 5. Pursuant to ARM 17.8.132, for the purpose of submitting a compliance certification, nothing in these rules shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether a source would have been in compliance. However, when compliance or noncompliance is demonstrated by a test or procedure provided by permit or other applicable requirements, the source shall then be presumed to be in compliance or noncompliance unless that presumption is overcome by other relevant credible evidence.
 6. The permit shield will not extend to minor permit modifications or changes not requiring a permit revision (see Sections I & J).
 7. The permit shield will extend to significant permit modifications and transfer or assignment of ownership (see Sections K & N).

D. Monitoring, Recordkeeping, and Reporting Requirements

ARM 17.8, Subchapter 12, Operating Permit Program §1212(2)&(3)

1. Unless otherwise provided in this permit, the permittee shall maintain compliance monitoring records that include the following information:
 - a. The date, place as defined in the permit, and time of sampling or measurement;
 - b. The date(s) analyses were performed;
 - c. The company or entity that performed the analyses;
 - d. The analytical techniques or methods used;
 - e. The results of such analyses; and
 - f. The operating conditions at the time of sampling or measurement.

2. The permittee shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, report, or application. Support information includes all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by the permit. All monitoring data, support information, and required reports and summaries may be maintained in computerized form at the plant site if the information is made available to Department personnel upon request, which may be for either hard copies or computerized format. Strip-charts must be maintained in their original form at the plant site and shall be made available to Department personnel upon request.
3. The permittee shall submit to the Department, at the addresses located in the Notification Addresses Appendix of this permit, reports of any required monitoring by February 15 and August 15 of each year, or more frequently if otherwise specified in an applicable requirement or elsewhere in the permit. The monitoring report submitted on February 15 of each year must include the required monitoring information for the period of July 1 through December 31 of the previous year. The monitoring report submitted on August 15 of each year must include the required monitoring information for the period of January 1 through June 30 of the current year. All instances of deviations from the permit requirements must be clearly identified in such reports. All required reports must be certified by a responsible official, consistent with ARM 17.8.1207.

E. Prompt Deviation Reporting

ARM 17.8, Subchapter 12, Operating Permit Program §1212(3)(c)

The permittee shall promptly report deviations from permit requirements, including those attributable to upset conditions as defined in the permit, the probable cause of such deviations, and any corrective actions or preventive measures taken. To be considered prompt, deviations shall be reported as part of the routine reporting requirements under ARM 17.8.1212(3)(b) and, if applicable, in accordance with the malfunction reporting requirements under ARM 17.8.110, unless otherwise specified in an applicable requirement.

F. Emergency Provisions

ARM 17.8, Subchapter 12, Operating Permit Program §1201(13) and §1214(5), (6)&(8)

1. An “emergency” means any situation arising from sudden and reasonably unforeseeable events beyond the control of the source, including acts of God, which situation requires immediate corrective action to restore normal operation and causes the source to exceed a technology-based emission limitation under this permit due to the unavoidable increases in emissions attributable to the emergency. An emergency shall not include noncompliance to the extent caused by improperly designed equipment, lack of reasonable preventive maintenance, careless or improper operation, or operator error.
2. An emergency constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the permittee demonstrates through properly signed, contemporaneous logs, or other relevant evidence, that:
 - a. An emergency occurred and the permittee can identify the cause(s) of the emergency;
 - b. The permitted facility was at the time being properly operated;

- c. During the period of the emergency the permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in the permit; and
 - d. The permittee submitted notice of the emergency to the Department within 2 working days of the time when emission limitations were exceeded due to the emergency. This notice fulfills the requirements of ARM 17.8.1212(3)(c). This notice must contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken.
3. These emergency provisions are in addition to any emergency, malfunction or upset provision contained in any applicable requirement.

G. Inspection and Entry

ARM 17.8, Subchapter 12, Operating Permit Program §1213(3)&(4)

1. Upon presentation of credentials and other requirements as may be required by law, the permittee shall allow the Department, the administrator, or an authorized representative (including an authorized contractor acting as a representative of the Department or the administrator) to perform the following:
 - a. Enter the premises where a source required to obtain a permit is located or emissions-related activity is conducted, or where records must be kept under the conditions of the permit;
 - b. Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
 - c. Inspect at reasonable times any facilities, emission units, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - d. As authorized by the Montana Clean Air Act and rules promulgated thereunder, sample or monitor, at reasonable times, any substances or parameters at any location for the purpose of assuring compliance with the permit or applicable requirements.
2. The permittee shall inform the inspector of all workplace safety rules or requirements at the time of inspection. This section shall not limit in any manner the Department's statutory right of entry and inspection as provided for in 75-2-403, MCA.

H. Fee Payment

ARM 17.8, Subchapter 12, Operating Permit Program §1210(2)(f) and ARM 17.8, Subchapter 5, Air Quality Permit Application, Operation, and Open Burning Fees §505(3)-(5) (STATE ONLY)

1. The permittee must pay application and operating fees, pursuant to ARM Title 17, Chapter 8, Subchapter 5.
2. Annually, the Department shall provide the permittee with written notice of the amount of the fee and the basis for the fee assessment. The air quality operation fee is due 30 days after receipt of the notice, unless the fee assessment is appealed pursuant to ARM 17.8.511. If any portion of the fee is not appealed, that portion of the fee that is not appealed is due 30 days after receipt of the notice. Any remaining fee, which may be due after the completion of an appeal, is due immediately upon issuance of the Board's decision or upon completion of any judicial review of the Board's decision.

3. If the permittee fails to pay the required fee (or any required portion of an appealed fee) within 90 days of the due date of the fee, the Department may impose an additional assessment of 15% of the fee (or any required portion of an appealed fee) or \$100, whichever is greater, plus interest on the fee (or any required portion of an appealed fee), computed at the interest rate established under 15-31-510(3), MCA.

I. Minor Permit Modifications

ARM 17.8, Subchapter 12, Operating Permit Program §1226(3)&(11)

1. An application for a minor permit modification need only address in detail those portions of the permit application that require revision, updating, supplementation, or deletion, and may reference any required information that has been previously submitted.
2. The permit shield under ARM 17.8.1214 will not extend to any minor modifications processed pursuant to ARM 17.8.1226.

J. Changes Not Requiring Permit Revision

ARM 17.8, Subchapter 12, Operating Permit Program §1224(1)-(3), (5)&(6)

1. The permittee is authorized to make changes within the facility as described below, provided the following conditions are met:
 - a. The proposed changes do not require the permittee to obtain an air quality preconstruction permit under ARM Title 17, Chapter 8, Subchapter 7;
 - b. The proposed changes are not modifications under Title I of the FCAA, or as defined in ARM Title 17, Chapter 8, Subchapters 8, 9, or 10;
 - c. The emissions resulting from the proposed changes do not exceed the emissions allowable under this permit, whether expressed as a rate of emissions or in total emissions;
 - d. The proposed changes do not alter permit terms that are necessary to enforce applicable emission limitations on emission units covered by the permit; and
 - e. The facility provides the administrator and the Department with written notification at least 7 days prior to making the proposed changes.
2. The permittee and the Department shall attach each notice provided pursuant to 1.e above to their respective copies of this permit.
3. Pursuant to the conditions above, the permittee is authorized to make Section 502(b)(10) changes, as defined in ARM 17.8.1201(30), without a permit revision. For each such change, the written notification required under 1.e above shall include a description of the change within the source, the date on which the change will occur, any change in emissions, and any permit term or condition that is no longer applicable as a result of the change.
4. The permittee may make a change not specifically addressed or prohibited by the permit terms and conditions without requiring a permit revision, provided the following conditions are met:
 - a. Each proposed change does not weaken the enforceability of any existing permit conditions;

- b. The Department has not objected to such change;
 - c. Each proposed change meets all applicable requirements and does not violate any existing permit term or condition; and
 - d. The permittee provides contemporaneous written notice to the Department and the administrator of each change that is above the level for insignificant emission units as defined in ARM 17.8.1201(22) and 17.8.1206(3), and the written notice describes each such change, including the date of the change, any change in emissions, pollutants emitted, and any applicable requirement that would apply as a result of the change.
5. The permit shield authorized by ARM 17.8.1214 shall not apply to changes made pursuant to ARM 17.8.1224(3) and (5), but is applicable to terms and conditions that allow for increases and decreases in emissions pursuant to ARM 17.8.1224(4).

K. Significant Permit Modifications

ARM 17.8, Subchapter 12, Operating Permit Program §1227(1), (3)&(4)

- 1. The modification procedures set forth in 2 below must be used for any application requesting a significant modification of this permit. Significant modifications include the following:
 - a. Any permit modification that does not qualify as either a minor modification or as an administrative permit amendment;
 - b. Every significant change in existing permit monitoring terms or conditions;
 - c. Every relaxation of permit reporting or recordkeeping terms or conditions that limit the Department's ability to determine compliance with any applicable rule, consistent with the requirements of the rule; or
 - d. Any other change determined by the Department to be significant.
- 2. Significant modifications shall meet all requirements of ARM Title 17, Chapter 8, including those for applications, public participation, and review by affected states and the administrator, as they apply to permit issuance and renewal, except that an application for a significant permit modification need only address in detail those portions of the permit application that require revision, updating, supplementation or deletion.
- 3. The permit shield provided for in ARM 17.8.1214 shall extend to significant modifications.

L. Reopening for Cause

ARM 17.8, Subchapter 12, Operating Permit Program §1228(1)&(2)

This permit may be reopened and revised under the following circumstances:

- 1. Additional applicable requirements under the FCAA become applicable to the facility when the permit has a remaining term of 3 or more years. Reopening and revision of the permit shall be completed not later than 18 months after promulgation of the applicable requirement. No reopening is required under ARM 17.8.1228(1)(a) if the effective date of the applicable requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms or conditions have been extended pursuant to ARM 17.8.1220(12) or 17.8.1221(2);

2. Additional requirements (including excess emission requirements) become applicable to an affected source under the Acid Rain Program. Upon approval by the administrator, excess emission offset plans shall be deemed incorporated into the permit;
3. The Department or the administrator determines that the permit contains a material mistake or that inaccurate statements were made in establishing the emission standards or other terms or conditions of the permit; or
4. The administrator or the Department determines that the permit must be revised or revoked and reissued to ensure compliance with the applicable requirements.

M. Permit Expiration and Renewal

ARM 17.8, Subchapter 12, Operating Permit Program §1210(2)(g), §1220(11)&(12), and §1205(2)(d)

1. This permit is issued for a fixed term of 5 years.
2. Renewal of this permit is subject to the same procedural requirements that apply to permit issuance, including those for application, content, public participation, and affected state and administrator review.
3. Expiration of this permit terminates the permittee's right to operate unless a timely and administratively complete renewal application has been submitted consistent with ARM 17.8.1221 and 17.8.1205(2)(d). If a timely and administratively complete application has been submitted, all terms and conditions of the permit, including the application shield, remain in effect after the permit expires until the permit renewal has been issued or denied.
4. For renewal, the permittee shall submit a complete air quality operating permit application to the Department not later than 6 months prior to the expiration of this permit, unless otherwise specified. If necessary to ensure that the terms of the existing permit will not lapse before renewal, the Department may specify, in writing to the permittee, a longer time period for submission of the renewal application. Such written notification must be provided at least 1 year before the renewal application due date established in the existing permit.

N. Severability Clause

ARM 17.8, Subchapter 12, Operating Permit Program §1210(2)(i)&(l)

1. The administrative appeal or subsequent judicial review of the issuance by the Department of an initial permit under this subchapter shall not impair in any manner the underlying applicability of all applicable requirements, and such requirements continue to apply as if a final permit decision had not been reached by the Department.
2. If any provision of a permit is found to be invalid, all valid parts that are severable from the invalid part remain in effect. If a provision of a permit is invalid in one or more of its applications, the provision remains in effect in all valid applications that are severable from the invalid applications.

O. Transfer or Assignment of Ownership

ARM 17.8, Subchapter 12, Operating Permit Program §1225(2)&(4)

1. If an administrative permit amendment involves a change in ownership or operational control, the applicant must include in its request to the Department a written agreement containing a specific date for the transfer of permit responsibility, coverage and liability between the current and new permittee.

2. The permit shield provided for in ARM17.8.1214 shall not extend to administrative permit amendments.

P. Emissions Trading, Marketable Permits, Economic Incentives

ARM 17.8, Subchapter 12, Operating Permit Program §1226(2)

Notwithstanding ARM 17.8.1226(1) and (7), minor air quality operating permit modification procedures may be used for permit modifications involving the use of economic incentives, marketable permits, emissions trading, and other similar approaches, to the extent that such minor permit modification procedures are explicitly provided for in the Montana State Implementation Plan or in applicable requirements promulgated by the administrator.

Q. No Property Rights Conveyed

ARM 17.8, Subchapter 12, Operating Permit Program §1210(2)(d)

This permit does not convey any property rights of any sort, or any exclusive privilege.

R. Testing Requirements

ARM 17.8, Subchapter 1, General Provisions §105

The permittee shall comply with ARM 17.8.105.

S. Source Testing Protocol

ARM 17.8, Subchapter 1, General Provisions §106

The permittee shall comply with ARM 17.8.106.

T. Malfunctions

ARM 17.8, Subchapter 1, General Provisions §110

The permittee shall comply with ARM 17.8.110.

U. Circumvention

ARM 17.8, Subchapter 1, General Provisions §111

The permittee shall comply with ARM 17.8.111.

V. Motor Vehicles

ARM 17.8, Subchapter 3, Emission Standards §325

The permittee shall comply with ARM 17.8.325.

W. Annual Emissions Inventory

ARM 17.8, Subchapter 5, Air Quality Permit Application, Operation and Open Burning Fees §505 (STATE ONLY)

The permittee shall supply the Department with annual production and other information for all emission units necessary to calculate actual or estimated actual amount of air pollutants emitted during each calendar year. Information shall be gathered on a calendar-year basis and submitted to the Department by the date required in the emission inventory request, unless otherwise specified in this permit. Information shall be in the units required by the Department.

X. Open Burning

ARM 17.8, Subchapter 6, Open Burning §604, 605 and 606

The permittee shall comply with ARM 17.8.604, 605 and 606.

Y. Montana Air Quality Permits

ARM 17.8, Subchapter 7, Permit, Construction and Operation of Air Contaminant Sources §745 and 764 (ARM 17.8.745(1) and 764(1)(b) are STATE ENFORCEABLE ONLY until approval by the EPA as part of the SIP)

1. Except as specified, no person shall construct, install, alter or use any air contaminant source or stack associated with any source without first obtaining a permit from the Department or Board. A permit is not required for those sources or stacks as specified by ARM 17.8.744(1)(a)-(k).
2. The permittee shall comply with ARM 17.8.743, 744, 745, 748, and 764.
3. ARM 17.8.745(1) specifies de minimis changes as construction or changed conditions of operation at a facility holding an air quality preconstruction permit issued under Chapter 8 that does not increase the facility's potential to emit by more than 15 tons per year of any pollutant, except (STATE ENFORCEABLE ONLY until approved by the EPA as part of the SIP):
 - a. Any construction or changed condition that would violate any condition in the facility's existing air quality preconstruction permit or any applicable rule contained in Chapter 8 is prohibited, except as provided in ARM 17.8.745(2);
 - b. Any construction or changed conditions of operation that would qualify as a major modification under Subchapters 8, 9 or 10 of Chapter 8;
 - c. Any construction or changed condition of operation that would affect the plume rise or dispersion characteristic of emissions that would cause or contribute to a violation of an ambient air quality standard or ambient air increment as defined in ARM 17.8.804;
 - d. Any construction or improvement project with a potential to emit more than 15 tons per year may not be artificially split into smaller projects to avoid air quality preconstruction permitting; or
 - e. Emission reductions obtained through offsetting within a facility are not included when determining the potential emission increase from construction or changed conditions of operation, unless such reductions are made federally enforceable.
4. Any facility making a de minimis change pursuant to ARM 17.8.745(1) shall notify the Department if the change would include a change in control equipment, stack height, stack diameter, stack gas temperature, source location or fuel specifications, or would result in an increase in source capacity above its permitted operation or the addition of a new emission unit. The notice must be submitted, in writing, 10 days prior to start up or use of the proposed de minimis change, or as soon as reasonably practicable in the event of an unanticipated circumstance causing the de minimis change, and must include the information requested in ARM 17.8.745(1) (STATE ENFORCEABLE ONLY until approval by the EPA as part of the SIP).

Z. National Emission Standard for Asbestos

40 CFR, Part 61, Subpart M

The permittee shall not conduct any asbestos abatement activities except in accordance with 40 CFR 61, Subpart M (National Emission Standard for Hazardous Air Pollutants for Asbestos).

AA. Asbestos

ARM 17.74, Subchapter 3, General Provisions and Subchapter 4, Fees

The permittee shall comply with ARM 17.74.301, *et seq.*, and ARM 17.74.401, *et seq.* (State only)

BB. Stratospheric Ozone Protection – Servicing of Motor Vehicle Air Conditioners

40 CFR, Part 82, Subpart B

If the permittee performs a service on motor vehicles and this service involves ozone-depleting substance/refrigerant in the motor vehicle air conditioner (MVAC), the permittee is subject to all the applicable requirements as specified in 40 CFR 82, Subpart B.

CC. Stratospheric Ozone Protection – Recycling and Emission Reductions

40 CFR, Part 82, Subpart F

The permittee shall comply with the standards for recycling and emission reductions in 40 CFR 82, Subpart F, except as provided for MVACs in Subpart B:

1. Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to §82.156;
2. Equipment used during the maintenance, service, repair or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to §82.158;
3. Persons performing maintenance, service, repair or disposal of appliances must be certified by an approved technical certification program pursuant to §82.161;
4. Persons disposing of small appliances, MVACs and MVAC-like (as defined at §82.152) appliances must comply with recordkeeping requirements pursuant to §82.166;
5. Persons owning commercial or industrial process refrigeration equipment must comply with the leak repair requirements pursuant to §82.156; and
6. Owners/operators of appliances normally containing 50 or more pounds of refrigerant must keep records of refrigerant purchased and added to such appliances pursuant to §82.166.

DD. Emergency Episode Plan

The permittee shall comply with the requirements contained in Chapter 9.7 of the State of Montana Air Quality Control Implementation Plan.

Each major source emitting 100 tons per year located in a Priority I Air Quality Control Region, shall submit to the Department a legally enforceable Emergency Episode Action Plan (EEAP) that details how the source will curtail emissions during an air pollutant emergency episode. The industrial EEAP shall be in accordance with the Department’s EEAP and shall be submitted according to a timetable developed by the Department, following Priority I reclassification.

EE. Definitions

Terms not otherwise defined in this permit or in the Definitions and Abbreviations Appendix of this permit, shall have the meaning assigned to them in the referenced regulations.

APPENDICES

Appendix A INSIGNIFICANT EMISSION UNITS

Disclaimer: The information in this appendix is not State or Federally enforceable, but is presented to assist Pyramid, the permitting authority, inspectors, and the public.

Pursuant to ARM 17.8.1201(22)(a), an insignificant emission unit means any activity or emissions unit located within a source that: (i) has a potential to emit less than five tons per year of any regulated pollutant; (ii) has a potential to emit less than 500 pounds per year of lead; (iii) has a potential to emit less than 500 pounds per year of hazardous air pollutants listed pursuant to Section 7412 (b) of the FCAA; and (iv) is not regulated by an applicable requirement, other than a generally applicable requirement that applies to all emission units subject to Subchapter 12.

List of Insignificant Activities:

The following table of insignificant sources and/or activities were provided by Pyramid. Because there are no requirements to update such a list, the emission units and/or activities may change from those specified in the table.

Emissions Unit ID	Description
EU004	Hog
EU005	Chip Bin #1 Cyclone
EU006	Chip Silo Cyclone
EU007	Chip Bin #2 Cyclone
EU010	Blow Hog Sawdust Cyclone
EU011	Moulder Surge Bin Cyclone
EU012	Moulder Shavings Bin Cyclone
EU014	Shavings Bin Cyclone
EU015	Debarker
EU016	Bark Handling Fugitives
EU017	Chips Handling Fugitives
EU018	Shavings Loadout Fugitives
EU019	Hog Fuel Handling Fugitives
EU020	Sawdust Handling Fugitives
EU021	Sawmill Chippers
EU022	Cut off Saws
EU023	Building Vents
EU024	Sawdust Storage Pile Fugitives
EU026	Plant-wide Diesel Combustion
EU027	Plant-wide Gasoline Combustion
EU028	Plant-wide Propane Combustion
EU029	Gasoline Fuel Tank Fugitives
EU030	Diesel Fuel Tank Fugitives

Appendix B DEFINITIONS and ABBREVIATIONS

"Act" means the Clean Air Act, as amended, 42 U.S. 7401, *et seq.*

"Administrative permit amendment" means an air quality operating permit revision that:

- (a) Corrects typographical errors;
- (b) Identifies a change in the name, address or phone number of any person identified in the air quality operating permit, or identifies a similar minor administrative change at the source;
- (c) Requires more frequent monitoring or reporting by Pyramid;
- (d) Requires changes in monitoring or reporting requirements that the Department deems to be no less stringent than current monitoring or reporting requirements;
- (e) Allows for a change in ownership or operational control of a source if the Department has determined that no other change in the air quality operating permit is necessary, consistent with ARM 17.8.1225; or
- (f) Incorporates any other type of change that the Department has determined to be similar to those revisions set forth in (a)-(e), above.

"Applicable requirement" means all of the following as they apply to emission units in a source requiring an air quality operating permit (including requirements that have been promulgated or approved by the Department or the administrator through rule making at the time of issuance of the air quality operating permit, but have future-effective compliance dates, provided that such requirements apply to sources covered under the operating permit):

- (a) Any standard, rule, or other requirement, including any requirement contained in a consent decree or judicial or administrative order entered into or issued by the Department, that is contained in the Montana state implementation plan approved or promulgated by the administrator through rule making under Title I of the FCAA;
- (b) Any federally enforceable term, condition or other requirement of any air quality preconstruction permit issued by the Department under Subchapters 7, 8, 9 and 10 of this chapter, or pursuant to regulations approved or promulgated through rule making under Title I of the FCAA, including parts C and D;
- (c) Any standard or other requirement under Section 7411 of the FCAA, including Section 7411(d);
- (d) Any standard or other requirement under Section 7412 of the FCAA, including any requirement concerning accident prevention under Section 7412(r)(7), but excluding the contents of any risk management plan required under Section 7412(r);
- (e) Any standard or other requirement of the acid rain program under Title IV of the FCAA or regulations promulgated thereunder;
- (f) Any requirements established pursuant to Section 7661c(b) or Section 7414(a)(3) of the FCAA;

- (g) Any standard or other requirement governing solid waste incineration, under Section 7429 of the FCAA;
- (h) Any standard or other requirement for consumer and commercial products, under Section 7511b(e) of the FCAA;
- (i) Any standard or other requirement for tank vessels, under Section 7511b(f) of the FCAA;
- (j) Any standard or other requirement of the regulations promulgated to protect stratospheric ozone under Title VI of the FCAA, unless the administrator determines that such requirements need not be contained in an air quality operating permit;
- (k) Any national ambient air quality standard or increment or visibility requirement under part C of Title I of the FCAA, but only as it would apply to temporary sources permitted pursuant to Section 7661c(e) of the FCAA; or
- (l) Any federally enforceable term or condition of any air quality open burning permit issued by the Department under Subchapter 6.

"Department" means the Montana Department of Environmental Quality.

"Excess Emissions" means any visible emissions from a stack or source, viewed during the visual surveys, that meets or exceeds 15% opacity (or 30% opacity if associated with a 40% opacity limit) during normal operating conditions.

"Emissions unit" means any part or activity of a stationary source that emits or has the potential to emit any regulated air pollutant or any pollutant listed under Section 7412(b) of the FCAA. This term is not meant to alter or affect the definition of the term "unit" for purposes of Title IV of the FCAA.

"FCAA" means the Federal Clean Air Act, as amended.

"Federally enforceable" means all limitations and conditions which are enforceable by the administrator, including those requirements developed pursuant to 40 CFR Parts 60 and 61, requirements within the Montana state implementation plan, and any permit requirement established pursuant to 40 CFR 52.21 or under regulations approved pursuant to 40 CFR Part 51, Subpart I, including operating permits issued under an EPA approved program that is incorporated into the Montana state implementation plan and expressly requires adherence to any permit issued under such program.

"Fugitive emissions" means those emissions that could not reasonably pass through a stack, chimney, vent, or other functionally equivalent opening.

"General air quality operating permit" or "general permit" means an air quality operating permit that meets the requirements of ARM 17.8.1222, covers multiple sources in a source category, and is issued in lieu of individual permits being issued to each source.

"Hazardous air pollutant" means any air pollutant listed as a hazardous air pollutant pursuant to Section 112(b) of the FCAA.

"Non-federally enforceable requirement" means the following as they apply to emission units in a source requiring an air quality operating permit:

- (a) Any standard, rule, or other requirement, including any requirement contained in a consent decree, or judicial or administrative order entered into or issued by the Department, that is not contained in the Montana state implementation plan approved or promulgated by the administrator through rule making under Title I of the FCAA;

- (b) Any term, condition or other requirement contained in any air quality preconstruction permit issued by the Department under Subchapters 7, 8, 9 and 10 of this chapter that is not federally enforceable;
- (c) Does not include any Montana ambient air quality standard contained in Subchapter 2 of this chapter.

"Permittee" means the owner or operator of any source subject to the permitting requirements of this subchapter, as provided in ARM 17.8.1204, that holds a valid air quality operating permit or has submitted a timely and complete permit application for issuance, renewal, amendment, or modification pursuant to this subchapter.

"Regulated air pollutant" means the following:

- (a) Nitrogen oxides or any volatile organic compounds;
- (b) Any pollutant for which a national ambient air quality standard has been promulgated;
- (c) Any pollutant that is subject to any standard promulgated under Section 7411 of the FCAA;
- (d) Any Class I or II substance subject to a standard promulgated under or established by Title VI of the FCAA; or
- (e) Any pollutant subject to a standard or other requirement established or promulgated under Section 7412 of the FCAA, including but not limited to the following:
 - (i) Any pollutant subject to requirements under Section 7412(j) of the FCAA. If the administrator fails to promulgate a standard by the date established in Section 7412(e) of the FCAA, any pollutant for which a subject source would be major shall be considered to be regulated on the date 18 months after the applicable date established in Section 7412(e) of the FCAA;
 - (ii) Any pollutant for which the requirements of Section 7412(g)(2) of the FCAA have been met but only with respect to the individual source subject to Section 7412(g)(2) requirement.

"Responsible official" means one of the following:

- (a) For a corporation: a president, secretary, treasurer, or vice-president of the corporation in charge of a principal business function, or any other person who performs similar policy or decision-making functions for the corporation, or a duly authorized representative of such person if the representative is responsible for the overall operation of one or more manufacturing, production, or operating facilities applying for or subject to a permit and either:
 - (i) The facilities employ more than 250 persons or have gross annual sales or expenditures exceeding \$25 million (in second quarter 1980 dollars); or
 - (ii) The delegation of authority to such representative is approved in advance by the Department.
- (b) For a partnership or sole proprietorship: a general partner or the proprietor, respectively.
- (c) For a municipality, state, federal, or other public agency: either a principal executive officer or ranking elected official. For the purposes of this part, a principal executive officer of a federal agency includes the chief executive officer having responsibility for the overall operations of a principal geographic unit of the agency (e.g., a regional administrator of the environmental protection agency).

- (d) For affected sources: the designated representative in so far as actions, standards, requirements, or prohibitions under Title IV of the FCAA or the regulations promulgated thereunder are concerned, and the designated representative for any other purposes under this subchapter.

Abbreviations:

APCP	Missoula City-County Air Pollution Control Program
ARM	Administrative Rules of Montana
ASTM	American Society of Testing Materials
BACT	Best Available Control Technology
BDT	bone dry tons
BTU	British Thermal Unit
CFR	Code of Federal Regulations
CO	carbon monoxide
DEQ	Department of Environmental Quality
dscf	dry standard cubic foot
dscfm	dry standard cubic foot per minute
EEAP	Emergency Episode Action Plan
EPA	U.S. Environmental Protection Agency
EPA Method	Test methods contained in 40 CFR 60, Appendix A
EU	emissions unit
FCAA	Federal Clean Air Act
gr	grains
HAP	hazardous air pollutant
IEU	insignificant emissions unit
Mbdft	thousand board feet
Method 5	40 CFR 60, Appendix A, Method 5
Method 9	40 CFR 60, Appendix A, Method 9
MMbdft	million board feet
MMBTU	million British Thermal Units
NO _x	oxides of nitrogen
NO ₂	nitrogen dioxide
O ₂	oxygen
Pb	lead
PM	particulate matter
PM10	particulate matter less than 10 microns in size
psi	pounds per square inch
scf	standard cubic feet
SIC	Source Industrial Classification
SO ₂	sulfur dioxide
SO _x	oxides of sulfur
tpy	tons per year
U.S.C.	United States Code
VE	visible emissions
VOC	volatile organic compound

Appendix C NOTIFICATION ADDRESSES

Compliance Notifications:

Montana Department of Environmental Quality
Permitting and Compliance Division
Air Resources Management Bureau
P.O. Box 200901
Helena, MT 59620-0901

United States EPA
Air Program Coordinator
Region VIII, Montana Office
10 W. 15th Street, Suite 3200
Helena, MT 59626

Permit Modifications:

Montana Department of Environmental Quality
Permitting and Compliance Division
Air Resources Management Bureau
P.O. Box 200901
Helena, MT 59620-0901

Office of Partnerships and Regulatory Assistance
Air and Radiation Program
US EPA Region VIII 8P-AR
999 18th Street, Suite 300
Denver, CO 80202-2466

Appendix D AIR QUALITY INSPECTOR INFORMATION

Disclaimer: The information in this appendix is not State or Federally enforceable, but is presented to assist Pyramid, permitting authority, inspectors, and the public.

1. **Direction to Plant:** This Pyramid facility consists of a 95-acre site located in Missoula County and adjacent to the town of Seeley Lake. The legal description of the facility is the SE ¼ of Section 3, Township 16 North, Range 15 West. While traveling on state Highway 83, turn west on Boy Scout Road. The facility is on the south side of the road and there are several access roads to the property.
2. **Safety Equipment Required:** Hard-hat, steel-toed shoes/boots, and hearing protection are required at the facility. A detailed safety manual is available at the site and a Pyramid employee will conduct a safety briefing for any inspector prior to entering the plant area.
3. **Facility Plot Plan:** The facility plot plan was submitted as part of the application submitted on March 21, 1997.