

**MONTANA DEPARTMENT OF
ENVIRONMENTAL QUALITY**

AUTHORIZATION TO DISCHARGE UNDER THE
MONTANA POLLUTANT DISCHARGE ELIMINATION SYSTEM

In compliance with Montana Water Quality Act, Title 75, Chapter 5, Montana Code Annotated (MCA) and the Federal Water Pollution Control Act (the "Clean Water Act"), 33 U.S.C. § 1251 *et seq.*,

Paragon Mining Inc.

is authorized to discharge from its **Paragon Mining Inc. Suction Dredge Project**

located approximately $\frac{1}{2}$ mile below **Canyon Ferry Dam on Hauser Lake**

to five locations in receiving water named **Hauser Lake**,

in accordance with discharge point(s), effluent limitations, monitoring requirements and other conditions set forth herein. Authorization for discharge is limited to those outfalls specifically listed in the permit.

This permit shall become effective on **November 1, 2009**.

This permit and the authorization to discharge shall expire at midnight **October 31, 2014**.

FOR THE MONTANA DEPARTMENT OF
ENVIRONMENTAL QUALITY



Bob Habeck, Chief
Water Protection Bureau
Permitting and Compliance Division

Issuance Date: _____

8/15/13

TABLE OF CONTENTS

Cover Sheet--Issuance and Expiration Dates

- I. EFFLUENT LIMITATIONS, MONITORING REQUIREMENTS & OTHER CONDITIONS..... 3**
 - A. Description of Discharge Points and Mixing Zone..... 3
 - B. Effluent Limitations..... 5
 - C. Monitoring Requirements..... 5
 - D. Special Conditions..... 8
 - E. Compliance Schedule..... 11

- II. MONITORING, RECORDING AND REPORTING REQUIREMENTS..... 12**
 - A. Representative Sampling..... 12
 - B. Monitoring Procedures..... 12
 - C. Penalties for Tampering..... 12
 - D. Reporting of Monitoring Results..... 12
 - E. Compliance Schedules..... 12
 - F. Additional Monitoring by the Permittee..... 13
 - G. Records Contents..... 13
 - H. Retention of Records..... 13
 - I. Twenty-four Hour Notice of Noncompliance Reporting..... 13
 - J. Other Noncompliance Reporting..... 14
 - K. Inspection and Entry..... 14

- III. COMPLIANCE RESPONSIBILITIES..... 16**
 - A. Duty to Comply..... 16
 - B. Penalties for Violations of Permit Conditions..... 16
 - C. Need to Halt or Reduce Activity not a Defense..... 16
 - D. Duty to Mitigate..... 16
 - E. Proper Operation and Maintenance..... 16
 - F. Removed Substances..... 17
 - G. Bypass of Treatment Facilities..... 17
 - H. Upset Conditions..... 18
 - I. Toxic Pollutants..... 18
 - J. Changes in Discharge of Toxic Substances..... 18

- IV. GENERAL REQUIREMENTS..... 20**
 - A. Planned Changes..... 20
 - B. Anticipated Noncompliance..... 20
 - C. Permit Actions..... 20
 - D. Duty to Reapply..... 20
 - E. Duty to Provide Information..... 20
 - F. Other Information..... 20
 - G. Signatory Requirements..... 20
 - H. Penalties for Falsification of Reports..... 21
 - I. Availability of Reports..... 22
 - J. Oil and Hazardous Substance Liability..... 22
 - K. Property or Water Rights..... 22
 - L. Severability..... 22
 - M. Transfers..... 22
 - N. Fees..... 23
 - O. Reopener Provisions..... 23

- V. DEFINITIONS..... 25**

I. EFFLUENT LIMITATIONS, MONITORING REQUIREMENTS & OTHER CONDITIONS

A. Description of Discharge Points and Mixing Zone

The authorization to discharge provided under this permit is limited to those outfalls specially designated below as discharge locations. Discharges at any location not authorized under an MPDES permit is a violation of the Montana Water Quality Act and could subject the person(s) responsible for such discharge to penalties under the Act. Knowingly discharging from an unauthorized location or failing to report an unauthorized discharge within a reasonable time from first learning of an unauthorized discharge could subject such person to criminal penalties as provided under Section 75-5-632 of the Montana Water Quality Act.

<u>Outfall</u>	<u>Description</u>
----------------	--------------------

001	Location: Composed of the three sluice boxes on the 8-inch suction dredge barge discharging into Hauser Lake at the following five locations:
------------	--

S-1: The length of the area is 1,800 feet and the width is 150 feet. The water depth in the area is approximately 16 - 18 feet. The project will be 20 feet from the bank on the west side of Hauser Lake across from Riverside Campground. The latitude is 46° 39' and the longitude is 111° 44', which is located in Township 10N Range 1W Section 4.

S-2: The length of the area is 2,500 feet and the width is 150 feet. The water depth in the area is approximately 16 - 30 feet. The project will be 20 feet from the bank on the west side of Hauser Lake up from Brown's Gulch. The latitude is 46° 39' and the longitude is 111° 46' which is located in Township 10N Range 1W Sections 5 and 6.

S-3: The length of the area is 2,250 feet and the width is 150 feet. The water depth in the area is approximately 16 - 23 feet. The project will be 20 feet from the bank on the west side of Hauser Lake and is 600 feet up from Spokane Creek Bay. The latitude is 46° 39' 15" and the longitude is 111° 47' 45" which is located in Township 10N Range 2W Section 1 and Township 11N Range 2W Section 36.

S-4: The length of the area is 6,500 feet and the width is 600-800 feet. The water depth in the area is approximately 26 feet. The project will be 10 - 20 feet from the bank on the east side of Hauser Lake and goes from Devil's Elbow up to Metropolitan bar. The latitude is 46° 41' 30" and the longitude is 111° 48' 45" which is located in Township 11N Range 2W Sections 23, 24, and 26.

S-5: The length of the area is 650 feet and the width is 125 feet. The water depth in the area is approximately 30 - 50 feet. The project will be 35 feet from the bank on the east side of Hauser Lake and is outside of the Trout Creek bay. The latitude is 46° 42' 45" and the longitude is 111° 48' 30" which is located in Township 11N Range 2W Section 13.

Mixing Zone: The maximum extent of the mixing zone in Hauser Lake for turbidity is 500 feet directly downstream from the 8-inch suction dredge barge.

Treatment Works: none

002

Location: At the end of the three discharge structures (dump chutes) on the 16-inch suction dredge barge discharging into Hauser Lake at the following five locations:

S-1: The length of the area is 1,800 feet and the width is 150 feet. The water depth in the area is approximately 16 - 18 feet. The project will be 20 feet from the bank on the west side of Hauser Lake across from Riverside Campground. The latitude is 46° 39' and the longitude is 111° 44', which is located in Township 10N Range 1W Section 4.

S-2: The length of the area is 2,500 feet and the width is 150 feet. The water depth in the area is approximately 16 - 30 feet. The project will be 20 feet from the bank on the west side of Hauser Lake up from Brown's Gulch. The latitude is 46° 39' and the longitude is 111° 46' which is located in Township 10N Range 1W Sections 5 and 6.

S-3: The length of the area is 2,250 feet and the width is 150 feet. The water depth in the area is approximately 16 - 23 feet. The project will be 20 feet from the bank on the west side of Hauser Lake and is 600 feet up from Spokane Creek Bay. The latitude is 46° 39' 15" and the longitude is 111° 47' 45" which is located in Township 10N Range 2W Section 1 and Township 11N Range 2W Section 36.

S-4: The length of the area is 6,500 feet and the width is 600-800 feet. The water depth in the area is approximately 26 feet. The project will be 10 - 20 feet from the bank on the east side of Hauser Lake and goes from Devil's Elbow up to Metropolitan bar. The latitude is 46° 41' 30" and the longitude is 111° 48' 45" which is located in Township 11N Range 2W Sections 23, 24, and 26.

S-5: The length of the area is 650 feet and the width is 125 feet. The water depth in the area is approximately 30 - 50 feet. The project will be 35 feet from the bank on the east side of Hauser Lake and is outside of the Trout Creek bay. The latitude is 46° 42' 45" and the longitude is 111° 48' 30" which is located in Township 11N Range 2W Section 13.

Mixing Zone: The maximum extent of the mixing zone in Hauser Lake for turbidity is 500 feet directly downstream from the 16-inch suction dredge barge.

Treatment Works: none

B. Effluent Limitations

Outfall 001 and Outfall 002

Beginning on the effective date of this permit and lasting through the term of the permit, the quality of effluent discharged by the facility shall, as a minimum, meet the limitations as set forth below:

1. The maximum net turbidity limit is 5 NTU above the naturally occurring turbidity in Hauser Lake. Net turbidity is calculated by subtracting the turbidity value collected within 4 inches of the water surface in the front of the barge from the turbidity value collected within 4 inches of the water surface at the downstream end of the 500-foot mixing zone. [Turbidity at the end of the 500-foot mixing zone (Downstream) minus Turbidity at the front of barge (Upstream) equals Net turbidity].
2. There shall be no discharge that causes visible oil film (or be present in concentrations at or in excess of 10 mg/L) in the receiving water. If a visual examination of the discharge indicates the presence of hydrocarbons by sheen, film, odor or other sign, the permittee is required to sample for Oil and Grease using EPA Method 1664A or an equivalent method.
3. There shall be no discharge of floating solids or visible foam in other than trace amounts [ARM 17.30 647(1)(b)].
4. The maximum amount of raw material processed in a calendar year must not exceed 50,000 cubic yards.

C. Monitoring Requirements

Outfall 001 and Outfall 002

As a minimum, upon the effective date of this permit, the following constituents shall be monitored at the frequency and with the type of measurement indicated; samples or measurements shall be representative of the volume and nature of the monitored discharge. If no discharge occurs during the entire monitoring period, it shall be stated on the Discharge Monitoring Report Form (EPA No. 3320-1) that no discharge or overflow occurred.

1. Effluent Monitoring
 - a. **Outfall 001 - 8-inch Suction Dredge**

To obtain representative effluent samples, equal volumes of effluent must be obtained from the three discharge structures and combined before sample parameters are analyzed.

b. **Outfall 002 - 16-inch Suction Dredge**

To obtain representative effluent samples, equal volumes of effluent must be obtained from the three discharge structures (dump chutes) and combined before sample parameters are analyzed.

c. **Flow**

The average daily flow of the suction dredge must be estimated using the manufacturer's pump capacity or pump curves for each dredge. The average daily flow, maximum flow and number of hours the pump operates each day must be recorded in the logbook.

2. **Receiving stream (Hauser Lake) monitoring**

a. **Upstream receiving water**

Upstream receiving water samples for turbidity must be obtained within 4 inches of the water surface of Hauser Lake at the front (or side) of the barge away from divers supplied air bubbles.

b. **Downstream receiving water**

The downstream turbidity sample must be obtained within 4 inches of the water surface of Hauser Lake 500 feet downstream from the barge.

3. **Estimating cubic yards of raw material (gravel, cobbles and rocks)**

The diver operating the suction dredge intake must mark the starting point where dredging will occur each day. After completing suction dredging each day, the diver must estimate the length and width (in feet) of the area and estimate the average depth (in feet) of raw material dredged. Multiply the length times the width of the area dredged times the average depth of raw material to calculate cubic feet of raw material dredged. Divide the number of cubic feet of material by 27 to calculate the total number of cubic yards of material dredged each day. Multiply the number of cubic yards dredged by 1.4 tons per cubic yard to calculate the number of tons of raw material processed. Record the cubic yards and tons of raw material dredged each day in the logbook. Total the tons of raw material dredged each month and report on the DMR form.

Table 1. Monitoring Requirements¹

Parameter	Unit	Sample Location	Sample Frequency	Sample Type ¹	ML
Turbidity	NTU	Downstream	1/Day	Grab	1 NTU
Turbidity	NTU	Upstream	1/Day	Grab	1 NTU
Net Turbidity ²	NTU	Net Turbidity	1/Day	Calculated	1 NTU
Total Suspended Solids (TSS)	mg/L	Effluent	1/Week	Grab	10 mg/L
Dissolved oxygen (DO)	mg/L	Effluent	1/Month	Grab	0.05mg/L
Oil and Grease	mg/L	Effluent	³	Grab	³
Oil and Grease ³	Presence	Effluent	1/Day	Visual	--
Duration of discharge	Days/month	Effluent	1/Day	Report	--
Total tons of raw material processed ⁴	Tons	Intake	1/Day	Report	1 Ton
WET, acute and chronic ⁵	Pass/Fail	Effluent	Quarterly	Grab	Pass/fail

Footnotes:
1. See Definition section at end of permit for explanation of terms.
2. Net turbidity is calculated by subtracting the upstream turbidity value measured at the front of the barge from the turbidity value measured in the receiving stream at the downstream end of the 500-foot mixing zone [Turbidity at the end of the 500-foot mixing zone (Downstream) minus Turbidity in receiving water at the front of barge (Upstream) = Net turbidity].
3. If a visual examination of the effluent indicates the presence of hydrocarbons, by sheen, odor or other sign, the permittee is required to collect a sample for Oil and Grease and analyze it using EPA Method 1664A or equivalent. See Method for minimal detection level.
4. The total tons of raw material processed each day must be calculated using the method described in Section I.C.3 and recorded in the daily logbook. The total tons of raw material processed each month must be reported on the DMR.
5. See explanation for WET testing requirements in Section I.C.4.

4. Whole Effluent Toxicity Monitoring – Acute Toxicity

Starting in the first calendar quarter following the effective date of the permit, the permittee shall, at least once each quarter conduct an acute static replacement toxicity test on a composite/grab sample of the effluent. Testing will employ two species per quarter and will consist of 5 effluent concentrations (100, 50, 25, 12.5, 6.25 percent effluent) and a control. Dilution water and the control shall consist of the receiving water. Samples shall be collected on a two day progression; i.e., if the first quarterly sample is on a Monday, the second quarter sample shall be on a Wednesday, etc. Saturdays, Sundays and Holidays will be skipped in the progression.

The static toxicity tests shall be conducted in general accordance with the procedures set out in the latest revision of Methods for Measuring the Acute

Toxicity of Effluent to Freshwater and Marine Organisms, EPA-600/4-90/027 and the "Region VIII EPA NPDES Acute Test Conditions-State Renewal Whole Effluent Toxicity". The permittee shall conduct an acute 48-hour static renewal toxicity test using *Ceriodaphnia sp.* and an acute 96-hour static renewal toxicity test using fathead minnows (*Pimephales promelas*) as the alternating species. The permittee shall conduct chronic toxicity tests according to Short-term Methods for Estimating the Chronic Toxicity of Effluents and Receiving Waters to Freshwater Organisms, Fourth Edition, October 2002, EPA-821-R-02-013.

Acute toxicity occurs when 50 percent or more mortality is observed for either species at any effluent concentration. If more than 10 percent control mortality occurs, the test is considered invalid and shall be repeated until satisfactory control survival is achieved, unless a specific individual exception is granted by the Department. This exception may be granted if less than 10 percent mortality was observed at the dilutions containing high effluent concentrations.

If acute toxicity occurs in a routine test, an additional test shall be conducted within 14 days of the date of the initial sample. If no discharge will occur within 14 days of the initial failure, the additional test shall be conducted immediately upon resumption of the discharge. Should acute toxicity occur in the second test, testing shall occur once a month until further notified by the Department. In all cases, the results of all toxicity tests must be submitted to the Department in accordance with Part II of this permit.

The quarterly results from the laboratory shall be reported along with the Discharge Monitoring Report (DMR) form submitted for the end of the reporting calendar quarter (e.g., whole effluent results for the reporting quarter ending March 31 shall be reported with the March DMR due April 28th with the remaining quarterly reports submitted with the June, September, and December DMR's). The format for the laboratory report shall be consistent with the latest revision of Region VIII Guidance for Acute Whole Effluent Reporting, and shall include all chemical and physical data as specified.

The permittee may request a reduction or elimination of chronic WET testing following four consecutive samples demonstrating no chronic toxicity. The Department may approve, partially approve or deny the request based on test results and other information. The permit modification will take place without public notice.

D. Special Conditions

1. Toxicity Reduction Evaluation / Toxicity Identification Evaluation

Should acute toxicity be detected in the required resample, a TIE-TRE shall be undertaken by the permittee to establish the cause of the toxicity, locate the source(s) of the toxicity, and develop control or treatment for the toxicity. Failure to initiate or conduct an adequate TIE-TRE, or delays in the conduct of such tests, shall not be considered a justification for noncompliance with the whole effluent toxicity limits contained in Part I.B of this permit. A TRE plan needs to be submitted to the Department within 45 days after confirmation of the continuance of effluent toxicity (resample).

2. Supplemental Monitoring

The permittee must provide additional information for the Department to evaluate and determine if potential organochlorine pesticides, PCBs and total recoverable metals that may be reintroduced into the water column as the result of suction dredging will exceed water quality standards and create conditions that are harmful or toxic to human, animal, plant or aquatic life. Additional data must be provided for each proposed dredge site. Samples must be collected and analyzed during the first week the dredge operates at each of the proposed sites (S1 – S5).

One total recoverable metals (and hardness as CaCO₃), PCBs and organochlorine pesticides sample of the raw material (from the lake bottom) from each dredge site (S1 – S5) must be collected and analyzed for the total recoverable metals in Table 2 and organochlorine pesticides and PCBs in Table 3.

Table 2.

Analyses	RL	Units
Total Recoverable Antimony	0.003	mg/L
Total Recoverable Arsenic	0.005	mg/L
Total Recoverable Beryllium	0.001	mg/L
Total Recoverable Cadmium	0.00008	mg/L
Total Recoverable Chromium	0.001	mg/L
Total Recoverable Copper	0.001	mg/L
Total Recoverable Lead	0.0005	mg/L
Total Recoverable Mercury	0.00005	mg/L
Total Recoverable Nickel	0.01	mg/L
Total Recoverable Selenium	0.001	mg/L
Total Recoverable Silver	0.0005	mg/L
Total Recoverable Thallium	0.005	mg/L
Total Recoverable Zinc	0.01	mg/L

Table 3.

Analyses	RL	Units
Organochlorine Pesticides		
4,4'-DDD	0.097	mg/kg-dry
4,4'-DDE	0.097	mg/kg-dry
4 4'-DDT	0.097	mg/kg-dry
Aldrin	0.097	mg/kg-dry
alpha-BHC	0.097	mg/kg-dry
alpha-Chlordane	0.097	mg/kg-dry
beta-BHC	0.097	mg/kg-dry
Chlordane	0.97	mg/kg-dry
delta-BHC	0.097	mg/kg-dry
Dieldrin	0.097	mg/kg-dry
Endosulfan I	0.097	mg/kg-dry
Endosulfan II	0.097	mg/kg-dry
Endosulfan sulfate	0.097	mg/kg-dry
Endrin	0.097	mg/kg-dry
Endrin aldehyde	0.097	mg/kg-dry
Endrin ketone	0.097	mg/kg-dry
gamma-BHC (Lindane)	0.097	mg/kg-dry
gamma-Chlordane	0.097	mg/kg-dry
Heptachlor	0.097	mg/kg-dry
Heptachlor epoxide	0.097	mg/kg-dry
Methoxychlor	0.097	mg/kg-dry
Toxaphene	9.5	mg/kg-dry
PCBs		
Aroclor 1016	0.24	mg/kg-dry
Aroclor 1221	0.24	mg/kg-dry
Aroclor 1232	0.24	mg/kg-dry
Aroclor 1242	0.24	mg/kg-dry
Aroclor 1248	0.24	mg/kg-dry
Aroclor 1254	0.24	mg/kg-dry
Aroclor 1260	0.24	mg/kg-dry
Aroclor 1262	0.24	mg/kg-dry
Aroclor 1268	0.24	mg/kg-dry

One upstream sample of the receiving water must be collected (on the same day the raw material sample from the lake bottom is collected) and analyzed for total recoverable metals (and total hardness as CaCO₃) upstream from each dredging location using the monitoring method described in Section I.C.3 of this permit. The difference in analytical results between the total recoverable metals from the raw material and the upstream sample will be used by the Department to determine if total recoverable metals, already present in the water column, or if organochlorine pesticides and PCBs that

may be present in the raw material, are reintroduced to the water column during suction dredging. Copies of analytical results must be submitted with the DMR to the Water Protection Bureau in the month after samples are collected and analyzed.

3. Pollution Prevention:

- a. No chemical addition for the enhancement of gold, sapphires or mineral recovery is allowed in any operation covered under this permit.
- b. Dredging of concentrated silt and clay should be avoided. The permittee must use reasonable care to avoid dredging silt and clay materials that would result in a significant increase in turbidity or other pollutants. Reasonable care includes moving the dredge to a new location or reducing the volume of effluent discharge by limiting the pumping rate of the suction dredge.

E. Compliance Schedule

1. Best Management Plan

The permittee must develop a written Best Management Plan by February 1, 2010 that describes how fuel will be stored, handled and transported. The Plan must also address spill responses and be available to the Department during inspections. A copy of the Best Management Plan must be submitted to the Department by April 1, 2010.

II. MONITORING, RECORDING AND REPORTING REQUIREMENTS

A. Representative Sampling

Samples taken in compliance with the monitoring requirements established under Part I of the permit shall be collected from the effluent stream prior to discharge into the receiving waters. Samples and measurements shall be representative of the volume and nature of the monitored discharge.

B. Monitoring Procedures

Monitoring must be conducted according to test procedures approved under Part 136, Title 40 of the Code of Federal Regulations, unless other test procedures have been specified in this permit. All flow-measuring and flow-recording devices used in obtaining data submitted in self-monitoring reports must indicate values within 10 percent of the actual flow being measured.

C. Penalties for Tampering

The Montana Water Quality Act provides that any person who falsifies, tampers with, or knowingly renders inaccurate, any monitoring device or method required to be maintained under this permit shall, upon conviction, be punished by a fine of not more than \$10,000, or by imprisonment for not more than six months, or by both.

D. Reporting of Monitoring Results

Self-Monitoring results will be reported monthly. Monitoring results obtained during the previous reporting period shall be summarized and reported on a Discharge Monitoring Report Form (EPA No. 3320-1), postmarked no later than the 28th day of the month following the completed reporting period. Whole effluent toxicity (biomonitoring) results must be reported on forms from the most recent version of EPA Region VIII's "Guidance for Whole Effluent Reporting" with copies of the laboratory analysis report. If no discharge occurs during the reporting period, "no discharge" shall be reported. Legible copies of these, and all other reports required herein, shall be signed and certified in accordance with the "Signatory Requirements" (see Part IV.G of this permit), and submitted to the Department and the Regional Administrator at the following addresses:

- | | |
|---|--|
| (a) Montana Department of Environmental
Quality
Water Protection Bureau
PO Box 200901
Helena, Montana 59620-0901
Phone: (406) 444-3080 | (b) U.S. Environmental Protection
Agency
301 South Park Avenue
Drawer 10096
Helena, Montana 59626
Phone: (406) 441-1123 |
|---|--|

E. Compliance Schedules

Reports of compliance or noncompliance with, or any progress reports on interim and final requirements contained in any Compliance Schedule of this permit shall be submitted no later than 14 days following each schedule date.

F. Additional Monitoring by the Permittee

If the permittee monitors any pollutant more frequently than required by this permit, using approved analytical methods as specified in this permit, the results of this monitoring shall be included in the calculation and reporting of the data submitted in the Discharge Monitoring Report. Such increased frequency shall also be indicated.

G. Records Contents

Records of monitoring information shall include:

1. The date, exact place, and time of sampling or measurements;
2. The initials or name(s) of the individual(s) who performed the sampling or measurements;
3. The date(s) analyses were performed;
4. The time analyses were initiated;
5. The initials or name(s) of individual(s) who performed the analyses;
6. References and written procedures, when available, for the analytical techniques or methods used; and
7. The results of such analyses, including the bench sheets, instrument readouts, computer disks or tapes, etc., used to determine these results.

H. Retention of Records

The permittee shall retain records of all monitoring information, including all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by this permit, and records of all data used to complete the application for this permit, for a period of at least three years from the date of the sample, measurement, report or application. This period may be extended by request of the Department at any time. Data collected on site, copies of Discharge Monitoring Reports, and a copy of this MPDES permit must be maintained on site during the duration of activity at the permitted location.

I. Twenty-four Hour Notice of Noncompliance Reporting

1. The permittee shall report any serious incidents of noncompliance as soon as possible, but no later than twenty-four (24) hours from the time the permittee first became aware of the circumstances. The report shall be made to the Water Protection Bureau at (406) 444-3080 or the Office of Disaster and Emergency Services at (406) 841-3911. The following examples are considered serious incidents:

- a. Any noncompliance which may seriously endanger health or the environment;
 - b. Any unanticipated bypass which exceeds any effluent limitation in the permit (See Part III.G of this permit, "Bypass of Treatment Facilities"); or
 - c. Any upset which exceeds any effluent limitation in the permit (see Part III.H of this permit, "Upset Conditions").
2. A written submission shall also be provided within five days of the time that the permittee becomes aware of the circumstances. The written submission shall contain:
- a. a description of the noncompliance and its cause;
 - b. the period of noncompliance, including exact dates and times;
 - c. the estimated time noncompliance is expected to continue if it has not been corrected; and
 - d. steps taken or planned to reduce, eliminate, and prevent reoccurrence of the noncompliance.
3. The Department may waive the written report on a case-by-case basis if the oral report has been received within 24 hours by the Water Protection Bureau, by phone, (406) 444-3080.
4. Reports shall be submitted to the addresses in Part II.D of this permit, "Reporting of Monitoring Results".

J. Other Noncompliance Reporting

Instances of noncompliance not required to be reported within 24 hours shall be reported at the time that monitoring reports for Part II.D of this permit are submitted. The reports shall contain the information listed in Part II.I.2 of this permit.

K. Inspection and Entry

The permittee shall allow the head of the Department or the Director, or an authorized representative thereof, upon the presentation of credentials and other documents as may be required by law, to:

1. Enter upon the permittee's premises where a regulated facility or activity is located or conducted, or where records must be kept under the conditions of this permit;
2. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;

3. Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit; and
4. Sample or monitor at reasonable times, for the purpose of assuring permit compliance, any substances or parameters at any location.

III. COMPLIANCE RESPONSIBILITIES

A. Duty to Comply

The permittee must comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application. The permittee shall give the Department or the Regional Administrator advance notice of any planned changes at the permitted facility or of an activity which may result in permit noncompliance.

B. Penalties for Violations of Permit Conditions

The Montana Water Quality Act provides that any person who violates a permit condition of the Act is subject to civil or criminal penalties not to exceed \$10,000 per day of such violation. Any person who willfully or negligently violates permit conditions of the Act is subject to a fine of not more than \$50,000 per day of violation, or by imprisonment for not more than 2 years, or both, for subsequent convictions. MCA 75-5-611(a) also provides for administrative penalties not to exceed \$10,000 for each day of violation and up to a maximum not to exceed \$100,000 for any related series of violations. Except as provided in permit conditions on Part III.G of this permit, "Bypass of Treatment Facilities" and Part III.H of this permit, "Upset Conditions", nothing in this permit shall be construed to relieve the permittee of the civil or criminal penalties for noncompliance.

C. Need to Halt or Reduce Activity not a Defense

It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

D. Duty to Mitigate

The permittee shall take all reasonable steps to minimize or prevent any discharge in violation of this permit which has a reasonable likelihood of adversely affecting human health or the environment.

E. Proper Operation and Maintenance

The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the permittee to achieve compliance with the conditions of this permit. Proper operation and maintenance also includes adequate laboratory controls and appropriate quality assurance procedures. This provision requires the operation of back-up or auxiliary facilities or similar systems which are installed by a permittee only when the operation is necessary to achieve compliance with the conditions of the permit. However, the permittee shall operate, as a minimum, one complete set of each main line unit treatment process whether or not this process is needed to achieve permit effluent compliance.

F. Removed Substances

Collected screenings, grit, solids, sludges, or other pollutants removed in the course of treatment shall be disposed of in such a manner so as to prevent any pollutant from entering any waters of the state or creating a health hazard.

G. Bypass of Treatment Facilities

1. Bypass not exceeding limitations. The permittee may allow any bypass to occur which does not cause effluent limitations to be exceeded, but only if it also is for essential maintenance to assure efficient operation. These bypasses are not subject to the provisions of Parts III.G.2 and III.G.3 of this permit.

2. Notice:

a. Anticipated bypass. If the permittee knows in advance of the need for a bypass, it shall submit prior notice, if possible at least 10 days before the date of the bypass.

b. Unanticipated bypass. The permittee shall submit notice of an unanticipated bypass as required under Part II.I of this permit, "Twenty-four Hour Reporting".

3. Prohibition of bypass:

a. Bypass is prohibited and the Department may take enforcement action against a permittee for a bypass, unless:

1) The bypass was unavoidable to prevent loss of life, personal injury, or severe property damage;

2) There were no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate back-up equipment should have been installed in the exercise of reasonable engineering judgment to prevent a bypass which occurred during normal periods of equipment downtime or preventive maintenance; and

3) The permittee submitted notices as required under Part III.G.2 of this permit.

b. The Department may approve an anticipated bypass, after considering its adverse effects, if the Department determines that it will meet the three conditions listed above in Part III.G.3.a of this permit.

H. Upset Conditions

1. Effect of an upset. An upset constitutes an affirmative defense to an action brought for noncompliance with technology based permit effluent limitations if the requirements of Part III.H.2 of this permit are met. No determination made during administrative review of claims that noncompliance was caused by upset, and before an action for noncompliance, is final administrative action subject to judicial review (i.e. Permittees will have the opportunity for a judicial determination on any claim of upset only in an enforcement action brought for noncompliance with technology-based permit effluent limitations).
2. Conditions necessary for a demonstration of upset. A permittee who wishes to establish the affirmative defense of upset shall demonstrate, through properly signed, contemporaneous operating logs, or other relevant evidence that:
 - a. An upset occurred and that the permittee can identify the cause(s) of the upset;
 - b. The permitted facility was at the time being properly operated;
 - c. The permittee submitted notice of the upset as required under Part II.I of this permit, "Twenty-four Hour Notice of Noncompliance Reporting"; and
 - d. The permittee complied with any remedial measures required under Part III.D of this permit, "Duty to Mitigate".
3. Burden of proof. In any enforcement proceeding, the permittee seeking to establish the occurrence of an upset has the burden of proof.

I. Toxic Pollutants

The permittee shall comply with effluent standards or prohibitions established under Section 307(a) of the Clean Water Act for toxic pollutants within the time provided in the regulations that establish those standards or prohibitions, even if the permit has not yet been modified to incorporate the requirement.

J. Changes in Discharge of Toxic Substances

Notification shall be provided to the Department as soon as the permittee knows of, or has reason to believe:

1. That any activity has occurred or will occur which would result in the discharge, on a routine or frequent basis, of any toxic pollutant which is not limited in the permit, if that discharge will exceed the highest of the following "notification levels":
 - a. One hundred micrograms per liter (100 mg/L);

- b. Two hundred micrograms per liter (200 mg/L) for acrolein and acrylonitrile; five hundred micrograms per liter (500 mg/L) for 2,4-dinitrophenol and for 2-methyl-4, 6-dinitrophenol; and one milligram per liter (1 mg/L) for antimony;
 - c. Five (5) times the maximum concentration value reported for that pollutant in the permit application in accordance with 40 CFR 122.21(g)(7); or
 - d. The level established by the Department in accordance with 40 CFR 122.44(f).
2. That any activity has occurred or will occur which would result in any discharge, on a non-routine or infrequent basis, of a toxic pollutant which is not limited in the permit, if that discharge will exceed the highest of the following "notification levels":
- a. Five hundred micrograms per liter (500 mg/L);
 - b. One milligram per liter (1 mg/L) for antimony;
 - c. Ten (10) times the maximum concentration value reported for that pollutant in the permit application in accordance with 40 CFR 122.21(g)(7); or
 - d. The level established by the Department in accordance with 40 CFR 122.44(f).

IV. GENERAL REQUIREMENTS

A. Planned Changes

The permittee shall give notice to the Department as soon as possible of any planned physical alterations or additions to the permitted facility. Notice is required only when the alteration or addition could significantly change the nature or increase the quantity of pollutant discharged. This notification applies to pollutants which are not subject to effluent limitations in the permit.

B. Anticipated Noncompliance

The permittee shall give advance notice to the Department of any planned changes in the permitted facility or activity which may result in noncompliance with permit requirements.

C. Permit Actions

This permit may be modified, revoked and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance, does not stay any permit condition.

D. Duty to Reapply

If the permittee wishes to continue an activity regulated by this permit after the expiration date of this permit, the permittee must apply for and obtain a new permit. The application must be submitted at least 180 days before the expiration date of this permit.

E. Duty to Provide Information

The permittee shall furnish to the Department, within a reasonable time, any information which the Department may request to determine whether cause exists for revoking, modifying and reissuing, or terminating this permit, or to determine compliance with this permit. The permittee shall also furnish to the Department, upon request, copies of records required to be kept by this permit.

F. Other Information

When the permittee becomes aware that it failed to submit any relevant facts in a permit application, or submitted incorrect information in a permit application or any report to the Department, it shall promptly submit such facts or information with a narrative explanation of the circumstances of the omission or incorrect submittal and why they weren't supplied earlier.

G. Signatory Requirements

All applications, reports or information submitted to the Department or the EPA shall be signed and certified.

1. All permit applications shall be signed as follows:

a. For a corporation: by a responsible corporate officer;

- b. For a partnership or sole proprietorship: by a general partner or the proprietor, respectively;
 - c. For a municipality, State, Federal, or other public agency: by either a principal executive officer or ranking elected official.
2. All reports required by the permit and other information requested by the Department shall be signed by a person described above or by a duly authorized representative of that person. A person is considered a duly authorized representative only if:
 - a. The authorization is made in writing by a person described above and submitted to the Department; and
 - b. The authorization specified either an individual or a position having responsibility for the overall operation of the regulated facility or activity, such as the position of plant manager, operator of a well or a well field, superintendent, position of equivalent responsibility, or an individual or position having overall responsibility for environmental matters for the company. (A duly authorized representative may thus be either a named individual or an individual occupying a named position.)
 3. Changes to authorization. If an authorization under Part IV.G.2 of this permit is no longer accurate because a different individual or position has responsibility for the overall operation of the facility, a new authorization satisfying the requirements of Part IV.G.2 of this permit must be submitted to the Department prior to or together with any reports, information, or applications to be signed by an authorized representative.
 4. Certification. Any person signing a document under this section shall make the following certification:

“I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.”

H. Penalties for Falsification of Reports

The Montana Water Quality Act provides that any person who knowingly makes any false statement, representation, or certification in any record or other document

submitted or required to be maintained under this permit, including monitoring reports or reports of compliance or noncompliance shall, upon conviction be punished by a fine of not more than \$25,000 per violation, or by imprisonment for not more than six months per violation, or by both.

I. Availability of Reports

Except for data determined to be confidential under 40 CFR Part 2, all reports prepared in accordance with the terms of this permit shall be available for public inspection at the offices of the Department. As required by the Clean Water Act, permit applications, permits and effluent data shall not be considered confidential.

J. Oil and Hazardous Substance Liability

Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities, or penalties to which the permittee is or may be subject under Section 311 of the Clean Water Act.

K. Property or Water Rights

The issuance of this permit does not convey any property or water rights of any sort, or any exclusive privileges, nor does it authorize any injury to private property or any invasion of personal rights, nor any infringement of federal, state or local laws or regulations. Issuance of this permit does not convey any property right or use right to submerged lands owned by the State of Montana or any other person or entity.

L. Severability

The provisions of this permit are severable, and if any provision of this permit, or the application of any provision of this permit to any circumstance, is held invalid, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected thereby.

M. Transfers

This permit may be automatically transferred to a new permittee if:

1. The current permittee notifies the Department at least 30 days in advance of the proposed transfer date;
2. The notice includes a written agreement between the existing and new permittees containing a specific date for transfer of permit responsibility, coverage, and liability between them;
3. The Department does not notify the existing permittee and the proposed new permittee of an intent to revoke or modify and reissue the permit. If this notice is not received, the transfer is effective on the date specified in the agreement mentioned in Part IV.M.2 of this permit; and
4. Required annual and application fees have been paid.

N. Fees

The permittee is required to submit payment of an annual fee as set forth in ARM 17.30.201. If the permittee fails to pay the annual fee within 90 days after the due date for the payment, the Department may:

1. Impose an additional assessment consisting of 15% of the fee plus interest on the required fee computed at the rate established under 15-31-510(3), MCA, or
2. Suspend the processing of the application for a permit or authorization or, if the nonpayment involves an annual permit fee, suspend the permit, certificate or authorization for which the fee is required. The Department may lift suspension at any time up to one year after the suspension occurs if the holder has paid all outstanding fees, including all penalties, assessments and interest imposed under this sub-section. Suspensions are limited to one year, after which the permit will be terminated.

O. Reopener Provisions

This permit may be reopened and modified (following proper administrative procedures) to include the appropriate effluent limitations (and compliance schedule, if necessary), or other appropriate requirements if one or more of the following events occurs:

1. Water Quality Standards: The water quality standards of the receiving water(s) to which the permittee discharges are modified in such a manner as to require different effluent limits than contained in this permit.
2. Water Quality Standards are Exceeded: If it is found that water quality standards or trigger values in the receiving stream are exceeded either for parameters included in the permit or others, the department may modify the effluent limits or water management plan.
3. TMDL or Wasteload Allocation: TMDL requirements or a wasteload allocation is developed and approved by the Department and/or EPA for incorporation in this permit.
4. Water Quality Management Plan: A revision to the current water quality management plan is approved and adopted which calls for different effluent limitations than contained in this permit.
5. Toxic Pollutants: A toxic standard or prohibition is established under Section 307(a) of the Clean Water Act for a toxic pollutant which is present in the discharge and such standard or prohibition is more stringent than any limitation for such pollutant in this permit.
6. Toxicity Limitation: Change in the whole effluent protocol, or any other conditions related to the control of toxicants have taken place, or if one or more of the following events have occurred:

- a. Toxicity was detected late in the life of the permit near or past the deadline for compliance.
- b. The TRE/TIE results indicated that compliance with the toxic limits will require an implementation schedule past the date for compliance.
- c. The TRE/TIE results indicated that the toxicant(s) represent pollutant(s) that may be controlled with specific numerical limits.
- d. Following the implementation of numerical controls on toxicants, a modified whole effluent protocol is needed to compensate for those toxicants that are controlled numerically.
- e. The TRE/TIE revealed other unique conditions or characteristics which, in the opinion of the Department, justify the incorporation of unanticipated special conditions in the permit.

V. DEFINITIONS

1. **“Act”** means the Montana Water Quality Act, Title 75, chapter 5, MCA.
2. **“Administrator”** means the administrator of the United States Environmental Protection Agency.
3. **“Acute Toxicity”** occurs when 50 percent or more mortality is observed for either species (See Part I.C of this permit) at any effluent concentration. Mortality in the control must simultaneously be 10 percent or less for the effluent results to be considered valid.
4. **“Arithmetic Mean” or “Arithmetic Average”** for any set of related values means the summation of the individual values divided by the number of individual values.
5. **“Average Monthly Limitation”** means the highest allowable average of daily discharges over a calendar month, calculated as the sum of all daily discharges measured during a calendar month divided by the number of daily discharges measured during that month.
6. **“Bypass”** means the intentional diversion of waste streams from any portion of a treatment facility.
7. **“Chronic Toxicity”** means when the survival, growth, or reproduction, as applicable, for either test species, at the effluent dilution(s) designated in this permit (see Part I.C.), is significantly less (at the 95 percent confidence level) than that observed for the control specimens.
8. **“Composite samples”** shall be flow proportioned. The composite sample shall, as a minimum, contain at least four (4) samples collected over the compositing period. Unless otherwise specified, the time between the collection of the first sample and the last sample shall not be less than six (6) hours nor more than 24 hours. Acceptable methods for preparation of composite samples are as follows:
 - a. Constant time interval between samples, sample volume proportional to flow rate at time of sampling;
 - b. Constant time interval between samples, sample volume proportional to total flow (volume) since last sample. For the first sample, the flow rate at the time the sample was collected may be used;
 - c. Constant sample volume, time interval between samples proportional to flow (i.e. sample taken every “X” gallons of flow); and,
 - d. Continuous collection of sample, with sample collection rate proportional to flow rate.

9. **“Daily Discharge”** means the discharge of a pollutant measured during a calendar day or any 24-hour period that reasonably represents the calendar day for purposes of sampling. For pollutants with limitations expressed in units of mass, the daily discharge is calculated as the total mass of the pollutant discharged over the day. For pollutants with limitations expressed in other units of measurement, the daily discharge is calculated as the average measurement of the pollutant over the day.
10. **“Daily Maximum Limit”** means the maximum allowable discharge of a pollutant during a calendar day. Expressed as units of mass, the daily discharge is cumulative mass discharged over the course of the day. Expressed as a concentration, it is the arithmetic average of all measurements taken that day.
11. **“Department”** means the Montana Department of Environmental Quality (MDEQ). Established by 2-15-3501, MCA.
12. **“Director”** means the Director of the Montana Department of Environmental Quality.
13. **“Discharge”** means the injection, deposit, dumping, spilling, leaking, placing, or failing to remove any pollutant so that it or any constituent thereof may enter into state waters, including ground water.
14. **“EPA”** means the United States Environmental Protection Agency.
15. **“Federal Clean Water Act”** means the federal legislation at 33 USC 1251, *et seq.*
16. **“Grab Sample”** means a sample which is taken from a waste stream on a one-time basis without consideration of flow rate of the effluent or without consideration for time.
17. **“Instantaneous Maximum Limit”** means the maximum allowable concentration of a pollutant determined from the analysis of any discrete or composite sample collected, independent of the flow rate and the duration of the sampling event.
18. **“Instantaneous Measurement”**, for monitoring requirements, means a single reading, observation, or measurement.
19. **“Minimum Level”** (ML) of quantitation means the lowest level at which the entire analytical system gives a recognizable signal and acceptable calibration point for the analyte, as determined by the procedure set forth at 40 CFR 136. In most cases the ML is equivalent to the Required Reporting Value (RRV) unless otherwise specified in the permit. (ARM 17.30.702(22))
19. **“Mixing zone”** means a limited area of a surface water body or aquifer where initial dilution of a discharge takes place and where certain water quality standards may be exceeded.

20. "**Nondegradation**" means the prevention of a significant change in water quality that lowers the quality of high-quality water for one or more parameters. Also, the prohibition of any increase in discharge that exceeds the limits established under or determined from a permit or approval issued by the Department prior to April 29, 1993.
21. "**Regional Administrator**" means the administrator of Region VIII of EPA, which has jurisdiction over federal water pollution control activities in the state of Montana.
22. "**Severe property damage**" means substantial physical damage to property, damage to the treatment facilities which causes them to become inoperable, or substantial and permanent loss of natural resources which can reasonably be expected to occur in the absence of a bypass. Severe property damage does not mean economic loss caused by delays in production.
23. "**TIE**" means a toxicity identification evaluation.
24. "**TMDL**" means the total maximum daily load limitation of a parameter, representing the estimated assimilative capacity for a water body before other designated uses are adversely affected. Mathematically, it is the sum of wasteload allocations for point sources, load allocations for non-point and natural background sources, and a margin of safety.
25. "**TRE**" means a toxicity reduction evaluation.
26. "**TSS**" means the pollutant parameter total suspended solids.
27. "**Upset**" means an exceptional incident in which there is unintentional and temporary noncompliance with technology-based permit effluent limitations because of factors beyond the reasonable control of the permittee. An upset does not include noncompliance to the extent caused by operational error, improperly designed treatment facilities, inadequate treatment facilities, lack of preventive maintenance, or careless or improper operation.