VICEDON



### UNITED STATES ENVIRONMENTAL PROTECTION AGENCY REGION 8

1595 Wynkoop Street
DENVER, CO 80202-1129
Phone 800-227-8917
http://www.epa.gov/region08

Ref: 8EPR-EP

SEP 16 2011

Mr. George Mathieus Administrator Planning, Prevention and Assistance Division Montana Department of Environmental Quality P.O. Box 200901 Helena, MT 59620-0901

> Re: TMDL Approvals for the Tobacco Planning Area Sediment TMDLs and Framework Water Quality Improvement Plan

Dear Mr. Mathieus:

We have completed our review of the total maximum daily loads (TMDLs) as submitted by your office for the waterbodies listed in the enclosure to this letter. In accordance with the Clean Water Act (33 U.S.C. 1251 et. seq.), we approve all aspects of the TMDLs referenced above that were developed for the water quality limited waterbodies as described in Section 303(d)(1). Based on our review, we feel the separate elements of the TMDLs listed in the enclosed table adequately address the pollutants of concern as given in the table, taking into consideration seasonal variation and a margin of safety.

Thank you for submitting these TMDLs for our review and approval. If you have any questions, the most knowledgeable person on my staff is Jason Gildea and he may be reached at 406-457-5028.

Sincerely,

Carol L. Campbell

Assistant Regional Administrator Office of Ecosystems Protection

Carl & Carghell

and Remediation

			paired B Use	enef			XIIIIuIII Daily Loa			TMDL Endpo	oints		WLA	Load Allocation	ons		
Waterbody & Stream Description	Waterbody ID	Agriculture	Fishery	lier	Industry Contact Recreation	Cycle First Listed	Cause of Impairment	Pollutant for which TMDL has been prepared	DEQ Action	Indicators	Threshold Values	WLA <sup>1</sup>	WLA Permitted Facilities (Permit Number)	Source	LA <sup>1</sup>	TMDL <sup>1</sup>	MOS
						N/A	Excess Algal Growth	N/A	Not Addressed	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
						N/A	Alteration in stream-side or littoral vegetative covers	N/A	Addressed by sediment TMDL	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
										% riffle surface fines < 6mm (reach average via pebble count)	≤ 15%			Roads	1		
										% riffle surface fines < 2mm (reach average via pebble count)	≤ 8%			Human Caused Bank Erosion	117		
									% riffle and pool surface fines <6mm via grid toss (reach average)	≤ 8%							
Deep Creek, headwaters to mouth (Fortine	MT76D004_080	F	P P F	F	F P		Sedimentation / Siltation			Width/Depth Ratio	B & C Streams BFW < 30 ft: ≤ 21 B & C Streams BFW > 30 ft: ≤ 35 E channel: ≤ 8			Natural Background Bank	279		
Creek)						2006		Sediment		Entrenchment Ratio	B: ≥ 1.4, C: ≥ 2.7	N/A		Erosion	219	538 (14% Total Load Reduction)	Implicit
										Reach average residual pool depth	E: ≥ 2.3 <20' BFW: ≥ 0.8' 20'-35' BFW: ≥ 1.2' >35' BFW: ≥ 1.6'						
										Pools/mile	<20' BFW: ≥ 75 20'-35' BFW: ≥ 42 >35' BFW: ≥ 31; Tobacco River ≥ 12						
										LWD/mile	<20' BFW: ≥ 359 20'-35' BFW: ≥ 242 >35" BFW: 104			Upland Erosion	141		
										% Greenline shrub cover (where applicable)	≥ 57%						
										Significant & Controllable Sediment Sources	Indicator of stream problems - poor quality						
										Macroinvertebrate Indices	Mountain MMI: $>63$ O/E $\geq 0.80$						

1

		Im		ed Bei Uses	nefic	ial					TMDL Endpo	ints		WLA	Load Allocation	ons		
Waterbody & Stream Description	Waterbody ID	Agriculture	Prv	Water	Industry	Contact Recreation	Cycle First Listed	Cause of Impairment	Pollutant for which TMDL has been prepared	DEQ Action	Indicators	Threshold Values	WLA 1	WLA Permitted Facilities (Permit Number)	Source	LA¹	$\mathrm{TMDL}^1$	MOS
															Roads	4		
Edna Creek, headwaters to	MET (DOOA 020	n l					1002	Sedimentation / Siltation	G 1	TI (D)		Same as for Deep	21/4	21/4	Human Caused Bank Erosion	13	514 (8%	T 11.11
mouth (Fortine Creek)	MT76D004_030	F	P	F	F	F	1992		Sediment	TMDL	Same as for Deep Creek	Creek	N/A	N/A	Natural Background Bank Erosion	433	Total Load Reduction)	Implicit
Ź															Upland Erosion	64		
	o MT76D004_020 F P P						N/A	Alteration in stream-side or littoral vegetative covers	N/A	Addressed by sediment TMDL	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Fortine					F		N/A	Excess Algal Growth	N/A	Not Addressed	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Creek, headwaters to		F	P I	P F		P	2006	Temperature (water)	N/A	Not Addressed	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
mouth (Grave Creek)															Roads	33		
Creek)							1990	Sedimentation /	Sediment	TMDL	Same as for Deep Creek	Same as for Deep	N/A	N/A	Human Caused Bank Erosion	1,503	10,920 (9% Total Load	Implicit
								Siltation			The state of the s	Creek			Natural Bank Erosion	8,606	Reduction)	r
															Upland Erosion	778		
							N/A	Low flow alterations	N/A	Not Addressed	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
							2006	Arsenic	N/A	Not Addressed	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
							2006	Phosphorus (Total)	N/A	Not Addressed	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
							2006	Total Kjehldahl Nitrogen (TKN)	N/A	Not Addressed	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
							N/A	Chlorophyll-a	N/A	Not Addressed	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Lime Creek, headwaters to mouth (Fortine Creek)	MT76D004_050	F 1	N N	N N	F	F P	N/A	Alteration in stream-side or littoral vegetative covers	N/A	Addressed by sediment TMDL	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
															Roads	2		
							1996	Sedimentation /	Sediment	TMDL	Same as for Deen Creek	Same as for Deep Creek	N/A	N/A	Human Caused Bank Erosion	87	514 (10% Total Load Reduction)	Implicit
								Siltation	Seamient	TNIDL	Same as for Deep Creek			N/A	Natural Bank Erosion	400		implicit
															Upland Erosion	25		

			pair	ed Bei Uses				Ailliuili Dally Load			TMDL Endpo	ints		WLA	Load Allocation	ons				
Waterbody & Stream Description	Waterbody ID	Agriculture	Cold Wotor Fishore	Drinking Water	Industry	Contact Recreation	Cycle First Listed	Cause of Impairment	Pollutant for which TMDL has been prepared	DEQ Action	Indicators	Threshold Values	WLA 1	WLA Permitted Facilities (Permit Number)	Source	LA <sup>1</sup>	TMDL <sup>1</sup>	MOS		
Sinclair Creek,												Same as for Deep Creek			Roads	0.3				
confluence of un-named					X						Same as for Deep Creek			Composite for	Human Caused Bank Erosion	695	1088 (25% Total Load Reduction)			
tributary, Lat -114.945	MT76D004_091	X	P   1	P X		X	> 2010	Sedimentation / Siltation	Sediment	TMDL			0.7	Composite for Stormwater Construction	Natural Bank Erosion	344		Implicit		
Long 48.908 to mouth (Tobacco River)														(MTR100000)	Upland Erosion	48				
Swamp									N/A	Alterations in stream-side or littoral vegetative covers	N/A	Addressed by sediment TMDL	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Creek, headwaters to	MT76D004_040	F 1	P ]	P F	F	P	N/A	Low flow alterations	N/A	Not Addressed	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
mouth (Fortine	_														Roads	4				
Creek)							1992	Sedimentation /	Sediment	TMDL	Same as for Deep Creek	Same as for Deep	N/A	N/A	Human Caused Bank Erosion	191	1,477 (12% Total Load	Implicit		
							1992	Siltation	Seament	TNIDE	Same as for Beep creek	Creek	11/21	11//11	Natural Bank Erosion	1,123	Reduction)	implicit		
			+												Upland Erosion	159				
Therriault Creek, headwaters to								Sedimentation /				Same as for Deep			Roads Human Caused Bank Erosion	95	453 (16%			
mouth (Tobacco	MT76D004_070	F 1	P	PF	F	F	1988	Sedimentation / Siltation	Sediment	TMDL	TMDL Same as for Deep Creek	Same as for Deep Creek	N/A	N/A	Natural Bank Erosion	290	Total Load   Ir	Implicit		
River)															Upland Erosion	67				

		Impaired U	Beno ses	eficia	al					TMDL Endpo	ints		WLA	Load Allocation	ons		
Waterbody & Stream Description	Waterbody ID	Agriculture Aquatic Life Cold Water Fishery	Drinking Water	Industry	Contact Recreation	Cycle First Listed	Cause of Impairment	Pollutant for which TMDL has been prepared	DEQ Action	Indicators	Threshold Values	WLA 1	WLA Permitted Facilities (Permit Number)	Source	LA <sup>1</sup>	TMDL <sup>1</sup>	MOS
						N/A	Physical substrate habitat alterations	N/A	Addressed by sediment TMDL	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Tobacco River, confluence of Grave Creek & Fortine Creek to mouth (Lake Koocanusa)	MT76D004_010	F P P	F	F	F	1988	Sedimentation / Siltation	Sediment	TMDL	Same as for Deep Creek	Same as for Deep Creek	Eureka: 34; Tmbrln: 0.03; Constrtn: 5	Eureka WWTP (MTG580032); Timberline Ready Mix (MTR300259); Composite for Stormwater Construction (MTR100000)	Roads Road Sand Human Caused Bank Erosion Natural Bank Erosion Upland Erosion	42 11 3,544 15,402	20,623 (11% Total Load Reduction)	Implicit

F = Fully Supporting, P = Partially Supporting, N = Not Supporting, X = Not Assessed, N/A = Not Applicable

Footnote 1 - Sediment TMDLs and allocations are shown in tons/yr. Daily loads are reported in Appendix H.

#### **ENCLOSURE 2**

#### **EPA REGION VIII TMDL REVIEW**

#### TMDL Document Info:

Document Name:	Tobacco Planning Area Sediment TMDLs and Framework Water Quality Improvement Plan
Submitted by:	Montana Department of Environmental Quality
Date Received:	September 12, 2011
Review Date:	September 12, 2011
Reviewer:	Lisa Kusnierz
Rough Draft / Public Notice / Final Draft?	Final
Notes:	

Reviewers Final Recommendation(s) to EPA	Administrator (used for final draft review only):
Approve	
Partial Approval	
Disapprove	
Insufficient Information	

**Approval Notes to Administrator:** Based on the review presented below, I recommend approval of the TMDLs submitted in this document.

This document provides a standard format for EPA Region 8 to provide comments to state TMDL programs on TMDL documents submitted to EPA for either formal or informal review. All TMDL documents are evaluated against the minimum submission requirements and TMDL elements identified in the following 8 sections:

- 1. Problem Description
  - 1.1. TMDL Document Submittal Letter
  - 1.2. Identification of the Waterbody, Impairments, and Study Boundaries
  - 1.3. Water Quality Standards
- 2. Water Quality Target
- 3. Pollutant Source Analysis
- 4. TMDL Technical Analysis
  - 4.1. Data Set Description
  - 4.2. Waste Load Allocations (WLA)
  - 4.3. Load Allocations (LA)
  - 4.4. Margin of Safety (MOS)
  - 4.5. Seasonality and variations in assimilative capacity
- 5. Public Participation
- 6. Monitoring Strategy
- 7. Restoration Strategy
- 8. Daily Loading Expression

Under Section 303(d) of the Clean Water Act, waterbodies that are not attaining one or more water quality standard (WQS) are considered "impaired." When the cause of the impairment is determined to be a pollutant, a TMDL analysis is required to assess the appropriate maximum allowable pollutant loading rate. A TMDL document consists of a technical analysis conducted to: (1) assess the maximum pollutant loading rate that a waterbody is able to assimilate while maintaining water quality standards; and (2) allocate that assimilative capacity among the known sources of that pollutant. A well written TMDL document will describe a path forward that may be used by those who implement the TMDL recommendations to attain and maintain WOS.

Each of the following eight sections describe the rationale that EPA Region 8 staff uses when reviewing TMDL documents. Also included in each section is a list of EPA's minimum submission requirements relative to that section, a brief summary of the EPA reviewer's findings, and the reviewer's comments and/or suggestions. Use of the verb "must" in the minimum submission requirements denotes information that is required to be submitted because it relates to elements of the TMDL required by the CWA and by regulation. Use of the term "should" below denotes information that is generally necessary for EPA to determine if a submitted TMDL is approvable.

This review template is intended to ensure compliance with the Clean Water Act and that the reviewed documents are technically sound and the conclusions are technically defensible.

# 1.0 Problem Description

A TMDL document needs to provide a clear explanation of the problem it is intended to address. Included in that description should be a definitive portrayal of the physical boundaries to which the TMDL applies, as well as a clear description of the impairments that the TMDL intends to address and the associated pollutant(s) causing those impairments. While the existence of one or more impairment and stressor may be known, it is important that a comprehensive evaluation of the water quality be conducted prior to development of the TMDL to ensure that all water quality problems and associated stressors are identified. Typically, this step is conducted prior to the 303(d) listing of a waterbody through the monitoring and assessment program. The designated uses and water quality criteria for the waterbody should be examined against available data to provide an evaluation of the water quality relative to all applicable water quality standards. If, as part of this exercise, additional WQS problems are discovered and additional stressor pollutants are identified, consideration should be given to concurrently evaluating TMDLs for those additional pollutants. If it is determined that insufficient data is available to make such an evaluation, this should be noted in the TMDL document.

### 1.1 TMDL Document Submittal Letter

When a TMDL document is submitted to EPA requesting formal comments or a final review and approval, the submittal package should include a letter identifying the document being submitted and the purpose of the submission.

Minimum Submission Requirements.

- A TMDL submittal letter should be included with each TMDL document submitted to EPA requesting a formal review.
- The submittal letter should specify whether the TMDL document is being submitted for initial review and comments, public review and comments, or final review and approval.
- Each TMDL document submitted to EPA for final review and approval should be accompanied by a submittal letter that explicitly states that the submittal is a final TMDL submitted under Section 303(d) of the Clean Water

Act for EPA review and approval. This clearly establishes the State's/Tribe's intent to submit, and EPA's duty to review, the TMDL under the statute. The submittal letter should contain such identifying information as the name and location of the waterbody and the pollutant(s) of concern, which matches similar identifying information in the TMDL document for which a review is being requested.

	commendation: Approve ☐ Partial Approval ☐ Disapprove ☐ Insufficient Information
	<b>mmary and Comments:</b> This document was submitted to EPA for review on September 12, 2011. adequate cover letter was included.
	1.2 Identification of the Waterbody, Impairments, and Study Boundaries
is in clear	e TMDL document should provide an unambiguous description of the waterbody to which the TMDL needed to apply and the impairments the TMDL is intended to address. The document should also arrly delineate the physical boundaries of the waterbody and the geographical extent of the watershed a studied. Any additional information needed to tie the TMDL document back to a current 303(d) ang should also be included.
Min	imum Submission Requirements:
	The TMDL document should clearly identify the pollutant and waterbody segment(s) for which the TMDL is being established. If the TMDL document is submitted to fulfill a TMDL development requirement for a waterbody on the state's current EPA approved 303(d) list, the TMDL document submittal should clearly identify the waterbody and associated impairment(s) as they appear on the State's/Tribe's current EPA approved 303(d) list, including a full waterbody description, assessment unit/waterbody ID, and the priority ranking of the waterbody. This information is necessary to ensure that the administrative record and the national TMDL tracking database properly link the TMDL document to the 303(d) listed waterbody and impairment(s).
	One or more maps should be included in the TMDL document showing the general location of the waterbody and, to the maximum extent practical, any other features necessary and/or relevant to the understanding of the TMDL analysis, including but not limited to: watershed boundaries, locations of major pollutant sources, major tributaries included in the analysis, location of sampling points, location of discharge gauges, land use patterns, and the location of nearby waterbodies used to provide surrogate information or reference conditions. Clear and concise descriptions of all key features and their relationship to the waterbody and water quality data should be provided for all key and/or relevant features not represented on the map
	If information is available, the waterbody segment to which the TMDL applies should be identified/georeferenced using the National Hydrography Dataset (NHD). If the boundaries of the TMDL do not correspond to the Waterbody ID(s) (WBID), Entity_ID information or reach code (RCH_Code) information should be provided. If NHD data is not available for the waterbody, an alternative geographical referencing system that unambiguously identifies the physical boundaries to which the TMDL applies may be substituted.
	commendation: Approve  Partial Approval Disapprove Insufficient Information
Are	mmary and Comments: The waterbody/pollutant combinations addressed in the Tobacco Planning a Sediment TMDLs document are summarized in Table 1 (appended to the end of this document) and clearly described in the subject document. The number of TMDLs developed and the pollutants for

which they were developed are summarized below:

#### **Tobacco Sediment TMDLs**

Number of TMDLs:	8
Number of	
Waterbody/Pollutant	
Combinations addressed by	
TMDLs:	8
Number of Sediment TMDLs:	8

The waterbodies addressed by the sediment TMDLs are listed in Table 2 (appended to the end of this document).

The waterbody segments are not referenced to the NHD within the subject document. However, MTDEQ's internal databases do link between their waterbody ID and NHD.

At this time, TMDLs were not completed for 4 waterbody-pollutant combinations (WBPCs) in the Tobacco TMDL Planning Area. Remaining WBPCs are metals (1), nutrients (2), and temperature (1). The document states that future TMDL work will be required to address the remaining WBPCs but gives no timeframe.

The TMDL document addresses 6 WBPCs that originally appeared on Montana's 1996 303(d) list and fall under the current Montana TMDL Court Order. One remaining WBPC was listed on a subsequent list and the other does not currently appear on any 303(d) list. During the TMDL process, DEQ identified 1 new WBPC that was impaired because of sediment, noted as a cycle first listed of ">2010" in Table 1. A sediment TMDL was completed for the new WBPC.

# 2.0 Water Quality Standards

TMDL documents should provide a complete description of the water quality standards for the waterbodies addressed, including a listing of the designated uses and an indication of whether the uses are being met, not being met, or not assessed. If a designated use was not assessed as part of the TMDL analysis (or not otherwise recently assessed), the documents should provide a reason for the lack of assessment (e.g., sufficient data was not available at this time to assess whether or not this designated use was being met).

Water quality criteria (WQC) are established as a component of water quality standard at levels considered necessary to protect the designated uses assigned to that waterbody. WQC identify quantifiable targets and/or qualitative water quality goals which, if attained and maintained, are intended to ensure that the designated uses for the waterbody are protected. TMDLs result in maintaining and attaining water quality standards by determining the appropriate maximum pollutant loading rate to meet water quality criteria, either directly, or through a surrogate measurable target. The TMDL document should include a description of all applicable water quality criteria for the impaired designated uses and address whether or not the criteria are being attained, not attained, or not evaluated as part of the analysis. If the criteria were not evaluated as part of the analysis, a reason should be cited (e.g. insufficient data were available to determine if this water quality criterion is being attained).

#### **Minimum Submission Requirements:**

- The TMDL must include a description of the applicable State/Tribal water quality standard, including the designated use(s) of the waterbody, the applicable numeric or narrative water quality criterion, and the anti-degradation policy. (40 C.F.R. §130.7(c)(1)).
- □ The purpose of a TMDL analysis is to determine the assimilative capacity of the waterbody that corresponds to the existing water quality standards for that waterbody, and to allocate that assimilative capacity between the significant sources. Therefore, all TMDL documents must be written to meet the existing water quality standards for that waterbody (CWA §303(d)(1)(C)).
  - Note: In some circumstances, the load reductions determined to be necessary by the TMDL analysis may prove to be infeasible and may possibly indicate that the existing water quality standards and/or assessment methodologies may be erroneous. However, the TMDL must still be determined based on existing water quality standards. Adjustments to water quality standards and/or assessment methodologies may be evaluated separately, after the completion of the TMDL.
- ☐ The TMDL document should describe the relationship between the pollutant of concern and the water quality standard the pollutant load is intended to meet. This information is necessary for EPA to evaluate whether or not attainment of the prescribed pollutant loadings will result in attainment of the water quality standard in question.
- If a standard includes multiple criteria for the pollutant of concern, the document should demonstrate that the TMDL value will result in attainment of all related criteria for the pollutant. For example, both acute and chronic values (if present in the WQS) should be addressed in the document, including consideration of magnitude, frequency and duration requirements.

Re	commend	ation:
$\boxtimes$	Approve	☐ Partial Approval ☐ Disapprove ☐ Insufficient Information

### **Summary and Comments:**

The Tobacco Sediment document includes a description of all applicable water quality standards in Section 3.0 and a thorough discussion of water quality targets as well as an explanation of how the TMDLs are written to meet water quality standards in Section 5.

# 3.0 Water Quality Targets

TMDL analyses establish numeric targets that are used to determine whether water quality standards are being achieved. Quantified water quality targets or endpoints should be provided to evaluate each listed pollutant/water body combination addressed by the TMDL, and should represent achievement of applicable water quality standards and support of associated beneficial uses. For pollutants with numeric water quality standards, the numeric criteria are generally used as the water quality target. For pollutants with narrative standards, the narrative standard should be translated into a measurable value. At a minimum, one target is required for each pollutant/water body combination. It is generally desirable, however, to include several targets that represent achievement of the standard and support of beneficial uses (e.g., for a sediment impairment issue it may be appropriate to include a variety of targets representing water column sediment such as TSS, embeddeness, stream morphology, up-slope conditions and a measure of biota).

#### **Minimum Submission Requirements:**

The TMDL should identify a numeric water quality target(s) for each waterbody pollutant combination. The TMDL target is a quantitative value used to measure whether or not the applicable water quality standard is attained.

Generally, the pollutant of concern and the numeric water quality target are, respectively, the chemical causing the impairment and the numeric criteria for that chemical (e.g., chromium) contained in the water quality standard. Occasionally, the pollutant of concern is different from the parameter that is the subject of the numeric water quality target (e.g., when the pollutant of concern is phosphorus and the numeric water quality target is expressed as a numerical dissolved oxygen criterion). In such cases, the TMDL should explain the linkage between the pollutant(s) of concern, and express the quantitative relationship between the TMDL target and pollutant of concern. In all cases, TMDL targets must represent the attainment of current water quality standards.

When a numeric TMDL target is established to ensure the attainment of a narrative water quality criterion, the methodology used to determine the numeric target, and the link between the pollutant of concern and the narrative water quality criterion should all be described in the TMDL document. Any additional information supporting the numeric target and linkage should also be included in the document.

# **Recommendation:**☑ Approve ☐ Partial Approval ☐ Disapprove ☐ Insufficient Information

#### **Summary and Comments:**

Sediment targets are presented in Section 5.4 of the document. A suite of targets have been established to represent Montana's narrative sediment standards. The targets include Percentage of fine surface sediment in riffles < 6mm and <2mm (reach average via pebble count method); Percentage of fine surface sediment <6mm in riffles and pool tails (reach average via grid toss method); Bankfull width/depth ratio (median of channel x-sec measurements); Entrenchment ratio (median of channel x-sec measurements); Residual pool depth (reach average); Pools/mile; LWD/mile; Percent of streambank with understory shrub cover; significant and controllable sediment sources; and macroinvertebrate indices.

# 4.0 Pollutant Source Analysis

A TMDL analysis is conducted when a pollutant load is known or suspected to be exceeding the loading capacity of the waterbody. Logically then, a TMDL analysis should consider all sources of the pollutant of concern in some manner. The detail provided in the source assessment step drives the rigor of the pollutant load allocation. In other words, it is only possible to specifically allocate quantifiable loads or load reductions to each significant source (or source category) when the relative load contribution from each source has been estimated. Therefore, the pollutant load from each significant source (or source category) should be identified and quantified to the maximum practical extent. This may be accomplished using site-specific monitoring data, modeling, or application of other assessment techniques. If insufficient time or resources are available to accomplish this step, a phased/adaptive management approach can be employed so long as the approach is clearly defined in the document.

#### **Minimum Submission Requirements:**

- The TMDL should include an identification of all potentially significant point and nonpoint sources of the pollutant of concern, including the geographical location of the source(s) and the quantity of the loading, e.g., lbs/per day. This information is necessary for EPA to evaluate the WLA, LA and MOS components of the TMDL.
- The level of detail provided in the source assessment should be commensurate with the nature of the watershed and the nature of the pollutant being studied. Where it is possible to separate natural background from nonpoint sources, the TMDL should include a description of both the natural background loads and the nonpoint source loads.
- Natural background loads should not be assumed to be the difference between the sum of known and quantified anthropogenic sources and the existing *in situ* loads (e.g. measured in stream) unless it can be demonstrated that all significant anthropogenic sources of the pollutant of concern have been identified, characterized, and properly quantified.
- The sampling data relied upon to discover, characterize, and quantify the pollutant sources should be included in the document (e.g. a data appendix) along with a description of how the data were analyzed to characterize and quantify the pollutant sources. A discussion of the known deficiencies and/or gaps in the data set and their potential implications should also be included.

#### **Recommendation:**

$\boxtimes A_i$	pprove	☐ Partial A	Approval [	Disapprove		Insufficient	Information
-----------------	--------	-------------	------------	------------	--	--------------	-------------

#### **Summary and Comments:**

The sediment source assessment is presented in Section 5.6. Potentially significant sediment sources considered include streambank erosion, upland erosion, roads, and permitted point sources. Streambank erosion was quantified through direct measurements at sites on each listed stream. The measurements and loading estimates from the selected streams were then extrapolated to all streams based on a site stratification process (see Appendix E). Upland erosion was quantified by a simple USLE based approach that incorporated riparian buffer health (see Appendix F). Sediment loading from roads was derived from field measurements, modeling with WEPP, and GIS analyses (see Appendix G). Sediment from point sources was estimated based on site size, DMR data (when available), rainfall, and permit limits.

# 4.1 TMDL Technical Analysis

TMDL determinations should be supported by a robust data set and an appropriate level of technical analysis. This applies to <u>all</u> of the components of a TMDL document. It is vitally important that the technical basis for <u>all</u> conclusions be articulated in a manner that is easily understandable and readily apparent to the reader.

A TMDL analysis determines the maximum pollutant loading rate that may be allowed to a waterbody without violating water quality standards. The TMDL analysis should demonstrate an understanding of the relationship between the rate of pollutant loading into the waterbody and the resultant water quality impacts. This stressor → response relationship between the pollutant and impairment and between the selected targets, sources, TMDLs, and load allocations needs to be clearly articulated and supported by an appropriate level of technical analysis. Every effort should be made to be as detailed as possible, and to base all conclusions on the best available scientific principles.

The pollutant loading allocation is at the heart of the TMDL analysis. TMDLs apportion responsibility for taking actions by allocating the available assimilative capacity among the various point, nonpoint, and natural pollutant sources. Allocations may be expressed in a variety of ways, such as by individual discharger, by tributary watershed, by source or land use category, by land parcel, or other appropriate scale or division of responsibility.

The pollutant loading allocation that will result in achievement of the water quality target is expressed in the form of the standard TMDL equation:

$$TMDL = \sum LAs + \sum WLAs + MOS$$

Where:

TMDL = Total Pollutant Loading Capacity of the waterbody

LAs = Pollutant Load Allocations

WLAs = Pollutant Wasteload Allocations

MOS = The portion of the Load Capacity allocated to the Margin of safety.

#### Minimum Submission Requirements:

- A TMDL must identify the loading capacity of a waterbody for the applicable pollutant, taking into consideration temporal variations in that capacity. EPA regulations define loading capacity as the greatest amount of a pollutant that a water can receive without violating water quality standards (40 C.F.R. §130.2(f)).
- The total loading capacity of the waterbody should be clearly demonstrated to equate back to the pollutant load allocations through a balanced TMDL equation. In instances where numerous LA, WLA and seasonal TMDL capacities make expression in the form of an equation cumbersome, a table may be substituted as long as it is clear that the total TMDL capacity equates to the sum of the allocations.
- The TMDL document should describe the methodology and technical analysis used to establish and quantify the cause-and-effect relationship between the numeric target and the identified pollutant sources. In many instances, this method will be a water quality model.
- It is necessary for EPA staff to be aware of any assumptions used in the technical analysis to understand and evaluate the methodology used to derive the TMDL value and associated loading allocations. Therefore, the TMDL document should contain a description of any important assumptions (including the basis for those assumptions) made in developing the TMDL, including but not limited to:

- (1) the spatial extent of the watershed in which the impaired waterbody is located and the spatial extent of the TMDL technical analysis;
- (2) the distribution of land use in the watershed (e.g., urban, forested, agriculture);
- (3) a presentation of relevant information affecting the characterization of the pollutant of concern and its allocation to sources such as population characteristics, wildlife resources, industrial activities etc...;
- (4) present and future growth trends, if taken into consideration in determining the TMDL and preparing the TMDL document (e.g., the TMDL could include the design capacity of an existing or planned wastewater treatment facility);
- (5) an explanation and analytical basis for expressing the TMDL through surrogate measures, if applicable. Surrogate measures are parameters such as percent fines and turbidity for sediment impairments; chlorophyll *a* and phosphorus loadings for excess algae; length of riparian buffer; or number of acres of best management practices.
- ∑ The TMDL document should contain documentation supporting the TMDL analysis, including an inventory of the data set used, a description of the methodology used to analyze the data, a discussion of strengths and weaknesses in the analytical process, and the results from any water quality modeling used. This information is necessary for EPA to review the loading capacity determination, and the associated load, wasteload, and margin of safety allocations.
- ▼ TMDLs must take critical conditions (e.g., steam flow, loading, and water quality parameters, seasonality, etc...) into account as part of the analysis of loading capacity (40 C.F.R. §130.7(c)(1)). TMDLs should define applicable critical conditions and describe the approach used to determine both point and nonpoint source loadings under such critical conditions. In particular, the document should discuss the approach used to compute and allocate nonpoint source loadings, e.g., meteorological conditions and land use distribution.
- ☐ Where both nonpoint sources and NPDES permitted point sources are included in the TMDL loading allocation, and attainment of the TMDL target depends on reductions in the nonpoint source loads, the TMDL document must include a demonstration that nonpoint source loading reductions needed to implement the load allocations are actually practicable [40 CFR 130.2(i) and 122.44(d)].

### **Recommendation:**

🛮 Approve 🗌 Partial Approval 🗎 Disapprove 🗌 Insufficient Infor	mation
--	--------

#### **Summary and Comments:**

An adequate technical analysis has been completed. Summary information is presented in the main body of the document and supporting analyses/data are presented in appendices.

#### **4.1.1** *Data Set Description*

TMDL documents should include a thorough description and summary of all available water quality data that are relevant to the water quality assessment and TMDL analysis. An inventory of the data used for the TMDL analysis should be provided to document, for the record, the data used in decision making. This also provides the reader with the opportunity to independently review the data. The TMDL analysis should make use of all readily available data for the waterbody under analysis unless the TMDL writer determines that the data are not relevant or appropriate. For relevant data that were known but rejected, an explanation of why the data were not utilized should be provided (e.g., samples exceeded holding times, data collected prior to a specific date were not considered timely, etc...).

#### **Minimum Submission Requirements:**

MDL documents should include a thorough description and summary of all available water quality data that are relevant to the water quality assessment and TMDL analysis such that the water quality impairments are clearly defined and linked to the impaired beneficial uses and appropriate water quality criteria.

	The TMDL document submitted should be accompanied by the data set utilized during the TMDL analysis. If possible, it is preferred that the data set be provided in an electronic format and referenced in the document. If electronic submission of the data is not possible, the data set may be included as an appendix to the document.
Rec	commendation:
$\boxtimes$	Approve ☐ Partial Approval ☐ Disapprove ☐ Insufficient Information
Sur	mmary and Comments:
	e data and technical analyses are summarized in the main body of the document and presented in the pendices (Appendices D-G).
	4.1.2 Waste Load Allocations (WLA):
typ: Wh per ide	ste Load Allocations represent point source pollutant loads to the waterbody. Point source loads are ically better understood and more easily monitored and quantified than nonpoint source loads, enever practical, each point source should be given a separate waste load allocation. All NPDES mitted dischargers that discharge the pollutant under analysis directly to the waterbody should be ntified and given separate waste load allocations. The finalized WLAs are required to be incorporated of future NPDES permit renewals.
Min	nimum Submission Requirements:
	EPA regulations require that a TMDL include WLAs for all significant and/or NPDES permitted point sources of the pollutant. TMDLs must identify the portion of the loading capacity allocated to individual existing and/or future point source(s) (40 C.F.R. §130.2(h), 40 C.F.R. §130.2(i)). In some cases, WLAs may cover more than one discharger, e.g., if the source is contained within a general permit. If no allocations are to be made to point sources, then the TMDL should include a value of zero for the WLA.
	All NPDES permitted dischargers given WLA as part of the TMDL should be identified in the TMDL, including the specific NPDES permit numbers, their geographical locations, and their associated waste load allocations.
Rec	commendation:
$\boxtimes$	Approve ☐ Partial Approval ☐ Disapprove ☐ Insufficient Information ☐ No-action
Sur	mmary and Comments:
	NPDES permitted point sources received WLAs. Separate WLAs were provided for a wastewater atment facility and for a facility permitted under the general stormwater permit for discharges

All NPDES permitted point sources received WLAs. Separate WLAs were provided for a wastewater treatment facility and for a facility permitted under the general stormwater permit for discharges associated with mining and oil and gas activities. The six general permits for stormwater construction discharges were given composite wasteload allocations for each impaired segment with permitted dischargers. Permit numbers and other required information was presented. All WLAs rely on permittees following permit requirements.

#### **4.1.3** *Load Allocations (LA):*

Load allocations include the nonpoint source, natural, and background loads. These types of loads are typically more difficult to quantify than point source loads, and may include a significant degree of uncertainty. Often it is necessary to group these loads into larger categories and estimate the loading rates based on limited monitoring data and/or modeling results. The background load represents a composite of all upstream pollutant loads into the waterbody. In addition to the upstream nonpoint and upstream natural load, the background load often includes upstream point source loads that are not given specific waste load allocations in this particular TMDL analysis. In instances where nonpoint source loading rates are particularly difficult to quantify, a performance-based allocation approach, in which a detailed monitoring plan and adaptive management strategy are employed for the application of BMPs, may be appropriate.

Minimum Submission Requirements:

$\boxtimes$	EPA regulations require that TMDL expressions include LAs which identify the portion of the loading capacity
	attributed to nonpoint sources and to natural background. Load allocations may range from reasonably accurate
	estimates to gross allotments (40 C.F.R. §130.2(g)). Load allocations may be included for both existing and
	future nonpoint source loads. Where possible, load allocations should be described separately for natural
	background and nonpoint sources.
$\Box$	Load allocations assigned to natural hadraround loads should not be assumed to be the difference between the

□ Load allocations assigned to natural background loads should not be assumed to be the difference between the sum of known and quantified anthropogenic sources and the existing in situ loads (e.g., measured in stream) unless it can be demonstrated that all significant anthropogenic sources of the pollutant of concern have been identified and given proper load or waste load allocations.

#### **Recommendation:**

$\boxtimes$	Approve		Partial	Approval		Disapprove		Insufficient	Informat	ion
-------------	---------	--	---------	----------	--	------------	--	--------------	----------	-----

#### **Summary and Comments:**

LAs are broken out in each TMDL by source category and are presented as percent reductions as well as daily loads (tons/day). The background load is broken out for the LA to streambank erosion but provided as a composite load allocation to nonpoint and background sources for the other source categories.

#### **4.1.4** *Margin of Safety (MOS):*

Natural systems are inherently complex. Any mathematical relationship used to quantify the stressor  $\rightarrow$  response relationship between pollutant loading rates and the resultant water quality impacts, no matter how rigorous, will include some level of uncertainty and error. To compensate for this uncertainty and ensure water quality standards will be attained, a margin of safety is required as a component of each TMDL. The MOS may take the form of a explicit load allocation (e.g., 10 lbs/day), or may be implicitly built into the TMDL analysis through the use of conservative assumptions and values for the various factors that determine the TMDL pollutant load  $\rightarrow$  water quality effect relationship. Whether explicit or implicit, the MOS should be supported by an appropriate level of discussion that addresses the level of uncertainty in the various components of the TMDL technical analysis, the assumptions used in that analysis, and the relative effect of those assumptions on the final TMDL. The discussion should demonstrate that the MOS used is sufficient to ensure that the water quality standards would be attained if the TMDL pollutant loading rates are met. In cases where there is substantial uncertainty regarding the linkage between the proposed allocations and achievement of water quality standards, it may be necessary to employ a phased or adaptive management approach (e.g., establish a monitoring plan to determine if the proposed allocations are, in fact, leading to the desired water quality improvements).

### **Minimum Submission Requirements:**

	rela §13 TM	tionship between load and wasteload allocations and water quality (CWA §303(d)(1)(C), 40 C.F.R. 0.7(c)(1)). EPA's 1991 TMDL Guidance explains that the MOS may be implicit (i.e., incorporated into the DL through conservative assumptions in the analysis) or explicit (i.e., expressed in the TMDL as loadings aside for the MOS).
		If the MOS is implicit, the conservative assumptions in the analysis that account for the MOS should be identified and described. The document should discuss why the assumptions are considered conservative and the effect of the assumption on the final TMDL value determined.
		<u>If the MOS is explicit</u> , the loading set aside for the MOS should be identified. The document should discuss how the explicit MOS chosen is related to the uncertainty and/or potential error in the linkage analysis between the WQS, the TMDL target, and the TMDL loading rate.
		<u>If</u> , rather than an explicit or implicit MOS, the <u>TMDL relies upon a phased approach</u> to deal with large and/or unquantifiable uncertainties in the linkage analysis, the document should include a description of the planned phases for the TMDL as well as a monitoring plan and adaptive management strategy.
		mendation:  orove ☐ Partial Approval ☐ Disapprove ☐ Insufficient Information
Sui	nma	ary and Comments:

The document provides an implicit margin of safety through conservative assumptions and the use of an adaptive management strategy.

### **4.1.5** Seasonality and variations in assimilative capacity:

The TMDL relationship is a factor of both the loading rate of the pollutant to the waterbody and the amount of pollutant the waterbody can assimilate and still attain water quality standards. Water quality standards often vary based on seasonal considerations. Therefore, it is appropriate that the TMDL analysis consider seasonal variations, such as critical flow periods (high flow, low flow), when establishing TMDLs, targets, and allocations.

Minimum Subn	nission Requirements:
☐ The statute a	and regulations require that a TMDL be established with consideration of seasonal variations. The describe the method chosen for including seasonal variability as a factor. (CWA §303(d)(1)(C), 40
<b>Recommendat</b> ⊠ Approve [	ion: ☐ Partial Approval ☐ Disapprove ☐ Insufficient Information
Summary an	d Comments:

Seasonality considerations are incorporated into the data collection timeframe as well as the source assessments. Based on the timing of sediment loading and the critical period for sediment impairment, the percent reduction approach using an annual timescale is appropriate. As required, daily loads are also provided in Appendix H.

# **5.0 Monitoring Strategy**

TMDLs may have significant uncertainty associated with the selection of appropriate numeric targets and estimates of source loadings and assimilative capacity. In these cases, a phased TMDL approach may be necessary. For Phased TMDLs, it is EPA's expectation that a monitoring plan will be included as a component of the TMDL document to articulate the means by which the TMDL will be evaluated in the field, and to provide for future supplemental data that will address any uncertainties that may exist when the document is prepared.

# **Minimum Submission Requirements:**

$\bowtie$	When a TMDL involves both NPDES permitted point source(s) and nonpoint source(s) allocations, and attainment of the TMDL target depends on reductions in the nonpoint source loads, the TMDL document should include a monitoring plan that describes the additional data to be collected to determine if the load reductions provided for in the TMDL are occurring.
	Under certain circumstances, a phased TMDL approach may be utilized when limited existing data are relied upon to develop a TMDL, and the State believes that the use of additional data or data based on better analytica techniques would likely increase the accuracy of the TMDL load calculation and merit development of a second phase TMDL. EPA recommends that a phased TMDL document or its implementation plan include a monitoring plan and a scheduled timeframe for revision of the TMDL. These elements would not be an intrinsic part of the TMDL and would not be approved by EPA, but may be necessary to support a rationale for approving the TMDL. http://www.epa.gov/owow/tmdl/tmdl_clarification_letter.pdf
	commendation: Approve □ Partial Approval □ Disapprove □ Insufficient Information

**Summary and Comments**: Although most stream segments only have nonpoint sources and WLAs are based on meeting the standard at the end of pipe or are related to construction stormwater, a conceptual monitoring strategy is provided in Section 6.3.

# 6.0 Restoration Strategy

The overall purpose of the TMDL analysis is to determine what actions are necessary to ensure that the pollutant load in a waterbody does not result in water quality impairment. Adding additional detail regarding the proposed approach for the restoration of water quality is not currently a regulatory requirement, but is considered a value added component of a TMDL document. During the TMDL analytical process, information is often gained that may serve to point restoration efforts in the right direction and help ensure that resources are spent in the most efficient manner possible. For example, watershed models used to analyze the linkage between the pollutant loading rates and resultant water quality impacts might also be used to conduct "what if" scenarios to help direct BMP installations to locations that provide the greatest pollutant reductions. Once a TMDL has been written and approved, it is often the responsibility of other water quality programs to see that it is implemented. The level of quality and detail provided in the restoration strategy will greatly influence the future success in achieving the needed pollutant load reductions.

### **Minimum Submission Requirements:**

EPA is not required to and does not approve TMDL implementation plans. However, in cases where a WLA is dependent upon the achievement of a LA, "reasonable assurance" is required to demonstrate the necessary LA

to be relied upon to achieve the LA(s), and programs and funding sources that will be relied upon to implement the load reductions called for in the document, may be included in the implementation/restoration section of the TMDL document to support a demonstration of "reasonable assurance". **Recommendation:** ✓ Approve ☐ Partial Approval ☐ Disapprove ☐ Insufficient Information ☐ No-action **Summary and Comments:** Most of the stream segments addressed in the Tobacco document only have nonpoint sources, and no RA is necessary. DEQ has provided a restoration strategy, as well as a summary of available funding, for all of the impaired streams in the Tobacco watershed, including those that have point sources. 7.0 Daily Loading Expression The goal of a TMDL analysis is to determine what actions are necessary to attain and maintain WQS. The appropriate averaging period that corresponds to this goal will vary depending on the pollutant and the nature of the waterbody under analysis. When selecting an appropriate averaging period for a TMDL analysis, primary concern should be given to the nature of the pollutant in question and the achievement of the underlying WQS. However, recent federal appeals court decisions have pointed out that the title TMDL implies a "daily" loading rate. While the most appropriate averaging period to be used for developing a TMDL analysis may vary according to the pollutant, a daily loading rate can provide a more practical indication of whether or not the overall needed load reductions are being achieved. When limited monitoring resources are available, a daily loading target that takes into account the natural variability of the system can serve as a useful indicator for whether or not the overall load reductions are likely to be met. Therefore, a daily expression of the required pollutant loading rate is a required element in all TMDLs, in addition to any other load averaging periods that may have been used to conduct the TMDL analysis. The level of effort spent to develop the daily load indicator should be based on the overall utility it can provide as an indicator for the total load reductions needed. **Minimum Submission Requirements:** The document should include an expression of the TMDL in terms of a daily load. However, the TMDL may also be expressed in temporal terms other than daily (e.g., an annual or monthly load). If the document expresses the TMDL in additional "non-daily" terms the document should explain why it is appropriate or advantageous to express the TMDL in the additional unit of measurement chosen. **Recommendation:** ☐ Approve ☐ Partial Approval ☐ Disapprove ☐ Insufficient Information **Summary and Comments:** The sediment TMDLs are presented as tons/day in Appendix H.

called for in the document is practicable). A discussion of the BMPs (or other load reduction measures) that are

# 8.0 Public Participation

EPA regulations require that the establishment of TMDLs be conducted in a process open to the public, and that the public be afforded an opportunity to participate. To meaningfully participate in the TMDL process it is necessary that stakeholders, including members of the general public, be able to understand the problem and the proposed solution. TMDL documents should include language that explains the issues to the general public in understandable terms, as well as provides additional detailed technical information for the scientific community. Notifications or solicitations for comments regarding the TMDL should be made available to the general public, widely circulated, and clearly identify the product as a TMDL and the fact that it will be submitted to EPA for review. When the final TMDL is submitted to EPA for approval, a copy of the comments received by the state and the state responses to those comments should be included with the document.

Miı	nimum Submission Requirements:
$\boxtimes$	The TMDL must include a description of the public participation process used during the development of
the	TMDL (40 C.F.R. §130.7(c)(1)(ii)).
$\boxtimes$	TMDLs submitted to EPA for review and approval should include a summary of significant comments and the State's/Tribe's responses to those comments.
Re	commendation:
$\boxtimes$	Approve

**Summary and Comments:** The document is fairly technical but does include a description of the TMDL process and an explanation of the solution in plain terms. The public participation process and a description of key stakeholders are summarized in Section 7.0. The document was sent out for public comment on July 20, 2011 and the comment period extended until August 22, 2011. One comment letter was received; responses are contained in Appendix I.

Table 1. Stream Segments in the Tobacco TMDL Planning Area Addressed in this Document, Their Associated Levels of Beneficial Use-Support, and Causes of Impairment.

Support, and Causes of In			Impa	ired Be	neficial	Uses					
Waterbody & Stream Description	Waterbody ID	Agriculture	Aquatic Life	Cold Water Fishery	Drinking Water	Industry	Contact Recreation	Cycle First Listed	Cause of Impairment	Pollutant for which TMDL has been prepared	DEQ Action
								N/A	Excess Algal Growth	N/A	Not Addressed
<b>Deep Creek,</b> headwaters to mouth (Fortine Creek)	MT76D004_080	F	Р	Р	F	F	P	N/A	Alteration in stream-side or littoral vegetative covers	N/A	Addressed by sediment TMDL
								2006	Sedimentation / Siltation	Sediment	TMDL
Edna Creek, headwaters to mouth (Fortine Creek)	MT76D004_030	F	P	F	F	F	F	1992	Sedimentation / Siltation	Sediment	TMDL
	MT76D004_020			P	F			N/A	Alteration in stream-side or littoral vegetative covers	N/A	Addressed by sediment TMDL
Fortine Creek, headwaters to			P					N/A	Excess Algal Growth	N/A	Not Addressed
mouth (Grave Creek)		F				F	Р	2006	Temperature (water)	N/A	Not Addressed
								1990	Sedimentation / Siltation	Sediment	TMDL
								N/A	Low flow alterations	N/A	Not Addressed
								2006	Arsenic	N/A	Not Addressed
	MT76D004_050							2006	Phosphorus (Total)	N/A	Not Addressed
No College de la companya de la college de l								2006	Total Kjehldahl Nitrogen (TKN)	N/A	Not Addressed
Lime Creek, headwaters to mouth (Fortine Creek)		F	N	N	N	F	P	N/A	Chlorophyll-a	N/A	Not Addressed
								N/A	Alteration in stream-side or littoral vegetative covers	N/A	Addressed by sediment TMDL
								1996	Sedimentation / Siltation	Sediment	TMDL
Sinclair Creek, confluence of unnamed tributary to mouth (Tobacco River)	MT76D004_091	X	P	P	X	X	X	> 2010	Sedimentation / Siltation	Sediment	TMDL

		Impaired Beneficial Uses									
Waterbody & Stream Description	Waterbody ID	Agriculture	Aquatic Life	Cold Water Fishery	Drinking Water	Industry	Contact Recreation	Cycle First Listed	Cause of Impairment	Pollutant for which TMDL has been prepared	DEQ Action
Swamp Creek, headwaters to	MT76D004_040	F	P	P	F	F		N/A	Alterations in stream-side or littoral vegetative covers	N/A	Addressed by sediment TMDL
mouth (Fortine Creek)							P	N/A	Low flow alterations	N/A	Not Addressed
								1992	Sedimentation / Siltation	Sediment	TMDL
Therriault Creek, headwaters to mouth (Tobacco River)	MT76D004_070	F	Р	Р	F	F	F	1988	Sedimentation / Siltation	Sediment	TMDL
<b>Tobacco River,</b> confluence of Grave Creek & Fortine Creek to	MT76D004 010	F	P	P	F	F	F	N/A	Physical substrate habitat alterations	N/A	Addressed by sediment TMDL
mouth (Lake Koocanusa)	141700004_010	1	ľ	r	Г		F	1988	Sedimentation / Siltation	Sediment	TMDL

F = Fully Supporting, P = Partially Supporting, N = Not Supporting, X = Not Assessed

Table 2. Waterbody segments addressed by <u>sediment</u> TMDLs.

Stream Segment	Waterbody ID
Deep Creek, headwaters to mouth (Fortine Creek)	MT76D004_080
Edna Creek, headwaters to mouth (Fortine Creek)	MT76D004_030
Fortine Creek, headwaters to mouth (Grave Creek)	MT76D004_020
Lime Creek, headwaters to mouth (Fortine Creek)	MT76D004_050
Sinclair Creek, confluence of un-named tributary to mouth (Tobacco River)	MT76D004_091
Swamp Creek, headwaters to mouth (Fortine Creek)	MT76D004_040
Therriault Creek, headwaters to mouth (Tobacco River)	MT76D004_070
Tobacco River, confluence of Grave Creek & Fortine Creek to mouth (Lake Koocanusa)	MT76D004_010