STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
	ACTION-SPECIFIC ERCLS		
WATER QUALITY REQ	QUIREMENTS, generally found in the Montana Water Quality Act at §§ 75-5-101, et seq.,	, MCA.	
33 USC §1342 Section 402; 40 CFR 122.26	Clean Water Act, Point Source Discharges Requirements, 33 USC § 1342: Section 402 of the Clean Water Act, 33 USC § 1342, <i>et seq.</i> , authorizes the issuance of permits for the discharge of any pollutant. This includes storm water discharges associated with industrial activity. <i>See</i> 40 Code of Federal Regulations (CFR) 122.26(a)(ii). Industrial activity includes inactive mining operations that discharge storm water contaminated by contact with or that has come into contact with any overburden, raw material, intermediate products, finished products, byproducts or waste products located on the site of such operations, <i>see</i> 40 CFR 122.26(b)(14)(iii); landfills, land application sites, and open dumps that receive or have received any industrial wastes including those subject to regulation under Resource Conservation and Recovery Act (RCRA) subtitle D, <i>see</i> 40 CFR 122.26(b)(14)(v); and construction activity including clearing, grading, and excavation activities, <i>see</i> 40 CFR 122.26(b)(14)(x). Because the State of Montana has been delegated the authority to implement the Clean Water Act, these requirements are enforced in Montana through the Montana Pollutant Discharge Elimination System (MPDES).	Applicable	A permit will be obtained prior to initiation of cleanup activities and the conditions of the permit will be met throughout the remediation. Therefore, the proposed remedy meets the requirements of this ERCL.
ARM 17.30.1342(4) and (5) ARM 17.30.1343 ARM 17.30.1344	ARM 17.30.1342-1344: The State of Montana has been delegated the authority to implement the Clean Water Act and these requirements are enforced in Montana through the MPDES. These regulations set forth the substantive requirements applicable to all MPDES and National Pollutant Discharge Elimination System permits. The substantive requirements, including the requirement to properly operate and maintain all facilities and systems of treatment and control, are applicable requirements.	Applicable	The tasks detailed in the ROD do not include wastewater discharges. Leachate will be collected and stored for either recirculation into the LTU or offsite disposal, depending on the properties of the leachate and the LTU irrigation needs. Excess leachate or groundwater collected during sampling activities will be used in the LTU or disposed offsite or discharged to the sanitary sewer system (if allowable) through a discharge permit.
§ 75-5-605(1)(a) and (c), MCA § 75-5-303(1) and (2), MCA	The Montana Water Quality Act, §§ 75-5-101, et seq., MCA, prohibits causing pollution of any state waters. Section 75-5-605(1)(a), MCA. Pollution is defined as contamination or other alteration of physical, chemical, or biological properties of state waters which exceeds that permitted by the water quality standards or the discharge, seepage, or drainage of any substances into state water that will likely create a nuisance or render the water harmful, detrimental or injurious to public health, recreation, safety, or welfare, or to livestock or wild animals. Section 75-5-103(30)(a), MCA. Also, it is unlawful to place or cause to be placed any wastes where they will cause pollution of any state waters or to cause degradation of state waters without authorization pursuant to § 75-5-303, MCA. Sections 75-5-605(1)(a) and (c), MCA.	Applicable	To protect state waters from degradation/pollution, wastes generated during remedial activities will be stored and treated or disposed in such a manner as to not impact groundwater quality. Soil excavated from contaminant of concern (COC)-impacted so areas will be placed on liners to prevent contamination of surrounding surficial soil or contamination of the groundwater. If groundwater is collected during excavation or sampling activities, it will be disposed offsite. Contaminated soils and other contaminated media will be treated, recycled or disposed in accordance with solid and hazardous waste ERCLs in a manner that does not degrade water quality. This work plan addresses releases that may occur during COC-impacted soils excavation activities.
	Section 75-5-303, MCA, states that existing uses of state waters and the level of water quality necessary to protect the uses must be maintained and protected, with certain limited exceptions. Section 75-5-317, MCA, provides an exemption from non-degradation requirements which allows changes of existing water quality resulting from an emergency action or reclamation that is designed to protect the public health or the environment and that is approved, authorized, or required by the department. Degradation meeting these requirements may be considered nonsignificant.		

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
ARM 17.30.637 ARM 17.30.705(2)	ARM 17.30.637 prohibits certain discharges to surface waters including substances that will: (a) settle to form objectionable sludge deposits or emulsions beneath the surface of the water or upon adjoining shorelines; (b) create floating debris, scum, a visible oil film (or be present in concentrations at or in excess of 10 milligrams per liter) or globules of grease or other floating materials; (c) produce odors, colors or other conditions which create a nuisance or render undesirable tastes to fish flesh or make fish inedible; (d) create concentrations or combinations of materials which are toxic or harmful to human, animal, plant or aquatic life; or (e) create conditions which produce undesirable aquatic life. ARM 17.30.637 also states that no waste may be discharged and no activities conducted which, either alone or in combination with other waste activities, will cause violation of surface water quality standards. ARM 17.30.705(2) provides that for all state waters, existing and anticipated uses and the water quality necessary to protect these uses must be maintained and protected unless degradation of high quality waters is allowed under the non-degradation rules at ARM 17.30.708.	Applicable	To prevent state waters from degradation, wastes generated during remedy implementation activities will be stored and treated or disposed of in such a manner as to not impact groundwater quality. Contaminated soil and other contaminated media will be treated, recycled or disposed of in accordance with solid and hazardous waste ERCLs in a manner that does not impact water quality. Best management practices (BMPs) will be implemented to prevent impact of surface waters from site contaminants or sediment. No samples will be collected within 200 feet of surface water and excavated areas will be backfilled with soils remaining after sample collection and regraded/reshaped to the same topography as the surrounding area. Therefore, the remedial activities will not impact surface water.
ARM 17.30.1203(1), (3), (5), (8) ARM 17.30.1207(1)	ARM 17.30.1203(1), (3), (5), (8) and ARM 17.30.1207(1): If point sources of water contamination are retained or created by any remediation activity, applicable Clean Water Act standards would apply to those discharges. The State of Montana established state standards in conformity with the Clean Water Act, and these standards apply to point source discharges.	Applicable	A permit will be obtained prior to initiation of cleanup activities and the conditions of the permit will be met throughout the remediation. Therefore, the proposed remedy meets the requirements of this ERCL.
STORMWATER RUNO	FF CONTROL REQUIREMENTS		
ARM 17.24.633	ARM 17.24.633, provides all surface drainage from a disturbed area must be treated by the best technology currently available (BTCA). Sediment control through BTCA must be maintained until the disturbed area has been reclaimed, the revegetation requirements have been met, and the area meets state and federal requirements for the receiving stream.	Relevant	A Storm Water Pollution Prevention Plan (SWPPP) has been prepared because the disturbed acreage is greater than 1 acre and is included as Appendix F to this work plan. MDEQ has exempted the liable party from the requirement for the procedural portions of a MPDES General Permit because the SWPPP addresses the substantive requirements contained in the storm water management regulations. BMPs that will be placed or followed include decontamination pads, stone covered driveway, and vehicle tracking pad placement along the traffic route. Spill kits will be placed in the exclusion zone and support zone. Water or spray-on chemical agents will be applied to control dust during excavation and loading. Live loading of trucks will minimize the use of stockpiles. Stockpiles will be covered by polyethylene sheeting and weighted tarps. Decontamination pads will be constructed and used to prevent the tracking of impacted soil from those areas. Impacted soil will be loaded into lined trucks and the loads will be covered by tarps during transit.
ARM 17.30.1342(4) and (5) ARM 17.30.1343 ARM 17.30.1344	ARM 17.30.1342-1344: The State of Montana has been delegated the authority to implement the Clean Water Act and these requirements are enforced in Montana through the MPDES. These regulations set forth the substantive requirements applicable to all MPDES and National Pollutant Discharge Elimination System permits. The substantive requirements, including the requirement to properly operate and maintain all facilities and systems of treatment and control, are applicable requirements.	Applicable	A permit will be obtained prior to initiation of cleanup activities and the conditions of the permit will be met throughout the remediation. Therefore, the proposed remedy meets the requirements of this ERCL.

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
activities or emissions re	ARDS, generally found in the Clean Air Act of Montana at §§ 75-2-101, et seq., MCA. The esulting from wind erosion of exposed hazardous substances. State emission standards are They are also enforceable under the Clean Air Act of Montana, §§ 75-2-101, et seq., MCA.	,	
§ 75-2-203, MCA	Section 75-2-203, MCA provides that state emission standards are enforceable under the Clean Air Act of Montana.	Applicable	See examples below.
ARM 17.8.204(2)-(3) ARM 17.8.220	ARM 17.8.204(2)-(3) provides for ambient air monitoring and provides that, generally, all ambient air monitoring, sampling, and data collection, recording, analysis, and transmittal must be in compliance with the Montana Ambient Air Monitoring Program Quality Assurance Project Plan or a Quality Assurance Project Plan, depending on who is performing the monitoring. ARM 17.8.220 provides that no person shall cause or contribute to concentrations of particulate matter in the ambient air such that the mass of settled particulate matter exceeds a 30-day average of 10 grams per square meter. ARM 17.8.220(1)(a). Compliance is determined by the dust fall method or equivalent to measure large particulates. ARM 17.8.220(2).	Applicable	BMPs implemented will include dust control measures such as spraying of water or other dust suppressant onto the surface of soils that are being disturbed to prevent particles or contaminants from becoming airborne and procedures for air monitoring to verify compliance with ambient air standards. Monitoring procedures are identified in the design report. Remedial actions will be halted if air monitoring indicates dust levels are approaching air quality limitations and will not resume until adequate dust control measures are in place.
ARM 17.8.308 and ARM 17.8.304(2)	ARM 17.8.308(1) and ARM 17.8.304(2) state that emissions of airborne particulate matter must be controlled so that they do not "exhibit an opacity of 20% or greater averaged over 6 consecutive minutes." Unless excluded by ARM 17.8.308(5), ARM 17.8.308(1)-(3) provides that no person shall cause or authorize the production, handling, transportation or storage of any material; or cause or authorize the use of any street, road, or parking lot; or operate a construction facility or demolition project, unless reasonable precautions to control emissions of airborne particulate matter are taken. Other requirements are set forth in ARM 17.8.308(4) for any area designated nonattainment in 40 CFR 81.327 for PM, specifically.	Applicable	Non-point source discharges may occur due to excavation, soil treatment, and other land disturbance activities. Dust control measures such as application to prevent particles or contaminants from becoming airborne, covers, fences, or spray-on chemical agents and procedures for air monitoring to verify compliance with ambient air standards may be necessary to meet air quality requirements. Excavation or backfill actions will be halted if air monitoring indicates dust concentrations are approaching air quality limitations and will not resume until adequate dust control measures are in place.
ARM 17.8.324	ARM 17.8.324 contains standards regarding hydrocarbon emissions and the treatment, storage, and handling of petroleum products.	Applicable	The proposed remedy does not involve the treatment, storage or handling of petroleum products other than basic refueling of construction equipment.
ARM 17.8.604	ARM 17.8.604 contains requirements for a list of certain wastes that may not be disposed of by open burning, including but not limited to oil or petroleum products, RCRA hazardous wastes, chemicals and wood and wood byproducts that have been coated, painted, stained, treated or contaminated by foreign material. Any waste which is moved from the premises where it was generated, and any trade waste may be open burned only in accordance with the substantive requirements of ARM 17.8.611 or 612(4)(a) or (4)(b) or if DEQ makes a determination pursuant to ARM 17.8.604(2).	Applicable	No open burning of wastes will be conducted as part of the remedial actions.

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
ARM 17.8.802	ARM 17.8.802 incorporates by reference the air regulations in certain parts of CFR Title 40 regarding quality assurance requirements for prevention of significant deterioration air monitoring; standards of performance for new stationary sources; emission standards for hazardous air pollutants, and other standards and requirements.	Applicable	BMPs implemented will include dust control measures such as spraying of water or other dust suppressant onto the surface of soils that are being disturbed to prevent particles or contaminants from becoming airborne and procedures for air monitoring to verify compliance with ambient air standards. Monitoring procedures are identified in the design report. Remedial actions will be halted if air monitoring indicates dust levels are approaching air quality limitations and will not resume until adequate dust control measures are in place.
ARM 17.8.805(1)	ARM 17.8.805(1) provides ambient air ceilings, and states that no concentrations of a pollutant shall exceed concentrations permitted under either the applicable secondary or the primary national ambient air quality standard, whichever concentration is lowest for the pollutant for a period of exposure.	Relevant	The proposed remedy will not result in emissions of the specific compounds included in these regulations.
ARM 17.24.761	ARM 17.24.761 specifies a range of measures for controlling fugitive dust emissions during mining and reclamation activities. Some of the measures could be considered relevant to control fugitive dust emissions in connection with excavation, earth moving, and transportation activities conducted as part of the remedy at the facility. Such measures include, for example, paving, watering, chemically stabilizing, or frequently compacting and scraping roads, promptly removing rock, soil or other dust-forming debris from roads, restricting vehicle speeds, revegetating, mulching, or otherwise stabilizing the surface of areas adjoining roads, restricting unauthorized vehicle travel, minimizing the area of disturbed land, and promptly revegetating regraded lands. See § 82-4-231(10)(m), MCA.	Relevant	The proposed remedy does involve handling impacted soil. However, remedial actions at the facility will include wetting and other best management practices related to fugitive dust control. Remedial actions will be halted if significant dust is generated and will not resume until adequate dust control measures are in place. Dust control measures will ensure that air standards will not be exceeded during the proposed remedial action. Air monitoring is not a necessary component of the proposed remedial action.
WATER WELL REQUI	REMENTS		
§85-2-505(1), MCA	Section 85-2-505(1), MCA precludes the wasting of groundwater. Any well producing waters that contaminate other waters must be plugged or capped, and wells must be constructed and maintained to prevent waste, contamination, or pollution of groundwater. However, withdrawal or use of groundwater is not considered waste pursuant to § 85-2-505(1)(a)-(e), MCA.	Applicable	A groundwater monitoring plan will be developed as part of long-term groundwater monitoring. New wells may be installed as part of the long-term groundwater monitoring program. Wells will be properly constructed to prevent further contamination or pollution of groundwater. Drilling subcontracts will require that drillers complete and file a well log report with the Montana Bureau of Mines and Geology. Compliance water quality monitoring will be conducted using methods approved by DEQ.

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
ARM 36.21.802-808 ARM 36.21.810	ARM 36.21.802-808 specifies requirements for constructing monitoring wells. ARM 36.21.810 specifies requirements that must be fulfilled when abandoning monitoring wells.	Applicable	A licensed monitoring well constructor will abandon monitoring well(s) and install monitoring well(s) as part of the proposed remedy. The licensed monitoring well constructor will install/abandon the monitoring well(s) in accordance with the construction standards and will complete a well log report and file it with the Montana Bureau of Mines and Geology pursuant to § 85-2-516, MCA. These activities will be conducted in accordance with the requirements of these ERCLs.
promulgated under the S	GEMENT REQUIREMENTS, generally found in the Solid Waste Management Act at §§ To olid Waste Management Act, and pursuant to the federal Solid Waste Disposal Act, as amentally to the to the transportation of solid wastes and the operation, closure, and post-closes.	nded by the Resource	Conservation and Recovery Act, 42 U.S.C. §§ 6901 et seq. (RCRA Subtitle D)
ARM 17.50.523(1)	ARM 17.50.523(1) specifies that solid waste must be transported in such a manner as to prevent its discharge, dumping, spilling, or leaking from the transport vehicle.	Applicable	Treated soils associated with implementation of this work plan will be disposed in an offsite licensed solid waste facility that is in compliance with applicable regulations. Non-hazardous waste generated during implementation of this work plan will be placed in an appropriate container and temporarily stored in a centralized storage area pending characterization and final disposition. All offsite disposal will occur in covered vehicles to prevent spilling, dumping, or leaking from the transport vehicle. Other solid waste (i.e., plastic wrapping, cardboard, etc.) will be contained in a plastic bag (if necessary), double-bagged (if necessary), and placed in a waste disposal dumpster for collection and appropriate disposal as solid waste.
ARM 17.50.1004 ARM 17.50.1005 ARM 17.50.1006 ARM 17.50.1007 ARM 17.50.1008 ARM 17.50.1009 ARM 17.50.1110 ARM 17.50.1116 ARM 17.50.1204(1), (2) ARM 17.50.1205(1)-(3) ARM 17.50.1303	ARM 17.50.1004 addresses Class II landfills in floodplains. ARM 17.50.1005 prohibits placement of a Class II landfill in a wetland unless special conditions are met. ARM 17.50.1006 prohibits placement of a Class II landfill within 200 feet of a fault which has had displacement in Holocene time unless special conditions are met. ARM 17.50.1007 prohibits placement of a Class II landfill in a seismic impact zone (as defined in ARM 17.50.1002(35)) unless special conditions are met. ARM 17.50.1008 prohibits placement of a Class II landfill in an unstable area, which are defined in ARM 17.50.1002(40) as including locations that are susceptible to events or forces that are capable of impairing the integrity of the landfill structural components responsible for preventing releases from the landfill. ARM 17.50.1009 provides a list of general location requirements for a solid waste management facility, including but not limited to: it must be located where a sufficient acreage of suitable land is available for solid waste management, including adequate separation of wastes from underlying groundwater and adjacent surface water; facility may not cause or contribute to the taking of any endangered or threatened species of plants, fish, or wildlife or result in the destruction or adverse modification of critical habitat for those species; and the facility must manage solid waste, gas, and leachate.	Applicable	Wastes generated during the remedial actions will not be disposed on-site. Waste generated during remedial actions will be transported off-site under appropriate manifest for disposal in an authorized permitted waste facility that meets these requirements.

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
	ARM 17.50.1109 requires that Class II landfills be designed, constructed, and maintained with a run-on and run-off control system to address 25-year storm events, and sets requirements for handling run-off from the active portion of a landfill in accordance with ARM 17.50.1110(1).		
	ARM 17.50.1110 prohibits a Class II landfill from causing a discharge of a pollutant into state waters, including wetlands, that violates the Montana Water Quality Act or cause the discharge from a nonpoint source of pollution to waters of the United States, including wetlands, that violates any requirement of an approved area-wide or statewide water quality management plan.		
	ARM 17.50.1116 outlines operating criterial at a solid waste management facility and requires that it be designed, constructed, and operated in a manner to prevent harm to human health and the environment.		
	ARM 17.50.1204(1), (2) sets design requirements for Class II landfills.		
	ARM 17.50.1205(1)-(3) requires additional design requirements for Class II landfills.		
	ARM 17.50.1303 identifies requirements for groundwater monitoring and corrective action at Class II landfill units, with the exception listed in ARM 17.501303(2).		
ARM 17.50.1312	ARM 17.50.1312 identifies requirements for monitoring well abandonment.	Applicable	Well abandonment activities at the Facility will be performed in accordance with ARM 17.50.1312, 36.21.670 to 678, and 36.21.810.
ARM 17.50.1403	ARM 17.50.1403 sets forth the closure requirements for Class II landfills. Among other requirements, the landfill unit must be designed to minimize infiltration and erosion. The final cover system must be designed and constructed to:	Applicable	Wastes generated during the remedial actions will not be disposed on-site. Waste generated during remedial actions will be transported off-site under appropriate manifest for disposal in an authorized permitted waste facility that meets these
ARM 17.50.1404	(a) have a permeability no greater than to the permeability of any bottom liner system or natural subsoils present, or a permeability no greater than 1W10<-5> cm/sec, whichever is less;		requirements.
	(b) minimize infiltration through the closed Class II or Class IV landfill unit by the use of an infiltration layer that contains at least 18 inches of earthen material; and		
	(c) minimize erosion of the final cover by the use of an erosion layer that contains at least six inches of earthen material that is capable of sustaining native plant growth.		
	ARM 17.50.1404 sets forth post closure care requirements for Class II landfills. Among other requirements, post closure care requires maintenance of the integrity and effectiveness of any final cover, including making repairs to the cover as necessary to correct the effects of settlement, subsidence, erosion, or other events, and preventing run-on and run-off from eroding or otherwise damaging the cover and comply with the groundwater monitoring requirements found at ARM Title 17, chapter 50, subchapter 13. ARM 17.50.1404(1).		

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
§ 75-10-212, MCA	Section 75-10-212, MCA, prohibits dumping or leaving any garbage, debris, or refuse upon or within 200 yards of any highway, road, street, or alley of the State or other public property, or on privately owned property where hunting, fishing, or other recreation is permitted. However, the restriction relating to privately owned property does not apply to the owner, his agents, or those disposing of debris or refuse with the owner's consent.	Applicable	Non-hazardous waste from this facility will be transported and disposed of at [insert the name of the disposal facility], a licensed solid waste management facility, in accordance with these ERCLs. Transport vehicles will be tarped and tied down to avoid any leaking of waste during transport.
Act, § 75-10-402(3), MC disposal of hazardous we Wastes may be designate 40 CFR Part 261, Subpa managed as hazardous w	MANAGEMENT REQUIREMENTS, generally found in the Resource Conservation and (A) and the Montana Hazardous Waste Act, §§ 75-10-401 et seq., MCA. Regulations under astes. These requirements are applicable to substances and actions at the facility which inverted as hazardous by either of two methods: listing or demonstration of a hazardous character of the concentration of the concentration of the constituents. Characteristic wastes are reactivity or toxicity, as described at 40 CFR Part 261, Subpart C (applicable, as incorporated).	these acts establish a olve the active manage ristic. Listed wastes a aste Act). Listed waste those that by virtue of	regulatory structure for the generation, transportation, treatment, storage, and ement of hazardous wastes. re the specific types of wastes determined by EPA to be hazardous as identified in es are designated hazardous by virtue of their origin or source, and must be f concentrations of hazardous constituents demonstrate the characteristic of
40 CFR Part 262 §§ 75-10-402(3) MCA	The RCRA regulations at 40 CFR Part 262 (as incorporated by the Montana Hazardous Waste Act) establish standards that apply to generators of hazardous waste. These standards include requirements for obtaining an EPA identification number and maintaining certain records and filing certain reports. These standards are applicable for any waste which will be transported offsite.	Applicable	Based on past experience, it is not anticipated that the treatment of SVE effluent vapors using granular activated carbon (GAC) will generate hazardous waste. However, prior to transportation, disposal or regeneration, laboratory analysis of VOCs by EPA Method 1311, toxic characteristic leaching procedure (TCLP) will be performed on each GAC drum for characterization.
40 CFR Part 263 § 75-10-402(3), MCA	The RCRA regulations at 40 CFR Part 263 (as incorporated by the Montana Hazardous Waste Act) establish standards that apply to transporters of hazardous waste. These standards include requirements for immediate action for hazardous waste discharges. These standards are applicable for any onsite transportation. These standards are independently applicable for any offsite transportation.		The EPA ID Number for the liable party and the Facility is MT000000000, which will be used to file the necessary reports if needed. If hazardous waste needs to be transported for disposal outside the Facility, a spill prevention response plan will be in place prior to transport. Hazardous waste to be disposed of offsite at a permitted RCRA disposal facility will be transported by a hazardous waste transporter and will be manifested. No hazardous waste will be disposed onsite.
40 CFR Part 264, Subpart B § 75-10-402(3), MCA	The regulations at 40 CFR 264, Subpart B (as incorporated by the Montana Hazardous Waste Act) establish general facility requirements. These standards include requirements for general waste analysis, security, and location standards.		
40 CFR Part 264, Subpart F § 75-10-402(3), MCA	The regulations at 40 CFR 264, Subpart F (as incorporated by the Montana Hazardous Waste Act) establish requirements for groundwater protection for RCRA-regulated solid waste management units (i.e., waste piles, surface impoundments, land treatment units, and landfills). The regulations at Subpart F establish monitoring requirements for RCRA-regulated solid waste management units (i.e., waste piles, surface impoundments, land treatment units, and landfills). Subpart F provides for three general types of groundwater monitoring: detection monitoring (40 CFR 264.98); compliance monitoring (40 CFR 264.99); and corrective action (40 CFR 264.100). Monitoring wells must be cased according to 264.97(c). Monitoring is required during the active life of a hazardous waste management unit. If hazardous waste remains, monitoring is required for a period necessary to protect human health and the environment.	Applicable	A long-term monitoring plan will be developed during the remedial design phase and will comply with the groundwater monitoring requirements.

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is <u>example</u> text. Please conduct a facilityspecific evaluation.)
40 CFR Part 264, Subpart G § 75-10-402(3), MCA	40 CFR Part 264, Subpart G (as incorporated by the Montana Hazardous Waste Act) establishes that hazardous waste management facilities must be closed in such a manner as to (a) minimize the need for further maintenance and (b) control, minimize or eliminate, to the extent necessary to protect public health and the environment, post-closure escape of hazardous wastes, hazardous constituents, leachate, contaminated runoff or hazardous waste decomposition products to the ground or surface waters or to the atmosphere and (c) complies with the closure requirements of this part, including, but not limited to, the requirements of §§ 264.178, 264.197, 264.228, 264.258, 264.280, 264.310, 264.351, 264.601 through 264.603, and 264.1102. See 40 CFR § 264.111. Requirements for facilities requiring post-closure care include the following: the facilities must undertake appropriate monitoring and maintenance actions, control public access, and control post-closure use of the property to ensure that the integrity of the final cover, liner, or containment system is not disturbed. In addition, all contaminated equipment, structures, and soil must be properly disposed of or decontaminated unless exempt and free liquids are removed or solidified, the wastes stabilized, and the waste management unit covered.	Applicable	No hazardous wastes will be generated during remedial actions.
40 CFR Part 264, Subparts I and J and § 75-10-402(3), MCA	40 CFR Part 264, Subparts I and J (as incorporated by the Montana Hazardous Waste Act) apply to owners and operators of facilities that store hazardous waste in containers, and store or treat hazardous waste in tanks, respectively. These regulations are applicable to any storage or treatment in these units at the facility. The related provisions of 40 CFR 261.7 regarding residues of hazardous waste in empty containers are also applicable.	Applicable	Hazardous waste generated during implementation of the ROD will be placed in containers that meet RCRA requirements and temporarily stored onsite in an access-controlled outdoor location in a manner that meets RCRA requirements. Containers will be compatible with the wastes and secondary containment will be provided with sufficient capacity to contain leaks or spills.
40 CFR Part 264, Subpart L and § 75-10-402(3), MCA	40 CFR Part 264, Subpart L (Applicable, as incorporated by the Montana Hazardous Waste Act) applies to owners and operators of facilities that store or treat hazardous waste in piles. The regulations include requirements for the use of run-on and run-off control systems and collection and holding systems to prevent the release of contaminants from waste piles. These regulations apply to any storage in waste piles.	Applicable	No waste piles will be used during remedial actions.
40 CFR Part 264, Subpart M, 40 CFR Part 264, Subpart S, and § 75-10-402(3), MCA	40 CFR Part 264, Subpart M (Applicable, as incorporated by the Montana Hazardous Waste Act) apply to owners and operators of facilities that treat hazardous waste in land treatment units. 40 CFR Part 264, Subpart S (Applicable, as incorporated by the Montana Hazardous Waste Act) provides special provisions for cleanup; 40 CFR 264.552 allows the designation of a corrective action management unit (CAMU) located within the contiguous property under the control of the owner or operator where the wastes to be managed in the CAMU originated and provides requirements for siting, managing, and closing the CAMU.	Applicable	The LTU will minimize runoff of hazardous constituents during the active life of the LTU. The LTU recovery system has been designed to hold runoff from a 25-year, 24-hour storm event from the LTU. The LTU will be located within the designated CAMU. The LTU will be located within the facility on contiguous property under the control of the liable party. Closure specifics for the LTU are included in this work plan and closure of the LTU will be further discussed with DEQ after the start of treatment of the last lift in the LTU.

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
40 CFR 264.554	40 CFR 264.554 sets forth the requirements for a staging pile. A staging pile must be located within the contiguous property under the control of the owner/operator where the wastes to be managed in the staging pile originated. 40 CFR 264.554(a). The staging pile must be designed so as to prevent or minimize releases of hazardous wastes and hazardous constituents into the environment, and minimize or adequately control cross-media transfer, as necessary to protect human health and the environment (for example, through the use of liners, covers, run-off/run-on controls, as appropriate). 40 CFR 264.554(d)(1)(ii). Except under certain circumstances, the staging pile must not operate for more than two years and cannot be used for treatment. 40 CFR 264.554(d)(1)(iii).	Applicable	Staging piles will not be used during remedial actions.
63 Fed. Reg. 65874 40 CFR 268.49(c)(1)(C) § 75-10-402(3), MCA	The Hazardous Waste Identification Rule (HWIR) Media Rule promulgated at 63 Fed. Reg. 65874 (November 30, 1998) (as incorporated by the Montana Hazardous Waste Act) allows listed waste treated to levels protective of human health and the environment to be disposed onsite without triggering land ban or minimum technology requirements for these disposal requirements. Treated soils containing hazardous waste will need to meet site-specific cleanup levels as well as the LDR treatment standards (applicable, as incorporated by the Montana Hazardous Waste Act) (40 CFR 268.49(c)(1)(C)), which requires that contaminated soil to be land disposed be treated to reduce concentrations of the hazardous constituents by 90 percent or meet hazardous constituent concentrations that are ten times the universal treatment standards (UTS) (found at 40 CFR 268.48), whichever is greater, to avoid triggering land ban.	Applicable	Hazardous waste will be generated during remedial activities to be performed under this plan. F032 listed wastes will be treated to site-specific cleanup levels and universal treatment standards during remedial action prior to offsite disposal as nonhazardous waste. PCP will be treated to levels protective of human health and the environment and will not trigger a land ban. Hazardous waste will not be disposed of onsite. A confirmation sampling plan, which is described in this work plan, will provide for data collection and comparison to cleanup levels and universal treatment standards. DEQ must approve all confirmation sampling results prior to disposal offsite as nonhazardous waste.
40 CFR Part 270 § 75-10-402(3), MCA	40 CFR Part 270 (as incorporated by the Montana Hazardous Waste Act) sets forth the hazardous waste permit program. The requirements set forth in 40 CFR Part 270, Subpart C (permit conditions), including the requirement to properly operate and maintain all facilities and systems of treatment and control are applicable requirements. For any management (i.e., treatment, storage, or disposal) or removal or retention, the RCRA regulations found at 40 CFR 264.116 (survey plats) and 264.119 (governing notice and deed restrictions), 264.228(a)(2)(i) (addressing de-watering of wastes prior to disposal), and 264.228(a)(2)(iii)(B)(C)(D) and 264.251 (c)(d)(f) (regarding run-on and run-off controls), are relevant requirements for any waste management units created or retained at the facility that contain non-exempt waste. A construction de-watering permit covers similar requirements.	Applicable	Hazardous waste will be generated during the activities to be performed under this work plan. The EPA ID Number for the liable party and the Facility is MT000000000, which will be used to file the necessary reports. Substantive requirements will be met for the following permit types: Storm Water Pollution Prevention and Hazardous Waste Treatment. The liable party will provide a written request for exemption from the administrative parts of the Hazardous Waste Treatment permit under separate cover and will not begin work until receiving a permit or permit exemption. Exemptions from the administrative parts of the Storm Water Pollution Prevention permit was previously approved by DEQ. The SWPPP phasing sheets have been updated in this work plan, specific to the work proposed during this phase or remedial action.
ARM 17.53.501-502	ARM 17.53.501-502 adopts the equivalent of RCRA regulations at 40 CFR Part 261, establishing standards for the identification and listing of hazardous wastes, including standards for recyclable materials and standards for empty containers, with certain State exceptions and additions.	Applicable	Excavated soils impacted with PCP and dioxin (F032 listed hazardous waste) will be treated using bioremediation in an onsite LTU. Soils will be treated to meet site-specific cleanup levels, will be protective of human health and the environment, and will not trigger a land ban.
ARM 17.53.601-604	ARM 17.53.601-604 adopts the equivalent to RCRA regulations at 40 CFR Part 262, establishing standards that apply to generators of hazardous waste, including standards pertaining to the accumulation of hazardous wastes, with certain State exceptions and additions.		The EPA ID Number for the liable party and the Facility is MT000000000, which will be used to file the necessary reports. A hazardous waste transporter is not required to

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
ARM 17.53.701-708	ARM 17.53.701-708 adopts the equivalent to RCRA regulations at 40 CFR Part 263, establishing standards that apply to transporters of hazardous waste, with certain State exceptions and additions.		transport hazardous waste onsite from a work area to the LTU or a centralized storage area, provided transportation remains within the CAMU area to be designated by DEQ. The onsite haul route to be used is shown in Figure 4 of this work plan. If hazardous waste needs to be transported outside the Facility, a hazardous waste transporter will be
ARM 17.53.801-803	ARM 17.53.801-803 adopts the equivalent to RCRA regulations at 40 CFR Part 264, establishing standards that apply to owners of hazardous waste treatment, storage and disposal facilities, with certain State exceptions and additions.		used and the hazardous waste will be manifested. Hazardous waste generated during implementation of the ROD, other than the PCP-containing soil to be treated in the LTU, will be contained in appropriate containers that meet the requirements of RCRA and stored in an access-controlled location in a manner that meets RCRA requirements.
ARM 17.53.1101-1102	ARM 17.53.1101-1102 adopts the equivalent to RCRA regulations at 40 CFR Part 268, establishing land disposal restrictions, with certain State exceptions and additions.		Hazardous wastes will not be disposed of at the Facility.
§ 75-10-422, MCA	Section 75-10-422, MCA, prohibits the unlawful disposal of hazardous wastes.		
ARM 17.53.1201-1202	ARM 17.53.1201-1202 adopts the equivalent to RCRA regulations at 40 CFR Part 270 and 124, which establish standards for permitted facilities, with certain State exceptions and additions.		
ARM 17.53.1401-1402	ARM 17.53.1401 adopts the equivalent of RCRA regulations at 40 CFR Part 279 that set forth the standards for the management of used oil, except for 40 CFR 279.82(b), pertaining to the use of used oil as a dust suppressant.	Applicable	Used oil will not be managed as part of the remedial actions.
TECHNOLOGY-BASE	D TREATMENT		
ARM 17.30.1203	ARM 17.30.1203: Provisions of 40 CFR Part 125 for criteria and standards for the imposition of technology-based treatment requirements are adopted and incorporated in DEQ permits. For toxic and nonconventional pollutants treatment must apply the best available technology economically achievable (BAT) (ARM 17.30.1203(3)(d)); for conventional pollutants, application of the best conventional pollutant control technology (BCT) is required (ARM 17.30.1203(3)(b)). Where effluent limitations are not specified for the particular industry or industrial category at issue, BCT/BAT technology-based treatment requirements are determined on a case-by-case basis using best professional judgment (BPJ). ARM 17.30.1203(5)(b).	Applicable	The VCP applicant will obtain the required permit which may impose a technology-based treatment requirement. The applicant will comply with all permit requirements. Therefore, the proposed remedy meets the requirements of these ERCLs.
UNDERGROUND INJ	ECTION CONTROL PROGRAM		
40 CFR Parts 144 and 146	The Underground Injection Control Program provided in 40 CFR Parts 144 and 146 sets forth the standards and criteria for the injection of substances into aquifers. Wells are classified as Class I through V, depending on the location and the type of substance injected. For all classes, no owner may construct, operate or maintain an injection well in a manner that results in the contamination of an underground source of drinking water at levels that violate maximum contaminant levels (MCLs) or otherwise adversely affect the health of persons. Each classification may also contain further specific standards, depending on the classification	Applicable	No injection of substances will occur as part of the proposed remedy. Therefore, the proposed remedy meets the requirements of these ERCLs.

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
UNDERGROUND STO	RAGE TANK REQUIREMENTS		
40 CFR Part 280, Subpart F	40 CFR Part 280, Subpart F sets forth requirements for Release Response and Corrective Action for underground storage tank (UST) Systems Containing Petroleum or Hazardous Substances. These include initial response, initial abatement measures, facility characterization, free product removal, and investigations for soil and groundwater cleanup.	Relevant	Information generated during the Remedial Investigation indicates that all known tanks have been removed from the Facility, but that underground piping associated with the tanks may remain. In addition, there is free product at the site. Therefore, certain storage tank regulations are applicable or relevant.
40 CFR 280.64(a), (c)	40 CFR 280.64 provides that where investigations in connection with leaking underground storage tanks reveal the presence of free product, owners and operators must remove free product to the maximum extent practicable as determined by the implementing agency. This regulation also requires that the free product removal be conducted in a manner that minimizes the spread of contamination into previously uncontaminated zones by using recovery and disposal techniques appropriate to the hydrogeologic conditions at the facility, and that properly treats, discharges or disposes of recovery byproducts in compliance with applicable local, state and federal regulations. Abatement of free product migration is a minimum objective for the design of the free product removal system provides that any flammable products must be handled in a safe and competent manner to prevent fires or explosions.	Relevant	
40 CFR 280.64	40 CFR 280.64 provides that abatement of free product migration is a minimum objective for the design of the free product removal system provides that any flammable products must be handled in a safe and competent manner to prevent fires or explosions.	Relevant	
40 CFR Part 280, Subpart D	40 CFR Part 280, Subpart D sets forth requirements for release detection.	Relevant	
40 CFR 280.43 ARM 17.56.407	40 CFR 280.43 and ARM 17.56.407 specifies groundwater monitoring requirements for underground storage tanks. 40 CFR 280.43(a)(2), (b)(3) and ARM 17.56.407(1)(a)(ii), (1)(b)(iii) require continuous monitoring devices or manual methods used to detect the presence of at least 1/8 of an inch of free product on top of the groundwater in the monitoring wells.	Relevant	
ARM Title 17, Chapter 56, Sub-Chapter 4	ARM Title 17, Chapter 56, Sub-Chapter 4 specifies release detection.	Relevant	
ARM 17.56.407	ARM 17.56.407 specifies groundwater monitoring requirements for underground storage tanks and requires continuous monitoring devices or manual methods used to detect the presence of at least 1/8 of an inch of free product on top of the groundwater in the monitoring wells.	Relevant	
ARM Title 17, Chapter 56, Sub-Chapter 6	ARM Title 17, Chapter 56, Sub-Chapter 6 specifies release response and corrective action for tanks containing petroleum or hazardous substances.	Relevant	
ARM 17.56.602 through 605	ARM 17.56.602 through 605 requires certain mitigation measures including removal of as much of the regulated substance from the system as is necessary to prevent further release into the environment and prevention of further migration of the released substance into surrounding soil and groundwater. In particular, ARM 17.56.602(1)(c) requires that after a release from an underground storage tank system is identified in any manner, owners and operators must	Relevant	

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
	investigate to determine the possible presence of free product, begin free product removal as soon as practicable, conduct free product removal in a manner that minimizes the spread of contamination into previously uncontaminated zones by using recovery and disposal techniques appropriate to the hydrogeologic conditions at the site, and that properly treats, discharges or disposes of recovery byproducts in compliance with applicable local, state and federal regulations. This regulation also provides that abatement of free product migration is a minimum objective for the design of the free product removal system and provides that any flammable products must be handled in a safe and competent manner to prevent fires or explosions.		
ARM 17.56.607(4)	ARM 17.56.607(4) outlines requirements that must be met before a release may be categorized as resolved. For example, ARM 17.56.607(4)(d) specifies that all free product must be removed to the maximum extent practicable before a release may be considered resolved.	Relevant	
ARM 17.56.702(2)	ARM 17.56.702(2) requires that all tanks and connecting piping which are taken out of service permanently must be removed from the ground. This applies if any remaining underground piping is encountered during remedial activities.	Relevant	
RECLAMATION AND	REVEGETATION REQUIREMENTS		
ARM 17.24.501	ARM 17.24.501 gives general backfilling and final grading requirements.	Relevant	See examples below.
ARM 17.24.631(1), (2), (3)(a) and (b)	ARM 17.24.631(1), (2), (3)(a) and (b): Disturbances to the prevailing hydrologic balance will be minimized. Changes in water quality and quantity, in the depth to groundwater and in the location of surface water drainage channels will be minimized, to the extent consistent with the selected remedial action. Other pollution minimization devices must be used if appropriate, including stabilizing disturbed areas through land shaping, diverting runoff, planting quickly germinating and growing stands of temporary vegetation, regulating channel velocity of water, lining drainage channels with rock or vegetation, mulching, and control of acid-forming, and toxic-forming waste materials.	Relevant	The soil/sludge/sediment and asphaltic removal activities are temporary actions. The SWPPP developed for the Facility identifies the BMPs that will be implemented to reduce the potential for impacts to streams or state surface waters from site contaminants or sediment. Final stabilization will be established once land disturbance activities have been completed. There are no streams or state surface water bodies present on the Facility under current site conditions. As part of the remedy implementation, site grading or filling will be completed as needed, to provide for positive stormwater drainage.
ARM 17.24.633(1), (2) ARM 17.24.635 through 17.24.637 ARM 17.24.638 ARM 17.24.640 ARM 17.24.641 ARM 17.24.643 through 17.24.646 ARM 17.24.701 and 702	ARM 17.24.633(1) states that all surface drainage from a disturbed area must be treated by the best technology currently available (BTCA). ARM 17.24.633(2) provides that treatment must continue until the area is stabilized. ARM 17.24.635 through 17.24.637 set forth requirements for temporary and permanent diversions for different flows, drainageways, and streams. ARM 17.24.638 specifies sediment control measures to be implemented during remedial activities. ARM 17.24.640 provides that discharge from diversions must be controlled to reduce erosion and minimize disturbance of the hydrologic balance. ARM 17.24.641 indicates that practices to prevent drainage from acid or toxic forming spoil material into groundwater and surface water must be employed, and outlines how to do so.	Relevant	A Storm Water Pollution Prevention Plan (SWPPP) has been prepared because the disturbed acreage is greater than 1 acre and is included as Appendix F to this work plan. MDEQ has exempted the liable from the requirement for the procedural portions of a MPDES General Permit. The SWPPP addresses the substantive requirements contained in the storm water management regulations. BMPs that will be placed or followed include decontamination pads, stone covered driveway, and vehicle tracking pad placement along the traffic route. Spill kits will be placed in the exclusion zone and support zone. Water or spray-on chemical agents will be applied to control dust during excavation and loading. Live loading of trucks will minimize the use of stockpiles. Stockpiles will be covered by polyethylene sheeting and weighted tarps. Decontamination pads will be constructed and used to prevent the tracking of impacted soil. Impacted soil will be loaded into lined trucks and the loads will be covered by

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
	ARM 17.24.643 through 17.24.646 provide provisions for groundwater protection, groundwater recharge protection, and groundwater and surface water monitoring. ARM 17.24.701 and 702 provide requirements for removal and redistributing and stockpiling of soil for reclamation. Also outline practices to prevent compaction, slippage, erosion, and deterioration of biological properties of soil. ARM 17.24.704(4)(b), (5).		tarps during transit. Loads will be transported onsite using routes shown in Figure 4 of this work plan.
ARM 17.24.703 ARM 17.24.711 ARM 17.24.713 ARM 17.24.714 ARM 17.24.716	ARM 17.24.703 require that when using materials other than, or along with, soil for final surfacing in reclamation, the operator must demonstrate that the material (1) is at least as capable as the soil of supporting the approved vegetation and subsequent land use, and (2) the medium must be the best available in the area to support vegetation. Such substitutes must be used in a manner consistent with the requirements for redistribution of soil in ARM 17.24.701 and 702.	Relevant	Revegetation will be accomplished in cooperation with the County Weed District. A revegetation/weed management plan, approved by the County Weed District, and has been included as Appendix H to the Remediation Work Plan.
ARM 17.24.717 ARM 17.24.718 ARM 17.24.721 ARM 17.24.723	ARM 17.24.711 requires that a diverse, effective, and permanent vegetative cover of the same seasonal variety and utility as the vegetation native to the area of land to be affected must be established, in accordance with § 82-4-233, MCA. ARM 17.24.713 provides that seeding and planting of disturbed areas must be conducted during the first appropriate period for favorable planting after final seedbed preparation but may not be more than ninety days after soil has been replaced.		TRA
ARM 17.24.724 ARM 17.24.726 ARM 17.24.731	ARM 17.24.714 requires use of a mulch or cover crop or both until an adequate permanent cover can be established. Use of mulching and temporary cover may be suspended under certain		
	ARM 17.24.716 establishes the required method of revegetation. ARM 17.24.717 relates to the planting of trees and other woody species if necessary, as provided in § 82-4-233, MCA, to establish a diverse, effective, and permanent vegetative cover.		
	ARM 17.24.718 requires soil amendments if necessary to establish a permanent vegetative cover and includes management techniques and land use requirements.		
	ARM 17.24.721 specifies that rills and gullies must be stabilized and the area reseeded and replanted if the rills and gullies are disrupting the reestablishment of the vegetative cover.		
	ARM 17.24.723 requires periodic monitoring of vegetation, soils, water, and wildlife, and outlines certain uses of monitoring data.		
	ARM 17.24.724 specifies how revegetation success is measured.		
	ARM 17.24.726 sets the required methods for measuring vegetative success.		
	ARM 17.24.731 provides if toxicity to plants or animals is suspected, comparative chemical analyses of the revegetated area(s) may be required.		

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
§ 75-10-1404, MCA	Section 75-10-1404, MCA, requires minimum reclamation standards with respect to mine and smelter waste. Section 75-110-1404(3), specifically, provides that, except for provided in § 75-10-1411, MCA, lands where waste has been removed must be revegetated using plant species native to the area and must achieve a vegetative cover equal to 85 percent of the vegetative cover of adjacent lands that were not previously disturbed within three years of the initial seeding.	Relevant	
NOXIOUS WEED REQ 7-22-2101(9), MCA	QUIREMENTS, generally found in the County Weed Control Act at §§ 7-22-2101, et seq., I	MCA, which establishe	es and authorizes weed control at the local level. "Noxious weeds" are defined at §
Section 7-22-2116(1), MCA Section 7-22-2152, MCA ARM 4.5.201 ARM 4.5.206 through ARM 4.5.210	Section 7-22-2116(1), MCA, prohibits allowing noxious weeds to propagate. Section 7-22-2116(1), MCA, provides for preparation and implementation of a weed control plan. Designated noxious weeds are listed in ARM 4.5.201 and 4.5.206 through 4.5.209 and must be managed consistent with weed management criteria developed under § 7-22-2109(2)(b), MCA, and in compliance with revegetation requirements pursuant to § 7-22-2152, MCA. In addition, ARM 4.5.210 identifies regulated plants that may not be used for revegetation.	Relevant	As specified in Section ##, the county weed board will be notified of the impending cleanup activity and provided with a copy of the remedial design plan if requested. A revegetation plan meeting the requirements specified in Section ## and any other specific requirements of the board will be submitted to the board at least 15 days prior to initiation of the cleanup. A copy of the revegetation and approval letter will be provided to DEQ when available. Therefore, the proposed remedy meets the requirements of these ERCLs.
	CONTAMINANT-SPECIFIC ERCLS		
maximum contaminant le EPA's guidance on Remo [ARARs; the federal equi zero are relevant under t	NDARDS, generally found in the Safe Drinking Water Act, 42 U.S.C. § 300f et seq., and the evel goals (MCLGs) for contaminants in drinking water distributed in public water systems edial Action for Contaminated Groundwater at Superfund Sites states that MCLs developed ivalent of ERCLs] for current or potential drinking water sources. EPA has also established the same conditions (55 Fed.Reg. 8750-8752, March 8, 1990). See also, State of Ohio v. EF which is a potential drinking water source.	I under the Safe Drink ed MCLGs for contami	ing Water Act generally are Applicable or Relevant and Appropriate Requirements inants in drinking water distributed in public water systems. MCLGs that are above
40 Code of Federal Regulations (CFR) Part 141		Applicable	The requirements were evaluated in this ERCLs analysis in conjunction with the groundwater classification standards promulgated by the State of Montana. The MCLs are identified because the groundwater at the facility is a source of drinking water. MCLs for the primary contaminants of concern in groundwater are listed below. However, compliance with all MCLs is required and remedial actions must meet the MCLs for all contaminants at the facility, including any breakdown products generated
40 CFR Part 143.3	The Secondary Maximum Contaminant Levels (SMCLs) specified in 40 CFR Part 143.3 are relevant requirements which are ultimately to be attained by the remedy for the facility. This regulation contains standards for iron, manganese, sulfate, color, odor, and corrosivity that are relevant to the remedial actions.	Relevant	during remedial actions. Because groundwater in the vicinity of the site is used as a drinking water source, the Secondary Maximum Contaminant Levels (SMCLs) specified in 40 CFR Part 143.3 are relevant requirements which are ultimately to be attained by the remedy for the site. 40 CFR Part 143.3 contains standards for iron, manganese, color, odor, and corrosivity which are relevant to the remedial action.

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
§ 75-5-605, MCA, § 75-6-112, MCA, and § 75-5-303, MCA	The Montana Water Quality Act, § 75-5-101, et seq., MCA provides that it is unlawful to cause pollution of any state waters. Section 75-5-605(1)(a), MCA. Section 75-5-605(1)(a) and (c), MCA, state that it is unlawful to place or cause to be placed any wastes where they will cause pollution of any state waters or to cause degradation of state waters without authorization pursuant to § 75-5-303, MCA. Section 75-5-303(1), MCA states that existing uses of state waters and the level of water quality necessary to protect the uses must be maintained and protected.	Applicable	To protect state waters from degradation/pollution, wastes generated during remedial activities will be stored and treated or disposed in such a manner as to not impact groundwater quality. Soil excavated from contaminant of concern (COC)-impacted soil areas will be placed on liners to prevent contamination of surrounding surficial soil or contamination of the groundwater. If groundwater is collected during excavation or sampling activities, it will be disposed offsite. Contaminated soils and other contaminated media will be treated, recycled or disposed in accordance with solid and hazardous waste ERCLs in a manner that does not degrade water quality. This work plan addresses releases that may occur during COC-impacted soils excavation activities.
ARM 17.30.1006	ARM 17.30.1006, classifies groundwater into Classes I through IV based upon its specific conductance and establishes the groundwater quality standards applicable with respect to each groundwater classification. Class I is the highest quality class; Class IV the lowest. The lowest measured specific conductance generally dictates its classification. ARM 17.30.1006 sets the standards for the different classes of groundwater based on beneficial uses. Concentrations of dissolved substances in groundwater may not exceed the human health standards listed in the most current version of Montana DEQ Circular DEQ-7 (June 2019 or later), including narrative standards, which are promulgated pursuant to the state Water Quality Act, §§ 75-5-101, et seq., MCA. Concentrations of other dissolved or suspended substances (i.e., parameters for which human health standards are not listed in DEQ-7) must not exceed levels that render the waters harmful, detrimental or injurious to beneficial uses listed for that class of water. ARM 17.30.1006(1)(b)(ii), (2)(b)(ii), (3)(b)(ii). Compliance with DEQ-7 standards is required for all contaminants at the facility, including any breakdown products generated during remedial actions.	Applicable	To protect state waters from degradation/pollution, wastes generated during remedial activities will be stored and treated or disposed in such a manner as to not impact groundwater quality. Soil excavated from COC-impacted soil areas will be placed on liners to prevent contamination of surrounding surficial soil or recontamination of the groundwater. If groundwater is collected during excavation or sampling activities, it will either be disposed offsite or discharged to the sanitary sewer system (if allowable) through a discharge permit. Contaminated soils and other contaminated media will be treated, recycled or disposed in accordance with solid and hazardous waste ERCLs in a manner that does not degrade water quality. This work plan addresses releases that may occur during COC-impacted soils excavation activities.
ARM 17.30.1011	ARM 17.30.1011 provides that any ground water whose existing quality is higher than the standard for its classification must be maintained at that high quality unless degradation may be allowed under the principles established in § 75-5-303, MCA, and the non-degradation rules at ARM 17.30.701 <i>et seq</i> .	Applicable	To protect state waters from degradation/pollution, wastes generated during remedial activities will be stored and treated or disposed in such a manner as to not impact groundwater quality. Soil excavated from COC-impacted soil areas will be placed on liners to prevent contamination of surrounding surficial soil or recontamination of the groundwater. If groundwater is collected during excavation or sampling activities, it will either be disposed offsite or discharged to the sanitary sewer system (if allowable) through a discharge permit. Contaminated soils and other contaminated media will be treated, recycled or disposed in accordance with solid and hazardous waste ERCLs in a manner that does not degrade water quality. This work plan addresses releases that may occur during COC-impacted soils excavation activities.

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
ground waters. Also fou to adopt water quality st	UALITY STANDARDS, generally found in the Montana Water Quality Act at §§ 75-5-101, and in the federal Clean Water Act, 33 U.S.C. §§ 1251, et seq., which establishes requirement and ards designed to protect beneficial uses of each water body and to designate uses for each to state waters and prohibit the degradation of state waters.	nts for restoring and n	naintaining the quality of surface waters. Under these Acts the state has authority
ARM 17.30.606-617	ARM 17.30.606-617 provides that the waters of the [<i>insert river name</i>] River drainage from [<i>insert stretch description</i>] are classified "B-3" for water use.	Applicable	Best management practices (BMPs) will be implemented to prevent impact of surface waters from site contaminants or sediment. No samples will be collected within 200 feet of surface water and excavated areas will be backfilled with soils remaining after sample collection and regraded/reshaped to the same topography as the surrounding
ARM 17.30.625	ARM 17.30.625 provides that concentrations of carcinogenic, bioconcentrating, toxic or harmful parameters which would remain in the water after conventional water treatment may not exceed the applicable standards set forth in DEQ-7.	Applicable	area. Therefore, the remedial activities will not impact surface water.
ARM 17.30.637	ARM 17.30.637 prohibits certain discharges to surface waters including but not limited to substances that will: (a) settle to form objectionable sludge deposits or emulsions beneath the surface of the water or upon adjoining shorelines; (b) create floating debris, scum, a visible oil film (or be present in concentrations at or in excess of 10 milligrams per liter (mg/L)) or globules of grease or other floating materials; (c) produce odors, colors or other conditions which create a nuisance or render undesirable tastes to fish flesh or make fish inedible; (d) create concentrations or combinations of materials which are toxic or harmful to human, animal, plant or aquatic life; (e) create conditions which produce undesirable aquatic life. ARM 17.30.637 also states that no waste may be discharged and no activities conducted which, either alone or in combination with other waste activities, will cause violation of surface water quality standards.	Applicable	RCLS
ARM 17.30.641	ARM 17.30.641 provides standards for sampling and analysis of water to determine quality.	Applicable	A groundwater monitoring plan will be developed as part of long-term groundwater monitoring. Compliance water quality monitoring will be conducted using methods approved by DEQ.
ARM 17.30.646	ARM 17.30.646 requires that bioassay tolerance concentrations be determined in a specified manner.	Applicable	Bioassays will not be required as part of the tasks detailed in the ROD.
ARM 17.30.705	ARM 17.30.705 provides that for any surface water, existing and anticipated uses and the water quality necessary to protect these uses must be maintained and protected unless degradation is allowed under the non-degradation rules at ARM 17.30.708.	Applicable	A Storm Water Pollution Prevention Plan (SWPPP) has been prepared for characterization and remedial activities to be conducted. There are no current data indicating that the Facility is impacting the River or other surface water. However, if information regarding the presence of or impact on surface water changes, DEQ will be notified and compliance with relevant and applicable standards will be investigated.
AIR STANDARDS, generally found in the Clean Air Act of Montana at §§ 75-2-101, et seq., MCA. The Clean Air Act (42 USC §§ 7401 et seq.), provides limitations on air emissions resulting from cleanup activities or emissions resulting from wind erosion of exposed hazardous substances. State emission standards are promulgated pursuant to section 109 of the Clean Air Act and are applicable to releases into the air from any cleanup activities. They are also enforceable under the Clean Air Act of Montana, §§ 75-2-101, et seq., MCA.			
40 CFR Part 61	The National Emission Standards for Hazardous Air Pollutants (NESHAPS), 40 CFR Part 61 establishes emission standards for specific air pollutants.		

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
§§ 75-2-101, et seq., MCA	Sections 75-2-203, MCA, provides that state emission standards are enforceable under the Clean Air Act of Montana.	Applicable	The liable party has determined that an air permit is not required. BMPs implemented will include dust control measures such as spraying of water or other dust suppressant onto the surface of soils that are being disturbed to prevent particles or contaminants from becoming airborne and procedures for air monitoring to verify compliance with ambient air standards. Monitoring procedures are identified in the design report. Remedial actions will be halted if air monitoring indicates dust levels are approaching air quality limitations and will not resume until adequate dust control measures are in place.
ARM 17.74 Subchapter 3	ARM 17.74 Subchapter 3 addresses requirements related to persons or entities engaged in asbestos related occupations, in charge of asbestos projects, or engaged in facility demolition or renovation activities. Training requirements for persons engaged in asbestos-type occupations are specified.	Applicable	The liable party has determined that asbestos containing materials are not present.
Sections 75-2-501 et seq., MCA	The Asbestos Control Act (§§ 75-2-501 <i>et seq.</i> , MCA) establishes requirements for asbestos projects including permitting and inspection requirements. Section 75-2-502, MCA, defines an asbestos project to exclude a project that involves less than ten square feet in surface area or three linear feet of pipe.	Applicable	The liable party has determined that asbestos containing materials are not present.
ARM 17.8.220 ARM 17.8.221 40 CFR 50.12 and ARM 17.8.222 ARM 17.8.223	ARM 17.8.220 provides that no person shall cause or contribute to concentrations of particulate matter in the ambient air such that the mass of settled particulate matter exceeds a 30-day average of 10 grams per square meter (gm/m²). A measurement method is provided in ARM 17.8.220(2). ARM 17.8.221 provides concentrations of particulate matter in ambient air shall not exceed annual average scattering coefficient of 3 x 10 ⁻⁵ per meter for certain areas. A measurement method is provided in ARM 17.8.221(3). 40 CFR 50.12 and ARM 17.8.222 provides ambient air quality standards for lead. Lead concentrations in air shall not exceed the following 90-day average: 1.5 micrograms per cubic meter (μg/m³) of air. ARM 17.8.223 provides PM-10 concentrations in ambient air shall not exceed a 24-hour average of 150 μg/m³ of air and an annual average of 50 μg/m³ of air. ARM 17.8.223(2) and (3) set how an exceedance is determined and measured.	Applicable	The liable party has determined that an air permit is not required. BMPs implemented will include dust control measures such as spraying of water or other dust suppressant onto the surface of soils that are being disturbed to prevent particles or contaminants from becoming airborne and procedures for air monitoring to verify compliance with ambient air standards. Monitoring procedures are identified in the design report. Remedial actions will be halted if air monitoring indicates dust levels are approaching air quality limitations and will not resume until adequate dust control measures are in place.
ARM 17.8.210 through 17.8.214	Ambient air standards under section 109 of the Clean Air Act are also promulgated for carbon monoxide, hydrogen sulfide, nitrogen dioxide, sulfur dioxide, and ozone. If emissions of these compounds were to occur at the facility in connection with any cleanup action, these standards would also be applicable. See ARM 17.8.210, 17.8.211, 17.8.212, 17.8.213, and 17.8.214.	Applicable	Activities to be conducted under this work plan are not expected to result in exceedance of ambient air quality standards for carbon monoxide, hydrogen sulfide, nitrogen dioxide, sulfur dioxide, lead, or ozone.

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is <u>example</u> text. Please conduct a facilityspecific evaluation.)
NATURAL STREAMB	ED AND LAND PRESERVATION ACT		
§ 75-7-111, MCA	Section 75-7-111, MCA, provides that a person planning to engage in any activity that will physically alter or modify the bed or banks of a stream must give written notice to the Board of Supervisors of a Conservation District, the Directors of a Grass Conservation District, or the Board of County Commissioners if the proposed project is not within a district and must submit a "310 Permit" application to one of those entities.	Applicable	As described in the ROD, there are no designated wetlands, floodplains, or other surface water bodies present at the Facility. If information regarding the presence of, or impact on, wetlands, floodplains, or surface water changes, DEQ may identify applicable or relevant ERCLs.
ARM 36.2.410§ 75-7-102, MCA	ARM 36.2.410 establishes minimum standards which would be applicable if a remedial action alters or affects a streambed, including any channel change, new diversion, riprap or other streambank protection project, jetty, new dam or reservoir or other commercial, industrial or residential development. No such project may be approved unless reasonable efforts will be made consistent with the purpose of the project to minimize the amount of stream channel alteration, insure that the project will be as permanent a solution as possible and will create a reasonably permanent and stable situation, insure that the project will pass anticipated water flows without creating harmful erosion upstream or downstream, minimize turbidity, effects on fish and aquatic habitat, and adverse effects on the natural beauty of the area and insure that streambed gravels will not be used in the project unless there is no reasonable alternative. Soils erosion and sedimentation must be kept to a minimum. Such projects must also protect the use of water for any useful or beneficial purpose. See § 75-7-102, MCA.	Applicable	
METHANE			
ARM 17.50.1106	ARM 17.50.1106(1) specifies the owner or operator of a Class II landfill unit shall ensure that the concentration of methane gas generated by a solid waste facility cannot exceed 25 percent of the lower explosive limit (LEL) for methane in facility structures.	Relevant	As described in this VCP, methane concentrations at the facility do not exceed 25 percent of the LEL and monitoring will be conducted during implementation of the remedy to ensure that level is not exceeded during cleanup. Therefore, the VCP meets the requirements of these ERCLs.
	LOCATION-SPECIFIC ERCLS		
257.3-2) require that any Also found in the Montar	IES, generally found in the Endangered Species Act at 16 U.S.C. §§ 1531, et seq., and its a syfederal activity or federally authorized activity may not jeopardize the continued existence and Nongame and Endangered Species Act, §§ 87-5-101, et seq., MCA, which provides that a gered species, prohibited acts, and penalties.	e of any threatened or	endangered species or destroy or adversely modify a critical habitat.
50 CFR Part 402 40 CFR 6.302 40 CFR 257.3-2	Compliance with this requirement involves consultation with the U.S. Fish and Wildlife Service (USFWS) and a determination of whether there are listed or proposed species or critical habitats present at the facility, and, if so, whether any proposed activities will impact such wildlife or habitat.	Relevant	While activities proposed in this work plan will result in significant disturbance, no endangered or threatened species or critical habitats have been identified at this sit Therefore, the work will not impact threatened or endangered species. However, if threatened or endangered species or critical habitats are encountered during remea
§ 87-5-201, MCA ARM 12.5.201	Section 87-5-201, MCA, prohibits certain actions towards a number of wild birds, nests and eggs. ARM 12.5.201 prohibits certain activities with respect to specified endangered species.	Applicable	actions, compliance with these ERCLs is required and consultation with the USFWS will occur.

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
MIGRATORY BIRD TH	REATY ACT		
16 USC §§ 703 et seq.	This requirement (16 USC §§ 703 <i>et seq.</i>) establishes a federal responsibility for the protection of the international migratory bird resource and requires continued consultation with the appropriate program within the USFWS during remedial design and remedial construction to ensure that the cleanup of the facility does not unnecessarily impact migratory birds.	Relevant	Migratory birds are present near the facility. However, the facility does not provide the majority of habitat for these species relative to the surrounding area. There are no features of the facility that are particularly attractive to these species. Therefore, remedial actions at the facility are not expected to impact migratory birds. Thus, the proposed remedy meets the requirements of this ERCL.
BALD EAGLE PROTE	CTION ACT		
16 USC §§ 668 et seq.	This requirement (16 USC §§ 668 <i>et seq.</i>) establishes a federal responsibility for protection of bald and golden eagles, and requires continued consultation with the appropriate program within the USFWS during remedial design and remedial construction to ensure that any cleanup of the facility does not unnecessarily adversely affect the bald and golden eagle.	Relevant	Bald and golden eagles have not been observed at the facility. In addition, the facility does not provide the majority of habitat for these species relative to the surrounding area. There are no features of the facility that are particularly attractive to these species. Therefore, remedial actions at the facility are not expected to impact these species. Thus, the proposed remedy meets the requirements of this ERCL.
HISTORIC SITES, BUI	ILDINGS, OBJECTS AND ANTIQUITIES ACT		
16 USC §§ 461 et seq.	These requirements, found at 16 USC 461 <i>et seq.</i> , provide that, in conducting an environmental review of a proposed action, the responsible official shall consider the existence and location of natural landmarks using information provided by the National Park Service pursuant to 36 CFR § 62.6(d) to avoid undesirable impacts upon such landmarks.	Relevant	Current data indicate that no landmarks are present on the facility. Thus, the proposed remedy meets the requirements of this ERCL.
MONTANA GREATER	SAGE-GROUSE STEWARDSHIP ACT		
§§ 2-15-243 and 76-22-101, et seq., MCA, and related Executive Orders 10-2014, 12-2015, and 21-2015	The Montana Greater Sage-Grouse Stewardship Act, §§ 2-15-243 and 76-22-101, et seq., MCA, and related Executive Orders 10-2014, 12-2015, and 21-2015 establishes a map of sage-grouse Core Areas, Connectivity Areas, and General Habitat (https://sagegrouse.mt.gov/ProgramMap) (Executive Order 21-2015), a Montana sage-grouse oversight team, and a Sage Grouse Habitat Conservation program. If a remedial action will occur within one of the designated areas on the map, consultation is required with the Sage Grouse Habitat Conservation program, which is housed within the Department of Natural Resources and Conservation (https://sagegrouse.mt.gov/). Certain activities are prohibited or limited within the designated areas on the map. See the Core Area Stipulations, General Habitat Stipulations, and Connectivity Habitat Stipulations in Attachment D of Executive Order 10- 2014, as amended by Executive Order 12-2015, including requirements/restrictions on surface disturbance; surface occupancy; seasonal use limitations; transportation limitations; pipelines; overhead power lines and communications towers; noise; vegetation removal; sagebrush eradication; wildfire and prescribed burns; monitoring; reclamation; conifer expansion; and rangelands. The industry-specific stipulations (for oil and gas, mining, coal mining, and wind energy industries) within Core Areas in Attachment D may be relevant, depending upon the type of facility and activities required for remedial action. A waiver of the various requirements is allowed through creation of a Special Management Area where a planned land use or activities associated with "valid rights" cannot be implemented. "Valid rights" are defined as "legal 'rights' or interest that are	Applicable, substantive provisions only	Based on a review of designated areas on the sage grouse map, the facility is not with a sage grouse core area, connectivity area, or general habitat. Thus, the proposed remedy meets the requirements of this ERCL.

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
	associated with land or mineral estate and that cannot be divested from the estate until that interest expires, is relinquished, or acquired." (Executive Order 10- 2014, Attachment H). The procedures for Special Management Areas are outlined in Attachment E to Executive Order 10-2014, as amended by Executive Order 12-2015. Certain activities outlined in Attachment F of Executive Order 10-2014, as amended by Executive Order 12-2015, are exempt from these requirements.		
RESOURCE CONSERV	VATION AND RECOVERY ACT		
40 CFR 264.18	40 CFR 264.18 provides location requirements for owners and operators of hazardous waste management units. Portions of new management units must not be located within 200 feet of a fault which has had displacement in Holocene time and management units in or near a 100- year floodplain must be designed, constructed, operated, and maintained to avoid washout. Noncontainerized or bulk liquid hazardous waste must not be placed in any salt dome formation, salt bed formation, underground mine or cave with an exception for a New Mexico project.	Relevant	All hazardous waste will be removed from the facility and no management units will be created. Thus, the proposed remedy meets the requirements of this ERCL.
FISH AND WILDLIFE	COORDINATION ACT		
16 USC § 661 et seq. and 40 CFR 6.302	These standards are found at 16 USC § 661 et seq. and 40 CFR 6.302 and require that federally funded or authorized projects ensure that any modification of any stream or other water body affected by a funded or authorized action provide for adequate protection of fish and wildlife resources.	Relevant	As stated in section ##, the proposed remedy includes rerouting of the stream channel. Any fish caught in pools after the stream diversion will be collected and relocated into the active stream channel. No other wildlife species reside primarily at the facility and the proposed remedy is not expected to impact any other species. Therefore, the proposed remedy meets the requirements of these ERCLs.
FLOODPLAIN MANAC	GEMENT ORDER		
Executive Order 11988 40 CFR Part 6	Executive Order 11988 requires federal agencies to avoid to the extent possible the long and short-term adverse impacts associated with the occupancy and modification of floodplains and to avoid direct and indirect support of floodplain development wherever there is a practicable alternative. Implementing regulations for this executive order are found at 40 CFR Part 6.	Relevant	No federal action is anticipated at the facility. Also, as stated in section 5.1 of the VCP, the proposed remedy includes reconstruction of a 100-year floodplain along the new stream channel which will comply with Montana's floodplain requirements. Therefore, the proposed remedy will not result in adverse impacts to the floodplain and will meet the requirements of this ERCL.
PROTECTION OF WE	TLANDS ORDER		
40 CFR Part 6, Appendix A Executive Order No. 11,990 33 U.S.C. § 1344(b)(1)	This requirement (40 CFR Part 6, Appendix A, Executive Order No. 11,990) mandates that federal agencies and potentially responsible parties avoid, to the extent possible, the adverse impacts associated with the destruction or loss of wetlands and to avoid support of new construction in wetlands if a practicable alternative exists. 33 U.S.C. § 1344(b)(1), which is Section 404(b)(1) of the Clean Water Act, also prohibits the discharge of dredged or fill material into waters of the United States. Together, these requirements create a "no net loss" of wetlands standard.	Relevant	There is one small designated wetland present at the facility. The VCP provides a detailed pre-construction drawing that reflects the location of this wetland. It is not anticipated that the excavation conducted under the VCP will impact the wetland. However, if the wetland is disturbed by the proposed remedy, this habitat will be reestablished by reseeding with appropriate vegetation and ensuring the reconstructed stream channel will continue to support a wetland. Therefore, the proposed remedy will meet the requirements of this ERCL.

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
SOLID WASTE MANA facility.	GEMENT REQUIREMENTS, generally found in the Solid Waste Management Act, at §§	75-10-201 et seq., MC	CA, specify requirements that apply to the location of any solid waste management
ARM 17.50.1004 ARM 17.50.1009(1)(h)	ARM 17.50.1004 specifies a solid waste facility located within the 100-year floodplain may not restrict the flow of the 100-year flood, reduce the temporary water storage capacity of the floodplain, or result in washout of solid waste that poses a hazard to human health or the environment. <i>See also</i> ARM 17.50.1009(1)(h).	Applicable	The remedy does not include the requirement to construct such a facility. All solid waste at the facility will be removed, transported, and properly disposed of at [insert the name of the facility], an appropriate permitted disposal facility. Therefore, the proposed remedy meets the requirements of these ERCLs.
ARM 17.50.1005	ARM 17.50.1005 specifies a solid waste facility may not be located in a wetland, unless there is no demonstrable practicable alternative.	Applicable	
ARM 17.50.1006	ARM 17.50.1006 specifies a solid waste facility cannot be located within 200 feet (60 meters) of a fault that has had displacement in Holocene time without demonstration that an alternative setback will prevent damage to the structural integrity of the solid waste facility and will be protective of human health and the environment.	Applicable	
ARM 17.50.1007	ARM 17.50.1007 specifies a solid waste facility may not be located in a seismic impact zone without demonstration, by a Montana licensed engineer, that the solid waste structure is designed to resist the maximum horizontal acceleration in lithified earth material for the site.	Applicable	R() C
ARM 17.50.1008	ARM 17.50.1008 specifies a solid waste facility may not be located in an unstable area (determined by consideration of local soil conditions, local geographic or geomorphologic features, and local artificial features or events, both surface and subsurface) without demonstration, by a Montana licensed engineer, that the solid waste facility is designed to ensure that the integrity of the structural components will not be disrupted.	Applicable	
ARM 17.50.1009	ARM 17.50.1009 requires that Class II landfills be designed, constructed, and maintained with a run-on and run-off control system to address 25-year storm events.	Applicable	
ARM 17.50.1110	ARM 17.50.1110 prohibits a Class II landfill from causing a discharge of a pollutant into state waters, including wetlands.	Applicable	
ARM 17.50.1116	ARM 17.50.1116 requires that a solid waste management facility be designed, constructed, and operated in a manner to prevent harm to human health and the environment.	Applicable	
ARM 17.50.1204(1)	ARM 17.50.1204(1) outlines two ways that a Class II landfill may be constructed, once of which requires utilizing a composite liner and leachate collection and removal system that is designed and constructed to maintain less than a 30-centimeter depth of leachate over the liner.	Applicable	
ARM 17.50.1205(3)	ARM 17.50.1205(3) requires that the leachate system provide for accurate monitoring of the leachate level and provide a minimum slope at the base of the overlying leachate collection layer equal to at least two percent.	Applicable	

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
ARM 17.50.1303	ARM 17.50.1303 identifies requirements for groundwater monitoring and corrective action at Class II landfill units, with the exception listed in ARM 17.501303(2)	Applicable	
ARM 17.50.1312	ARM 17.50.1312 identifies requirements for monitoring well abandonment.	Applicable	
ARM 17.50.1403	ARM 17.50.1403 sets forth the closure requirements for Class II landfills. Among other requirements, the landfill unit must be designed to minimize infiltration and erosion. The final cover system must be designed and constructed to: (a) have a permeability no greater than to the permeability of any bottom liner system or	Applicable	
	natural subsoils present, or a permeability no greater than 1W10<-5> cm/sec, whichever is less; (b) minimize infiltration through the closed Class II or Class IV landfill unit by the use of an infiltration layer that contains at least 18 inches of earthen material; and (c) minimize erosion of the final cover by the use of an erosion layer that contains at least six inches of earthen material that is capable of sustaining native plant growth		
ARM 17.50.1404	ARM 17.50.1404 sets forth post closure care requirements for Class II landfills. Post closure care requires maintenance of the integrity and effectiveness of any final cover, including making repairs to the cover as necessary to correct the effects of settlement, subsidence, erosion, or other events, and preventing run-on and run-off from eroding or otherwise damaging the cover and comply with the groundwater monitoring requirements found at ARM Title 17, chapter 50, subchapter 13. ARM 17.50.1404(1).	Applicable	
§ 75-10-212, MCA	Section 75-10-212, MCA prohibits dumping or leaving any debris or refuse upon or within 200 yards of any highway, road, street, or alley of the State or other public property, or on privately owned property where hunting, fishing, or other recreation is permitted. However, the restriction relating to privately owned property does not apply to the owner, his agents, or those disposing of debris or refuse with the owner's consent.	Applicable	
FLOODPLAIN AND FI	LOODWAY MANAGEMENT ACT AND REQUIREMENTS		
§ 76-5-401, MCA and ARM 36.15.601	Section 76-5-401, MCA and ARM 36.15.601 provide that residential, certain agricultural, industrial-commercial, recreational and other uses are permissible within the designated floodway, provided they do not require structures other than portable structures, fill, or permanent storage of materials or equipment.	Applicable	As described in the ROD, there are no designated wetlands, floodplains, or other surface water bodies present at the Facility. If information regarding the presence of, or impact on, wetlands, floodplains, or surface water changes, DEQ may identify applicable or relevant ERCLs.
§ 76-5-402, MCA and ARM 36.15.701	Section 76-5-402, MCA and ARM 36.15.701 provide that in the flood fringe (i.e., within the floodplain but outside the floodway), residential, commercial, industrial, and other structures may be permitted subject to certain conditions relating to placement of fill, roads, and floodproofing.	Applicable	

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.

STANDARD / REGULATION (ERCL Citation) ¹	DESCRIPTION	Please identify if each ERCL is APPLICABLE OR RELEVANT	EXPLANATION OF COMPLIANCE Please describe action to comply with each ERCL. (Text shown below is example text. Please conduct a facilityspecific evaluation.)
ARM 36.15.602(6)	ARM 36.15.602(6) provides that domestic water supply wells may be permitted, even within the floodway, provided the well casing and well meets certain conditions.	Applicable	
ARM 36.15.602(5)(b), 36.15.605(2)(c), (d), and 36.15.703	ARM 36.15.602(5)(b); 36.15.605(2)(c), (d); and 36.15.703 provide that solid and hazardous waste disposal and storage of toxic, flammable, hazardous, or explosive materials are prohibited anywhere in floodways, floodplains, or flood fringe.	Applicable	
ARM 36.15.605(1)	ARM 36.15.605(1) states that the following are prohibited in a floodway: buildings for living purposes or place of assembly or permanent use by human beings; any structure or excavation that will cause water to be diverted from the established floodway, cause erosion, obstruct the natural flow of water, or reduce the carrying capacity of the floodway; and the construction or permanent storage of an object subject to flotation or movement during flood level periods.	Applicable	
§ 76-5-406, MCA and ARM 36.15.216(2)	Section 76-5-406, MCA and ARM 36.15.216(2) contain substantive factors that address obstruction or use within the floodway or floodplain.	Applicable	
ARM 36.15.604 ARM 36.15.602(1) ARM 36.15.603	ARM 36.15.604 (increase in upstream elevation or significantly increase flood velocities), ARM 36.15.602(1) (excavation of material from pits or pools), and ARM 36.15.603 (water diversions or changes in place of diversion) provide further conditions or restrictions that generally apply to specific activities within the floodway or floodplain.	Applicable	
ARM 36.15.701(3)(c)	ARM 36.15.701(3)(c) requires that roads, streets, highways, and rail lines must be designed to minimize increases in flood heights.	Applicable	
ARM 36.15.701(3)(d)	ARM 36.15.701(3)(d) provides that structures and facilities for liquid or solid waste treatment and disposal must be floodproofed to ensure that no pollutants enter flood waters and may be allowed and approved only in accordance with DEQ regulations, which include certain additional prohibitions on such disposal.	Applicable	
ARM 36.15.702(2)	ARM 36.15.702(2) provides the standards applied to residential, commercial, and industrial structures.	Applicable	
ARM 36.15.606	ARM 36.15.606 provides that flood control works comply with safety standards for levees, floodwalls, and riprap.	Applicable	
ARM 36.15.901	ARM 36.15.901 requires electrical systems to be flood-proofed and conform to certain conditions.	Applicable	

¹ This document identifies common environmental requirements, criteria, or limitations (ERCLs) at Comprehensive Environmental Cleanup and Responsibility Act sites. However, this document should be used as a starting point, and is subject to change, as ERCLs are identified on a site-specific basis. As different stages of the cleanup are completed and new ones arise, an ERCLs list may require detailed refinement.