

Brian Schweitzer, Governor

P. O. Box 200901 Helena, MT 59620-0901

(406) 444-2544

Website: www.deq.mt.gov

June 5, 2012

David Mahn All Montana Crematory 1022 Lyon Avenue Lake City, MN 55041

Dear Mr. Mahn:

Montana Air Quality Permit #4735-00 is deemed final as of June 5, 2012, by the Department of Environmental Quality (Department). This permit is for a human remains crematorium. All conditions of the Department's Decision remain the same. Enclosed is a copy of your permit with the final date indicated.

For the Department,

Vickie (1) plan

Vickie Walsh Air Permitting Program Supervisor Air Resources Management Bureau (406) 444-3490

VW:CH Enclosures

Craig Henry

Craig Henrikson P. E. Environmental Engineer Air Resources Management Bureau (406) 444-6711

Montana Department of Environmental Quality Permitting and Compliance Division

Montana Air Quality Permit #4735-00

All Montana Crematory 1022 Lyon Avenue Lake City, MN 55041

June 5, 2012



MONTANA AIR QUALITY PERMIT

Issued To: All Montana Crematory 1022 Lyon Avenue Lake City, MN 55041 Montana Air Quality Permit: #4735-00 Application Complete: March 26, 2012 Preliminary Determination Issued: April 16, 2012 Department's Decision Issued: May 18, 2012 Permit Final: June 5, 2012 AFS: #023-0003

A Montana Air Quality Permit (MAQP), with conditions, is hereby granted to All Montana Crematory. (AMC), pursuant to Sections 75-2-204, 211, and 215 of the Montana Code Annotated (MCA), as amended, and Administrative Rules of Montana (ARM) 17.8.740, *et seq.*, as amended, for the following:

SECTION I: Permitted Facilities

A. Permitted Equipment

AMC proposes to install and operate a natural gas fired 2012 U.S. Equipment "Classic" batch load human remains crematorium with a maximum incineration design capacity of 200 pounds per hour (lb/hr) or 750 lbs per batch. A complete description of the permitted equipment is contained in the permit analysis.

B. Plant Location

AMC is physically located at 107 Oak Street, Anaconda, MT 59711. The legal description of the facility is Section 3, Township 4 North, Range 11 West, Block 26, Lots 11-12 in Deer Lodge County, Montana.

SECTION II: Conditions and Limitations

- A. Operational Requirements
 - 1. AMC shall not incinerate/cremate any material other than human remains and/or any corresponding container unless otherwise approved by the Department of Environmental Quality (Department) in writing (ARM 17.8.749).
 - 2. The operating mode shall rely on a programmable logic controller (PLC) based control which uses temperature control, a primary burner temperature interlock, and timers to insure proper operation for each cremation cycle (ARM 17.8.752).
 - 3. The secondary chamber burner shall be used to preheat the secondary chamber of the crematorium to the minimum required operating temperature prior to igniting the primary chamber burner. The secondary chamber operating temperature of the crematorium shall be maintained above 1600 degrees Fahrenheit (°F) with no single reading less than 1575 °F. The operating temperatures shall be maintained during operation and for one-half hour after waste feed has stopped (ARM 17.8.752).
 - 4. Burners shall be monitored with continuous ultraviolet (UV) detection for detection of loss of flame and an opacity sensor which temporarily suspends operation of the primary chamber burner (ARM 17.8.752).

- 5. AMC shall operate the crematorium as specified in the application for MAQP #4735-00 including all correspondence related to the application. Further, AMC shall develop crematorium operation procedures for the crematorium, print those procedures in a crematorium operation procedures manual, and require all personnel who operate the unit to familiarize themselves with the operating procedures. The operating procedures manual shall be readily available to all personnel who operate the unit. A copy of this manual shall be supplied to the Department upon request (ARM 17.8.752).
- 6. The incinerator exhaust stack shall be a vertical orientation and not horizontal as submitted in the original application. The Department confirmed the vertical design intention with the applicant and considers all correspondence related to the application, part of the application itself (ARM 17.8.749).
- B. Emission Limitations

AMC shall not cause or authorize to be discharged into the atmosphere from the crematorium:

- 1. Visible emissions that exhibit an opacity of 10% or greater averaged over 6 consecutive minutes (ARM 17.8.752).
- 2. Any particulate emissions in excess of 0.10 grains per dry standard cubic foot (gr/dscf) corrected to 12% carbon dioxide (CO₂) (ARM 17.8.752).
- C. Testing Requirements
 - 1. All compliance source tests shall conform to the requirements of the Montana Source Test Protocol and Procedures Manual (ARM 17.8.106).
 - 2. The Department may require further testing (ARM 17.8.105).
- D. Monitoring Requirements
 - 1. AMC shall install, calibrate, maintain, and operate continuous monitoring and recording equipment on the crematorium to measure the secondary chamber exit gas temperature (ARM 17.8.749).
 - 2. AMC shall also record the daily quantity of material incinerated/cremated and the daily hours of operation of the crematorium (ARM 17.8.749).
 - 3. AMC shall maintain on site a log of maintenance activities for the crematorium and temperature monitoring equipment. The log shall be submitted to the Department upon request (ARM 17.8.749).
- E. Operational Reporting Requirements
 - 1. AMC shall supply the Department with annual production information for all emission points, as required by the Department in the annual emission inventory request. The request will include, but is not limited to, all sources of emissions identified in the emission inventory contained in the permit analysis.

Production information shall be gathered on a calendar-year basis and submitted to the Department by the date required in the emission inventory request. Information shall be in the units required by the Department. This information may be used to calculate operating fees, based on actual emissions from the facility, and/or to verify compliance with permit limitations (ARM 17.8.505).

- 2. AMC shall notify the Department of any construction or improvement project conducted, pursuant to ARM 17.8.745, that would include *the addition of a new emissions unit*, change in control equipment, stack height, stack diameter, stack flow, stack gas temperature, source location, or fuel specifications, or would result in an increase in source capacity above its permitted operation. The notice must be submitted to the Department, in writing, 10 days prior to startup or use of the proposed de minimis change, or as soon as reasonably practicable in the event of an unanticipated circumstance causing the de minimis change, and must include the information requested in ARM 17.8.745(l)(d) (ARM 17.8.745).
- 3. All records compiled in accordance with this permit must be maintained by AMC as a permanent business record for at least 5 years following the date of the measurement, must be available at the plant site for inspection by the Department, and must be submitted to the Department upon request (ARM 17.8.749).
- F. Notification

AMC shall provide the Department with written notification of the actual start-up date of the crematorium within 15 days after the actual start-up date (ARM 17.8.749).

SECTION III: General Conditions

- A. Inspection AMC shall allow the Department's representatives access to the source at all reasonable times for the purpose of making inspections or surveys, collecting samples, obtaining data, auditing any monitoring equipment (continuous emissions monitoring system (CEMS) or continuous emissions rate monitoring system (CERMS)) or observing any monitoring or testing, and otherwise conducting all necessary functions related to this permit.
- B. Waiver The permit and the terms, conditions, and matters stated herein shall be deemed accepted if AMC fails to appeal as indicated below.
- C. Compliance with Statutes and Regulations Nothing in this permit shall be construed as relieving AMC of the responsibility for complying with any applicable federal or Montana statute, rule, or standard, except as specifically provided in ARM 17.8.740, *et seq.* (ARM 17.8.756).
- D. Enforcement Violations of limitations, conditions and requirements contained herein may constitute grounds for permit revocation, penalties, or other enforcement action as specified in Section 75-2-401, *et seq.*, MCA.
- E. Appeals Any person or persons jointly or severally adversely affected by the Department's decision may request, within 15 days after the Department renders its decision, upon affidavit setting forth the grounds therefore, a hearing before the Board of Environmental Review (Board). A hearing shall be held under the provisions of the Montana Administrative Procedures Act. The filing of a request for a hearing does not stay the Department's decision, unless the Board issues a stay upon receipt of a petition

and a finding that a stay is appropriate under Section 75-2-211(11)(b), MCA. The issuance of a stay on a permit by the Board postpones the effective date of the Department's decision until conclusion of the hearing and issuance of a final decision by the Board. If a stay is not issued by the Board, the Department's decision on the application is final 16 days after the Department's decision is made.

- F. Permit Inspection As required by ARM 17.8.755, Inspection of Permit, a copy of the air quality permit shall be made available for inspection by the Department at the location of the source.
- G. Permit Fee Pursuant to Section 75-2-220, MCA, failure to pay the annual operation fee by AMC may be grounds for revocation of this permit, as required by that section and rules adopted thereunder by the Board.
- H. Duration of Permit Construction or installation must begin or contractual obligations entered into that would constitute substantial loss within 3 years of permit issuance and proceed with due diligence until the project is complete or the permit shall expire (ARM 17.8.762).

Montana Air Quality Permit (MAQP) Analysis All Montana Crematory MAQP #4735-00

I. Introduction/Process Description

All Montana Crematory (AMC) owns and operates a human crematory (crematorium) with a maximum incineration capacity of 200 pounds per hour (lb/hr). AMC is located at 107 Oak Street, Anaconda, Montana. The legal description of the facility is Section 3, Township 4 North, Range 11 West, Block 26, Lots 11-12 in Deer Lodge County, Montana.

A. Permitted Equipment

AMC proposes to operate a 2012 U.S. Equipment "Classic" multiple chamber human cremation unit with a maximum incineration capacity of 200 pounds per hour (lb/hr), and associated equipment.

B. Source Description

The crematory is fired on natural gas and is capable of incinerating up to 200 lb/hr of human remains. The operating mode shall rely on automatic programmable logic control (PLC) based control which uses temperature control, a primary burner temperature interlock, and PLC based timers to insure proper operation for each cremation cycle. The secondary chamber burner shall be used to preheat the secondary chamber of the crematorium to the minimum required operating temperature prior to igniting the primary chamber burner. The secondary chamber operating temperature of the crematorium shall be maintained above 1600 degrees Fahrenheit (°F) with no single reading less than 1575 °F. Burners are also monitored with continuous ultraviolet (UV) detection for detection of loss of flame and an opacity sensor which temporarily suspends operation of the primary chamber burner when the opacity gets too high. Residence time in the secondary chamber is in excess of 1.0 second to achieve a high level of destruction efficiency

Initial and supplementary combustion is provided by two burners, one in the primary chamber and one in the secondary chamber, with a total maximum rated design capacity of 2,000,000 British thermal units per hour (Btu/hr).

II. Applicable Rules and Regulations

The following are partial explanations of some applicable rules and regulations that apply to the facility. The complete rules are stated in the Administrative Rules of Montana (ARM) and are available, upon request, from the Department of Environmental Quality (Department). Upon request, the Department will provide references for location of complete copies of all applicable rules and regulations or copies where appropriate.

- A. ARM 17.8, Subchapter 1 General Provisions, including but not limited to:
 - 1. <u>ARM 17.8.101 Definitions</u>. This rule includes a list of applicable definitions used in this chapter, unless indicated otherwise in a specific subchapter.
 - 2. <u>ARM 17.8.105 Testing Requirements</u>. Any person or persons responsible for the emission of any air contaminant into the outdoor atmosphere shall, upon written request of the Department, provide the facilities and necessary equipment (including instruments and sensing devices) and shall conduct tests, emission or ambient, for such periods of time as may be necessary using methods approved by the Department.

3. <u>ARM 17.8.106 Source Testing Protocol</u>. The requirements of this rule apply to any emission source testing conducted by the Department, any source or other entity as required by any rule in this chapter, or any permit or order issued pursuant to this chapter, or the provisions of the Clean Air Act of Montana, 75-2-101, *et seq.*, Montana Code Annotated (MCA).

AMC shall comply with the requirements contained in the Montana Source Test Protocol and Procedures Manual, including, but not limited to, using the proper test methods and supplying the required reports. A copy of the Montana Source Test Protocol and Procedures Manual is available from the Department upon request.

- 4. <u>ARM 17.8.110 Malfunctions</u>. (2) The Department must be notified promptly by telephone whenever a malfunction occurs that can be expected to create emissions in excess of any applicable emission limitation or to continue for a period greater than 4 hours.
- 5. <u>ARM 17.8.111 Circumvention</u>. (1) No person shall cause or permit the installation or use of any device or any means that, without resulting in reduction of the total amount of air contaminant emitted, conceals or dilutes an emission of air contaminant that would otherwise violate an air pollution control regulation. (2) No equipment that may produce emissions shall be operated or maintained in such a manner as to create a public nuisance.
- B. ARM 17.8, Subchapter 2 Ambient Air Quality, including, but not limited to the following:
 - 1. ARM 17.8.204 Ambient Air Monitoring
 - 2. <u>ARM 17.8.210 Ambient Air Quality Standards for Sulfur Dioxide</u>
 - 3. ARM 17.8.211 Ambient Air Quality Standards for Nitrogen Dioxide
 - 4. ARM 17.8.212 Ambient Air Quality Standards for Carbon Monoxide
 - 5. ARM 17.8.213 Ambient Air Quality Standard for Ozone
 - 6. ARM 17.8.214 Ambient Air Quality Standard for Hydrogen Sulfide
 - 7. ARM 17.8.220 Ambient Air Quality Standard for Settled Particulate Matter
 - 8. ARM 17.8.221 Ambient Air Quality Standard for Visibility
 - 9. ARM 17.8.222 Ambient Air Quality Standard for Lead
 - 10. ARM 17.8.223 Ambient Air Quality Standard for PM₁₀
 - 11. ARM 17.8.230 Fluoride in Forage

AMC must maintain compliance with the applicable ambient air quality standards. As part of the risk assessment required for this project, the Department conducted SCREEN3 modeling, an Environmental Protection Agency (EPA)-approved air dispersion model. The screening analysis demonstrated that the proposed project would comply with all applicable ambient air quality standards and demonstrated negligible risk to human health as required for permit issuance.

- C. ARM 17.8, Subchapter 3 Emission Standards, including, but not limited to:
 - 1. <u>ARM 17.8.304 Visible Air Contaminants</u>. This rule requires that no person may cause or authorize emissions to be discharged into the outdoor atmosphere from any source installed after November 23, 1968, that exhibit an opacity of 20% or greater averaged over 6 consecutive minutes.
 - 2. <u>ARM 17.8.308 Particulate Matter, Airborne</u>. (1) This rule requires an opacity limitation of less than 20% for all fugitive emission sources and that reasonable precautions be taken to control emissions of airborne particulate matter.

- 3. <u>ARM 17.8.309 Particulate Matter, Fuel Burning Equipment</u>. This rule requires that no person shall cause, allow, or permit to be discharged into the atmosphere particulate matter caused by the combustion of fuel in excess of the amount determined by this rule.
- 4. <u>ARM 17.8.310 Particulate Matter, Industrial Process</u>. This rule requires that no person shall cause, allow, or permit to be discharged into the atmosphere particulate matter in excess of the amount set forth in this rule.
- 5. <u>ARM 17.8.316 Incinerators</u>. This rule requires that no person may cause or authorize emissions to be discharged into the outdoor atmosphere from any incinerator, particulate matter in excess of 0.10 grains per standard cubic foot (gr/dscf) of dry flue gas, adjusted to 12% carbon dioxide and calculated as if no auxiliary fuel had been used. Further, no person shall cause or authorize to be discharged into the outdoor atmosphere from any incinerator emissions that exhibit an opacity of 10% or greater averaged over 6 consecutive minutes.
- 6. <u>ARM 17.8.322 Sulfur Oxide Emissions--Sulfur in Fuel</u>. This rule requires that no person shall burn liquid, solid, or gaseous fuel in excess of the amount set forth in this rule.
- ARM 17.8.340 Standard of Performance for New Stationary Sources and Emission <u>Guidelines for Existing Sources</u>. This rule incorporates, by reference, 40 Code of Federal Regulations (CFR) Part 60, Standards of Performance for New Stationary Sources (NSPS). This facility is not an NSPS affected source because it does not meet the definition of any NSPS subpart defined in 40 CFR Part 60.
- D. ARM 17.8, Subchapter 5 Air Quality Permit Application, Operation, and Open Burning Fees, including, but not limited to:
 - 1. <u>ARM 17.8.504 Air Quality Permit Application Fees</u>. This rule requires that an applicant submit an air quality permit application fee concurrent with the submittal of an air quality permit application. A permit application is incomplete until the proper application fee is paid to the Department. AMC submitted the appropriate permit application fee for the current permit action.
 - 2. <u>ARM 17.8.505 Air Quality Operation Fees</u>. An annual air quality operation fee must, as a condition of continued operation, be submitted to the Department by each source of air contaminants holding an air quality permit (excluding an open burning permit) issued by the Department. The air quality operation fee is based on the actual or estimated actual amount of air pollutants emitted during the previous calendar year.

An air quality operation fee is separate and distinct from an air quality permit application fee. The annual assessment and collection of the air quality operation fee, described above, shall take place on a calendar-year basis. The Department may insert into any final permit issued after the effective date of these rules, such conditions as may be necessary to require the payment of an air quality operation fee on a calendar-year basis, including provisions that prorate the required fee amount.

- E. ARM 17.8, Subchapter 7 Permit, Construction, and Operation of Air Contaminant Sources, including, but not limited to:
 - 1. <u>ARM 17.8.740 Definitions</u>. This rule is a list of applicable definitions used in this chapter, unless indicated otherwise in a specific subchapter.

- 2. <u>ARM 17.8.743 Montana Air Quality Permits--When Required</u>. This rule requires a person to obtain an air quality permit or permit modification to construct, modify, or use any air contaminant sources that have the potential to emit (PTE) greater than 25 tons per year of any pollutant. AMC does not have a PTE greater than 25 tons per year of any pollutant; however, in accordance with the MCA 75-2-215, an air quality permit must be obtained prior to the construction and operation of any incinerator, regardless of potential incinerator emissions. Because AMC must obtain an air quality permit, all normally applicable requirements apply in this case.
- 3. <u>ARM 17.8.744 Montana Air Quality Permits--General Exclusions</u>. This rule identifies the activities that are not subject to the Montana Air Quality Permit program.
- 4. <u>ARM 17.8.745 Montana Air Quality Permits--Exclusion for De Minimis Changes</u>. This rule identifies the de minimis changes at permitted facilities that do not require a permit under the Montana Air Quality Permit Program.
- 5. <u>ARM 17.8.748 New or Modified Emitting Units--Permit Application Requirements</u>. (1) This rule requires that a permit application be submitted prior to installation, modification, or use of a source. AMC submitted the required permit application for the current permit action. (7) This rule requires that the applicant notify the public by means of legal publication in a newspaper of general circulation in the area affected by the application for a permit. AMC submitted an affidavit of publication of public notice for the March 9, 2012, issue of the *Anaconda Leader*, a newspaper of general circulation in the County of Deer Lodge, as proof of compliance with the public notice requirements.
- 6. <u>ARM 17.8.749 Conditions for Issuance or Denial of Permit</u>. This rule requires that the permits issued by the Department must authorize the construction and operation of the facility or emitting unit subject to the conditions in the permit and the requirements of this subchapter. This rule also requires that the permit must contain any conditions necessary to assure compliance with the Federal Clean Air Act (FCAA), the Clean Air Act of Montana, and rules adopted under those acts.
- 7. <u>ARM 17.8.752 Emission Control Requirements</u>. This rule requires a source to install the maximum air pollution control capability that is technically practicable and economically feasible, except that Best Available Control Technology (BACT) shall be utilized. The required BACT analysis is included in Section III of this permit analysis.
- 8. <u>ARM 17.8.755 Inspection of Permit</u>. This rule requires that air quality permits shall be made available for inspection by the Department at the location of the source.
- 9. <u>ARM 17.8.756 Compliance with Other Requirements</u>. This rule states that nothing in the permit shall be construed as relieving AMC of the responsibility for complying with any applicable federal or Montana statute, rule, or standard, except as specifically provided in ARM 17.8.740, *et seq*.
- 10. <u>ARM 17.8.759 Review of Permit Applications</u>. This rule describes the Department's responsibilities for processing permit applications and making permit decisions on those permit applications that do not require the preparation of an environmental impact statement.
- 11. <u>ARM 17.8.762 Duration of Permit</u>. An air quality permit shall be valid until revoked or modified, as provided in this subchapter, except that a permit issued prior to construction of a new or modified source may contain a condition providing that the permit will expire unless construction is commenced within the time specified in the permit, which in no event may be less than 1 year after the permit is issued.

- 12. <u>ARM 17.8.763 Revocation of Permit</u>. An air quality permit may be revoked upon written request of the permittee, or for violations of any requirement of the Clean Air Act of Montana, rules adopted under the Clean Air Act of Montana, the FCAA, rules adopted under the FCAA, or any applicable requirement contained in the Montana State Implementation Plan (SIP).
- 13. <u>ARM 17.8.764 Administrative Amendment to Permit</u>. An air quality permit may be amended for changes in any applicable rules and standards adopted by the Board of Environmental Review (Board) or changed conditions of operation at a source or stack that do not result in an increase of emissions as a result of those changed conditions. The owner or operator of a facility may not increase the facility's emissions beyond permit limits unless the increase meets the criteria in ARM 17.8.745 for a de minimis change not requiring a permit, or unless the owner or operator applies for and receives another permit in accordance with ARM 17.8.748, ARM 17.8.749, ARM 17.8.752, ARM 17.8.755, and ARM 17.8.756, and with all applicable requirements in ARM Title 17, Chapter 8, Subchapters 8, 9, and 10.
- 14. <u>ARM 17.8.765 Transfer of Permit</u>. This rule states that an air quality permit may be transferred from one person to another if written notice of intent to transfer, including the names of the transferor and the transferee, is sent to the Department.
- 15. <u>ARM 17.8.770 Additional Requirements for Incinerators</u>. This rule specifies the additional information that must be submitted to the Department for incineration facilities subject to 75-2-215, MCA.
- F. ARM 17.8, Subchapter 8 Prevention of Significant Deterioration of Air Quality, including, but not limited to:
 - 1. <u>ARM 17.8.801 Definitions</u>. This rule is a list of applicable definitions used in this subchapter.
 - 2. <u>ARM 17.8.818 Review of Major Stationary Sources and Major Modifications--Source</u> <u>Applicability and Exemptions</u>. The requirements contained in ARM 17.8.819 through ARM 17.8.827 shall apply to any major stationary source and any major modification, with respect to each pollutant subject to regulation under the FCAA that it would emit, except as this subchapter would otherwise allow.

This facility is not a major stationary source because this facility is not a listed source and the facility's PTE is below 250 tons per year of any pollutant.

- G. ARM 17.8, Subchapter 12 Operating Permit Program Applicability, including, but not limited to:
 - 1. <u>ARM 17.8.1201 Definitions</u>. (23) Major Source under Section 7412 of the FCAA is defined as any source having:
 - a. PTE > 100 tons/year of any pollutant;
 - b. PTE > 10 tons/year of any one hazardous air pollutant (HAP), PTE > 25 tons/year of a combination of all HAPs, or lesser quantity as the Department may establish by rule; or

- c. PTE > 70 tons/year of particulate matter with an aerodynamic diameter of 10 microns or less (PM₁₀) in a serious PM₁₀ nonattainment area.
- <u>ARM 17.8.1204 Air Quality Operating Permit Program</u>. (1) Title V of the FCAA amendments of 1990 requires that all sources, as defined in ARM 17.8.1204(1), obtain a Title V Operating Permit. In reviewing and issuing MAQP #4735-00 for All Montana Crematory, the following conclusions were made:
 - a. The facility's PTE is less than 100 tons/year for any pollutant.
 - b. The facility's PTE is less than 10 tons/year for any one HAP and less than 25 tons/year for all HAPs.
 - c. This source is not located in a serious PM_{10} nonattainment area.
 - d. This facility is not subject to any current NSPS.
 - e. This facility is not subject to any current National Emission Standards for Hazardous Air Pollutants (NESHAP) standards.
 - f. This source is not a Title IV affected source, or a solid waste combustion unit.
 - g. This source is not an EPA designated Title V source.

Based on these facts, the Department determined that AMC will be a minor source of emissions as defined under the Title V operating permit program.

- H. MCA 75-2-103, Definitions provides, in part, as follows:
 - 1. "Incinerator" means any single or multiple-chambered combustion device that burns combustible material, alone or with a supplemental fuel or catalytic combustion assistance, primarily for the purpose of removal, destruction, disposal, or volume reduction of all or any portion of the input material.
 - 2. "Solid waste" means all putrescible and nonputrescible solid, semisolid, liquid, or gaseous wastes, including, but not limited to air pollution control facilities...
- I. MCA 75-2-215, Solid or Hazardous Waste Incineration Additional permit requirements:
 - 1. MCA 75-2-215 requires air quality permits for all new solid waste incinerators; therefore, AMC must obtain an air quality permit.
 - 2. MCA 75-2-215 requires the applicant to provide, to the Department's satisfaction, a characterization and estimate of emissions and ambient concentrations of air pollutants, including hazardous air pollutants, from the incineration of solid waste. The information in the initial permit application fulfilled this requirement.
 - 3. MCA 75-2-215 requires that the Department reach a determination that the projected emissions and ambient concentrations constitute a negligible risk to public health, safety, and welfare. The Department completed a health risk assessment, based on an emissions inventory and ambient air quality modeling, for this MAQP application. Based on the results of the emission inventory, modeling, and the health risk assessment, the Department determined that AMC complies with this requirement.

4. MCA 75-2-215 requires the application of pollution control equipment or procedures that meet or exceed BACT. The Department determined that the operating the proposed incinerator (crematorium) according to the manufacturer-recommended operation procedures constitutes BACT.

III. BACT Determination

A BACT determination is required for each new or modified source. AMC shall install on the new or modified source the maximum air pollution control capability which is technically practicable and economically feasible, except that BACT shall be utilized. In addition, MCA 75-2-215 requires a BACT determination for all pollutants resulting from the crematory operations, not only criteria pollutants.

AMC proposes to control the emissions from the crematorium with a secondary chamber designed specifically to reduce the amount of pollutants, including HAPs, emitted from the incinerator. Previous research conducted by the Department indicates crematoriums of this size have not been required to install additional air pollution control equipment beyond that provided by the controlled air design of the incinerator. With the estimated particulate matter emissions being 2.05 tons per year (TPY), the incremental cost per ton of additional control would be very high and not in line with control costs of other similar sources. In addition, the incinerator is limited by the MAQP to 0.10 gr/dscf for particulate matter and to 10% opacity (visible emissions). Furthermore, the health risk assessment shows negligible risks from the small amount of HAP emissions from this incinerator as is. Therefore, the Department determined that proper operation of the controlled air incinerator, and compliance with the operational conditions of MAQP #4735-00 constitutes BACT in this case.

BACT for products of combustion/incineration (carbon monoxide [CO], oxides of nitrogen [NO_x], volatile organic compounds [VOC], and Sulfur dioxide [SO₂]) and HAPs resulting from crematorium operations is proper crematorium design and operation. Proper design includes relying on good turbulence, high temperature and the residence time within the secondary combustion chamber. Turbulence is achieved with proper introduction of air into the combustion chambers. Temperature is achieved by including the requirement that the secondary chamber must be maintained at an operating temperature of 1600 °F with no single reading less than 1575 °F (ARM 17.8.752). Residence time is achieved by sizing the secondary combustion chamber. The operating procedures, design and temperature and timer interlocks requirement contained in MAQP #4735-00 will ensure proper combustion and constitutes BACT for this source. BACT for incinerators also includes ultraviolet (UV) monitoring for both the primary and secondary chamber burners which detect loss of flame and result in primary burner shutdown. Continuous opacity sensing interlocked with the primary combustion chamber burner also suspends operation when the opacity gets too high.

Further, natural gas combustion inherently results in low emissions of air pollutants due to characteristics of the fuel fired. Potential PM_{10} , $PM_{2.5}$, NO_x , CO, VOC, and SO_2 emissions from the combustion of natural gas to operate the crematorium are 0.07 TPY, 0.07 TPY, 0.86 TPY, 0.72 TPY, 0.05 TPY, and 0.01 TPY, respectively. Because potential emissions of all regulated pollutants resulting from natural gas combustion are low, incorporation of available pollutant-specific control technologies would result in high cost-effective (cost per ton removed) values thereby making pollutant-specific add-on controls for PM_{10} , $PM_{2.5}$, NO_x , CO, VOC, and SO_2 economically infeasible in this case. Therefore, the Department determined that combustion of natural gas and proper operation and maintenance of the crematorium with no additional control constitutes BACT for all regulated pollutants resulting from natural gas combustion, in this case.

The BACT analysis for this source is similar to other recently permitted similar sources and should result in achieving the appropriate emission standards.

IV. Emission Inventory

		Emissions Tons/Year [PTE]							
Criteria Pollutant Emission Source			PM ₁₀	$PM_{2.5}$	NOx	CO	SOx	VOC	Lead
Crematorium			0.49	0.49	1.56	1.29	0.95	1.31	0.03
Natural Gas Combustion			0.07	0.07	0.86	0.72	0.01	0.05	0.00
	TOTAL EMISSIONS >	2.11	0.56	0.56	2.42	2.01	0.96	1.36	0.03

PM, particulate matter

 PM_{10} , particulate matter with an aerody namic diameter of 10 microns or less

 $\text{PM}_{2.5},\;\text{particulate matter with an aerody namic diameter of 2.5 microns or let$

NO_x, oxides of nitrogen

CO, carbon monoxide

SO₂, oxides of sulfur

VOC, volatile organic compounds

Lead, Lead emissions

MMscf, Million standard cubic feet

All Montana Crematory

Criteria Pollutant from Crematory

erematory			
Maximum Process Rate:	200.0 lbs/hr	(Note: Equipment submittal says 150-200 lbs/h	ır)
Operating Hours	8760 hours/year		
Annual Capacity	(200.00 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	876 tons/yr	
PM Emissions:			
Emission Factor	4.67 lbs/ton	(AP42 Table 2.3-2. 07/93)	
Calculations	(4.67 lbs/ton) * (876.00 tons/yr *(0.0005) =		2.05 tons/yr
PM ₁₀ Emissions:			
Emission Factor	1.13 lbs/ton	FIRE	
Calculations	(1.13 lbs/ton) * (876.00 tons/yr *(0.0005) =		0.49 tons/yr
PM _{2.5} Emissions:	(Assumed to be equivalent to PM ₁₀)		
NO _x Emissions			
Emission Factor	3.56 lbs/ton	(AP42 Table 2.3-1. 07/93)	
Calculations	(3.56 lbs/ton) * (876.00 tons/yr *(0.0005) =		1.56 tons/yr
CO Emissions			
Emission Factor	2.95 lbs/ton	(AP42 Table 2.3-1. 07/93)	
Calculations	(2.95 lbs/ton) * (876.00 tons/yr *(0.0005) =		1.29 tons/yr
SOx			
Emission Factor	2.17 lbs/ton	(AP42 Table 2.3-1. 07/93)	
Calculations	(2.17 lbs/ton) * (876.00 tons/yr *(0.0005) =		0.95 tons/yr

VOC Emissions				
Emission Factor Calculations	3 Ibs/ton (3 Ibs/ton) * (876.00 tons/yr *(0.0005) =	AFSSCC 5-02-005-05, 3/90	1.31 tor	ns/yr
Lead Emissions				
Emission Factor Calculations	0.0728 lbs/ton (0.0728 lbs/ton) * (876.00 tons/yr *(0.0005) =	AP42 Table 2.3-2, 07/93	0.0318864 tor	ns/yr
Criteria Pollutants from	n Natural Gas Combustion			
Hours of Operation	8760 hrs/yr		Annelissant	
Max Fuel Compustion	from AP42	2,000,000 BTO/nr	Submittal	
PM Emissions:				
Emission Factor	7.60 lbs/MMSCF	AP42 Table 1.4-1,		
Calculations	(7.6 lbs/MMSCF) * (0.002 MMSCF/hour) = (0.01 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	07/98	0.015 lbs 0.07 TF	s/hr >Y
PM ₁₀ and PM _{2.5} Emissio	ns assumed equal to PM			
NO Enciesione				
NU _X Emissions				
Emission Factor		07/98		
Calculations	(100 lbs/MMSCF) * (0.002 MMSCF/hour) = (0.20 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =		0.196 lbs 0.86 TF	s/hr >Y
CO Emissions:				
Emission Factor	84.00 lbs/MMSCF	AP42 Table 1.4-1, 07/98		
Calculations	(84 lbs/MMSCF) * (0.002 MMSCF/hour) = (0.16 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =		0.165 lbs 0.72 TF	s/hr >Y
SO _x Emissions				
Emission Factor	0.60 lbs/MMSCF	AP42 Table 1.4-1,		
Calculations	(0.6 lbs/MMSCF) * (0.002 MMSCF/hour) =	07/98	0.001 lbs	s/hr
	(0.00 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =		0.01 TP	γ
Emission Factor	5.50 lbs/MMSCF	AP42 Table 1.4-1.		
		07/98	0.044	
Calculations	(5.5 lbs/MMSCF) * (0.002 MMSCF/hour) = (0.01078 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =		0.011 lbs 0.05 TP	s/hr >Y
Lead Emissions:				
Emission Factor	0.0005 lbs/MMSCF	AP42 Table 1.4-1,		
Calculations	(0.0005 lbs/MMSCF) * (0.002 MMSCF/hour) = (0.000001 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	07/98	9.8039E-07 lbs 0.00000 TF	s/hr >Y

HAP Emissions	HAP Emissions from Crematorium					
HAP TPY						
Bromoform	1.27E-05					
Carbon Tetrachloride	2.51E-05					
Chloroform	2.39E-05					
1,2- Dichloropropane	5.78E-04					
Ethyl Benzene	7.05E-04					
Napthalene	5.08E-03					
Tetrachloroethylene	1.77E-05					
1,1,2,2-tetrachlorethane	4.82E-05					
Toluene	2.02E-03					
Vinylidine chloride	3.11E-05					
Xylene	9.64E-04					
Total HAP Potential Emissions	9.51E-03					

HAP Emission Inventory: Crematorium (Montana DEQ Policy)

HAP Emissions from Crem	atorium (Montana DEQ Policy)			
Annual Capacity	(200.00 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	876 tons/yr		
Bromoform				
Emission Factor	0.000029 lbs/ton	AFSSCC 5-02-005-05		
Calculations	(0.000029 lbs/ton) * (876.00 tons/yr *(0.0005) =		1.27E-05	tons/yr
Carbon Tetrachloride				
Emission Factor	0.0000574 lbs/ton	AFSSCC 5-02-005-05		
Calculations	(0.0000574 lbs/ton) * (876.00 tons/yr *(0.0005) =		2.51E-05	tons/yr
Chloroform				
Emission Factor	0.0000545 lbs/ton	AFSSCC 5-02-005-05		
Calculations	(0.0000545 lbs/ton) * (876.00 tons/yr *(0.0005) =		2.39E-05	tons/yr
1,2- Dichloropropane				
Emission Factor Calculations	0.00132 lbs/ton (0.00132 lbs/ton) * (876.00 tons/vr *(0.0005)	AFSSCC 5-02-005-05	5.78F-04	tons/vr
	=			
Ethyl Benzene				
Emission Factor	0.00161 lbs/ton	AFSSCC 5-02-005-05		
Calculations	(0.00161 lbs/ton) * (876.00 tons/yr *(0.0005) =		7.05E-04	tons/yr
Napthalene				
Emission Factor	0.0116 lbs/ton	AFSSCC 5-02-005-05		
Calculations	(0.0116 lbs/ton) * (876.00 tons/yr *(0.0005) =		5.08E-03	tons/yr

Tetrachloroethylene				
Emission Factor Calculations	0.0000403 lbs/ton (0.0000403 lbs/ton) * (876.00 tons/vr	AFSSCC 5-02-005-05	1 77E-05	tons/vr
Calculation	*(0.0005) =			tonio, yr
1,1,2,2-tetrachlorethane				
Emission Factor	0.00011 lbs/ton	AFSSCC 5-02-005-05		
Calculations	(0.00011 lbs/ton) * (876.00 tons/yr *(0.0005) =		4.82E-05	tons/yr
Toluene				
Emission Factor	0.00462 lbs/ton	AFSSCC 5-02-005-05		
Calculations	(0.00462 lbs/ton) * (876.00 tons/yr *(0.0005) =		2.02E-03	tons/yr
		Note: Those have been workbook.	n copied in here fr	om
Vinylidine chloride				
Emission Factor	0.000071 lbs/ton	AFSSCC 5-02-005-05		
Calculations	(0.000071 lbs/ton) * (876.00 tons/yr *(0.0005) =		3.11E-05	tons/yr
Xylene				
Emission Factor	0.0022 lbs/ton	AFSSCC 5-02-005-05		
Calculations	(0.0022 lbs/ton) * (876.00 tons/yr *(0.0005) =		9.64E-04	tons/yr

НАР	ТРҮ	
2-Methy Inapthalene	2.06E-07	=
3-Methylchloranthrene	1.55E-08	_
7,12-Dimethylbenz(a) anthracene	1.37E-07	_
Acenaphthene	1.55E-08	-
Acenaphthylene	1.55E-08	-
Anthracene	2.06E-08	-
Benzene	1.80E-05	-
Benz(a)anthracene	1.55E-08	-
Benzo(a)py rene	1.03E-08	-
Benzo(b)fluoranthene	1.55E-08	-
Benzo(k)fluoranthene	1.55E-08	-
Benzo(g,h,i) perylene	1.03E-08	1
chrysene	1.55E-08	-
Dibenzo(a,h,)anthracene	1.03E-08	-
Dichlorobenzene	1.03E-05	-
Fluoranthene	2.58E-08	_
Fluorene	2.40E-08	_
Formaldehy de	6.44E-04	_
Hexane	1.55E-02	
Indeno(1,2,3,d,d,)py rene	1.55E-08	
Naphthalene	5.24E-06	
Phenanthrene	1.46E-07	
Pyrene	4.29E-08	
Toluene	2.92E-05	
Arsenic	1.72E-06	
Beryllium	1.03E-07	
Cadmium	9.45E-06	
Chromium, Total	1.20E-05	
Cobalt	7.21E-07	
Lead	4.29E-06	
Manganese	3.26E-06	
Mercury	2.23E-06	
Nickel	1.80E-05	
Selenium	2.06E-07	
Total HAP Potential Emissions	1.62E-02	4.67E-04

Hours of Operation			8760	hrs/yr		
Maximum Rated Design Ca	pacity		0.001960784	MMscf/hr		
2-Methylnapthalene						
Emission Factor	2.4000E-05	lbs/MMscf 7/98	[AP-42 Table 1.4-3,	MMscf/hr	4.706E-08	lbs/hr
Calculations	(0.000024 lbs/ (0.00000005 ll	MMscf) * (0.00 os/hr) * (8760 h	2 MMscf/hour) = nrs/yr) *(0.0005 tons/lb) =		2.06E-07	TPY

3-Methylchloranthrene			
Emission Factor	1.8000E-06 lbs/MMscf [AP-42 Table 1.4-3, 7/98	3.529E-09	lbs/hr
Calculations	(0.0000018 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000000 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	1.55E-08	TPY
7,12-Dimethylbenz(a) an	thracene		
Emission Factor Calculations	1.6000E-05 lbs/MMscf [AP-42 Table 1.4-3, 7/98 (0.000016 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000003 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	3.137E-08 1.37E-07	lbs/hr TPY
Acenaphthene			
Emission Factor	1.8000E-06 lbs/MMscf [AP-42 Table 1.4-3, 7/98	3.529E-09	lbs/hr
Calculations	(0.0000018 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000000 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	1.55E-08	TPY
Acenaphthylene			
Emission Factor	1.8000E-06 lbs/MMscf [AP-42 Table 1.4-3, 7/98	3.529E-09	lbs/hr
Calculations	(0.0000018 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000000 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	1.55E-08	TPY
Anthracene			
Emission Factor	2.4000E-06 lbs/MMscf [AP-42 Table 1.4-3, 7/98	4.706E-09	lbs/hr
Calculations	(0.0000024 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000000 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	2.06E-08	TPY
Benzene			
Emission Factor	2.1000E-03 lbs/MMscf [AP-42 Table 1.4-3, 7/98	4.118E-06	lbs/hr
Calculations	(0.0021 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000412 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	1.80E-05	TPY
Benz(a)anthracene			
Emission Factor	1.8000E-06 lbs/MMscf [AP-42 Table 1.4-3, 7/98	3.529E-09	lbs/hr
Calculations	(0.0000018 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000000 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	1.55E-08	TPY
Benzo(a)pyrene			
Emission Factor	1.2000E-06 lbs/MMscf [AP-42 Table 1.4-3, 7/98	2.353E-09	lbs/hr
Calculations	(0.0000012 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000000 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	1.03E-08	TPY
Benzo(b)fluoranthene			
Emission Factor	1.8000E-06 lbs/MMscf [AP-42 Table 1.4-3, 7/98	3.529E-09	lbs/hr
Calculations	(0.0000018 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000000 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	1.55E-08	TPY
Benzo(k)fluoranthene			
Emission Factor	1.8000E-06 lbs/MMscf [AP-42 Table 1.4-3, 7/98	3.529E-09	lbs/hr
Calculations	(0.0000018 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000000 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	1.55E-08	TPY

Benzo(g,h,i) perylene			
Emission Factor Calculations	1.2000E-06 lbs/MMscf [AP-42 Table 1.4-3, 7/98 (0.0000012 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000000 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	2.353E-09 1.03E-08	lbs/hr TPY
Chrysene			
Emission Factor Calculations	1.8000E-06 lbs/MMscf [AP-42 Table 1.4-3, 7/98 (0.0000018 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000000 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	3.529E-09 1.55E-08	lbs/hr TPY
Dibenzo(a,h,)anthracene			
Emission Factor Calculations	1.2000E-06 lbs/MMscf [AP-42 Table 1.4-3, 7/98 (0.0000012 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000000 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	2.353E-09 1.03E-08	lbs/hr TPY
Dichlorobenzene			
Emission Factor Calculations	1.2000E-03 lbs/MMscf [AP-42 Table 1.4-3, 7/98 (0.0012 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000235 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	2.353E-06 1.03E-05	lbs/hr TPY
Fluoranthene			
Emission Factor Calculations	3.0000E-06 lbs/MMscf [AP-42 Table 1.4-3, 7/98 (0.000003 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000001 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	5.882E-09 2.58E-08	lbs/hr TPY
Fluorene			
Emission Factor Calculations	2.8000E-06 lbs/MMscf [AP-42 Table 1.4-3, 7/98 (0.0000028 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000001 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	5.490E-09 2.40E-08	lbs/hr TPY
Formaldehyde			
Emission Factor Calculations	7.5000E-02 lbs/MMscf [AP-42 Table 1.4-3, 7/98 (0.075 lbs/MMscf) * (0.002 MMscf/hour) = (0.00014706 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	1.471E-04 6.44E-04	lbs/hr TPY
Hexane			
Emission Factor	1.8000E+00 lbs/MMscf [AP-42 Table 1.4-3, 7/98	3.529E-03	lbs/hr
Calculations	(1.8 lbs/MMscf) * (0.002 MMscf/hour) = (0.00352941 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	1.55E-02	TPY
Indeno(1,2,3,d,d,)pyrene			
Emission Factor Calculations	1.8000E-06 lbs/MMscf [AP-42 Table 1.4-3, 7/98 (0.0000018 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000000 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	3.529E-09 1.55E-08	lbs/hr TPY
Naphthalene			
Emission Factor Calculations	6.1000E-04 lbs/MMscf [AP-42 Table 1.4-3, 7/98 (0.00061 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000120 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	1.196E-06 5.24E-06	lbs/hr TPY

Phenanthrene			
Emission Factor Calculations	1.7000E-05 lbs/MMscf [AP-42 Table 1.4-3, 7/98 (0.000017 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000003 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	3.333E-08 1.46E-07	lbs/hr TPY
Pyrene			
Emission Factor Calculations	5.0000E-06 lbs/MMscf [AP-42 Table 1.4-3, 7/98 (0.000005 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000001 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	9.804E-09 4.29E-08	lbs/hr TPY
Toluene			
Emission Factor Calculations	3.4000E-03 lbs/MMscf [AP-42 Table 1.4-3, 7/98 (0.0034 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000667 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	6.667E-06 2.92E-05	lbs/hr TPY
Arsenic			
Emission Factor Calculations	2.0000E-04 lbs/MMscf [AP-42 Table 1.4-4, 7/98 (0.0002 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000039 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	3.922E-07 1.72E-06	lbs/hr TPY
Beryllium			
Emission Factor Calculations	1.2000E-05 lbs/MMscf [AP-42 Table 1.4-4, 7/98 (0.000012 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000002 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	2.353E-08 1.03E-07	lbs/hr TPY
Cadmium			
Emission Factor Calculations	1.1000E-03 lbs/MMscf [AP-42 Table 1.4-4, 7/98 (0.0011 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000216 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	2.157E-06 9.45E-06	lbs/hr TPY
Chromium, Total			
Emission Factor Calculations	1.4000E-03 lbs/MMscf [AP-42 Table 1.4-4, 7/98 (0.0014 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000275 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	2.745E-06 1.20E-05	lbs/hr TPY
Cobalt			
Emission Factor Calculations	8.4000E-05 lbs/MMscf [AP-42 Table 1.4-4, 7/98 (0.000084 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000016 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	1.647E-07 7.21E-07	lbs/hr TPY
Lead			
Emission Factor Calculations	5.0000E-04 lbs/MMscf [AP-42 Table 1.4-4, 7/98 (0.0005 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000098 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	9.804E-07 4.29E-06	lbs/hr TPY
Manganese			
Emission Factor Calculations	3.8000E-04 lbs/MMscf [AP-42 Table 1.4-4, 7/98 (0.00038 lbs/MMscf) * (0.002 MMscf/hour) = (0.00000075 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =	7.451E-07 3.26E-06	lbs/hr TPY

Mercury			
Emission Factor	2.6000E-04 lbs/MMscf [AP-42 Table 1.4-4, 7/98	5.098E-07	lbs/hr
Calculations	(0.00026 lbs/MMscf) * (0.002 MMscf/hour) =	2.23E-06	TPY
	(0.00000051 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =		
Nickel			
Emission Factor	2.1000E-03 lbs/MMscf [AP-42 Table 1.4-4, 7/98	4.118E-06	lbs/hr
Calculations	(0.0021 lbs/MMscf) * (0.002 MMscf/hour) =	1.80E-05	TPY
	(0.00000412 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =		
Selenium			
Emission Factor	2.4000E-05 lbs/MMscf [AP-42 Table 1.4-4, 7/98	4.706E-08	lbs/hr
Calculations	(0.000024 lbs/MMscf) * (0.002 MMscf/hour) =	2.06E-07	TPY
	(0.00000005 lbs/hr) * (8760 hrs/yr) *(0.0005 tons/lb) =		

V. Existing Air Quality

AMC is located at 107 Oak Street, Anaconda, MT 59711. The town of Anaconda and the immediate surrounding area is classified as attainment for all pollutants for EPA-established National Ambient Air Quality Standards (NAAQS). The screening analysis performed during the MAQP process demonstrated that the facility complies with all applicable ambient air quality standards and poses a negligible risk to human health as required for permit issuance. Additionally, MAQP #4735-00 contains operating and monitoring requirements to ensure that proper operation of the facility would not result in air emissions that violate any ambient air quality standards.

VI. Air Quality Impacts

The Department conducted SCREEN3 Modeling, an EPA-approved screening model, using the indicated inputs obtained from the emission inventory and a HAP emission rate of 2.74 E-04 grams per second (g/s), which is the sum of all the HAP emissions from the proposed crematorium. The individual one-hour results for each pollutant were then calculated by multiplying the modeled impact of 7.91E-02 micrograms per cubic meter (μ g/m³) by the percentage of each individual HAP making up the total of the HAP emissions. The maximum 1-hour concentrations were then converted to an annual average and used in the risk assessment. This process was repeated for the risk assessment of the HAPs emitted from the combustion of natural gas. The combined HAP emission rate from fuel combustion is 4.76E-04 g/s and the SCREEN3 modeled impact was 1.35 E-02 μ g/m³.

As shown by the Health Risk Assessment of the following Section VII, the Department determined that there is a negligible human health risk associated with the proposed project. With consideration of the modeling accomplished for the Health Risk Assessment, and the small potential to emit of criteria pollutants, the Department determined that the impacts from this permitting action will be minor. The Department believes it will not cause or contribute to a violation of any ambient air quality standard.

VII. Health Risk Assessment

A health risk assessment was conducted to determine if the proposed crematorium complies with the negligible risk requirement of MCA 75-2-215. The environmental effects unrelated to human health were not considered in determining compliance with the negligible risk standard, but were evaluated as required by the Montana Environmental Policy Act, in determining compliance with all applicable rules or other requirements requiring protection of public health, safety, and welfare and the environment.

Pursuant to ARM 17.8.770(1)(c), pollutants may be excluded from the human health risk assessment if the Department determines that exposure from inhalation is the only appropriate pathway to consider in the human health risk assessment and if the ambient concentrations of the pollutants (calculated using the potential to emit; enforceable limits or controls may be considered) are less than the levels specified in Table 1 or Table 2 of ARM 17.8.770.

AMC's proposed incinerator has a stack height of 17 feet with vertical discharge, a stack exit temperature of 1000 °F, and a flow rate of 2,827 actual cubic feet per minute (ACFM) with a 1.8 foot diameter stack. Ambient air modeling was accomplished using SCREEN3 software; an EPA approved ambient air modeling software used for conservative modeling. Ambient air impacts were modeled for the HAPs identified in the PTE calculations of Section IV. The emission inventory did not contain sufficient quantities of any pollutant on the Department's list of pollutants for which non-inhalation impacts must be considered; therefore, the Department determined that inhalation risk was the only necessary pathway to consider. No pollutants exceeded the levels specified in Table 1 or Table 2 of ARM 17.8.770. The SCREEN3 Modeling results are shown below:

Crematorium HAPs Emissions Modeling

SIMPLE	TERRAIN	INPUTS:							
SOURCE	TYPE	=	POINT						
EMISSION	RATE	(G/S)	=	2.74E-04					
STACK	HEIGHT	(M)	=	5.1816					
STK	INSIDE	DIAM	(M)	=	0.5486				
STK	EXIT	VELOCITY	(M/S)=	5.6436					
STK	GAS	EXIT	TEMP	(K)	=	810.9278			
AMBIENT	AIR	TEMP	(K)	=	293				
RECEPTOR	HEIGHT	(M)	=	0					
URBAN/RURAL	OPTION	=	URBAN						
BUILDING	HEIGHT	(M)	=	0					
MIN	HORIZ	BLDG	DIM	(M)	=	0			
MAX	HORIZ	BLDG	DIM	(M)	=	0			
STACK	EXIT	VELOCITY	WAS	CALCULATE	FROM				
VOLUME	FLOW	RATE	=	1.334194	(M**3/S)				
BUOY.	FLUX	=	2.66	M**4/S**3	MOM.	FLUX	=	0.866	M**4/S**2
***	FULL	METEOROL	***						
DIST	CONC	U10M	USTK	MIX	ΗΤ	PLUME	SIGMA	SIGMA	
((110 / 4**2)		1 I						
(171)	(UG/IVI**3)	STAB	(M/S)	(M/S)	(M)	HT	(M)	Y	(M)
(IVI) 	(UG/WI**3)	STAB 	(M/S) 	(M/S) 	(M) 	HT 	(M) 	Y 	(M)
(IVI) 1	(UG/MI**3) 0	STAB 1	(M/S) 1	(M/S) 1	(M) 320	HT 49.8	(M) 0.71	Y 0.68	(M) NO
(M) 1 100	(UG/M**3) 0 4.98E-02	STAB 1 4	(M/S) 1 4	(M/S) 1 4	(M) 320 1280	HT 49.8 16.24	(M) 0.71 16.01	Y 0.68 14.16	(M) NO NO
(M) 1 100 200	(UG/M**3) 0 4.98E-02 3.06E-02	STAB 1 4 4	(M/S) 1 4 2	(M/S) 1 4 2	(M) 320 1280 640	HT 49.8 16.24 27.49	(M) 0.71 16.01 31.44	Y 0.68 14.16 27.93	(M) NO NO NO
(M) 1 100 200 300	(UG/M**3) 4.98E-02 3.06E-02 2.50E-02	STAB 1 4 4 6	(M/S) 1 4 2 1	(M/S) 1 4 2 1	(M) 320 1280 640 10000	HT 49.8 16.24 27.49 39.36	(M) 0.71 16.01 31.44 32.67	Y 0.68 14.16 27.93 22.19	(M) NO NO NO NO
(M) 1 100 200 300	0 4.98E-02 3.06E-02 2.50E-02	STAB 1 4 4 6	(M/S) 1 4 2 1	(M/S) 4 2 1	(M) 320 1280 640 10000	HT 49.8 16.24 27.49 39.36	(M) 0.71 16.01 31.44 32.67	Y 14.16 27.93 22.19	(M) NO NO NO NO
(M) 1 100 200 300 MAXIMUM	0 4.98E-02 3.06E-02 2.50E-02 1-HR	5TAB 1 4 4 6 CONCENTRA	(M/S) 1 4 2 1 AT	(M/S) 4 2 1 OR	(M) 320 1280 640 10000 BEYOND	HT 49.8 16.24 27.49 39.36	(M) 16.01 31.44 32.67 M:	Y 0.68 14.16 27.93 22.19	(M) NO NO NO NO
(M) 1 0 200 300 MAXIMUM 30	(UG/M**3) 0 4.98E-02 3.06E-02 2.50E-02 	5TAB 1 4 4 6 CONCENTRA 3	(M/S) 1 4 2 1 1 AT 10	(M/S) 1 4 2 1 0 R 10	(M) 320 1280 640 10000 BEYOND 3200	HT 49.8 16.24 27.49 39.36 	(M) 16.01 31.44 32.67 M: 6.81	Y 0.68 14.16 27.93 22.19 6.23	(M) NO NO NO NO NO
(M) 1 100 200 300 MAXIMUM 30	0 4.98E-02 3.06E-02 2.50E-02 1-HR 7.91E-02	5TAB 4 4 6 CONCENTRA 3	(M/S) 4 2 1 AT 10	(M/S) 1 4 2 1 0R 10	(M) 1280 640 10000 BEYOND 3200	HT 49.8 16.24 27.49 39.36 1 8.62	(M) 16.01 31.44 32.67 M: 6.81	Y 14.16 27.93 22.19 6.23	(M) NO NO NO NO
(M) 1 100 200 300 MAXIMUM 30 DWASH=	(UG/M**3) 0 4.98E-02 3.06E-02 2.50E-02 2.50E-02 1-HR 7.91E-02 MEANS	STAB 1 4 4 6 CONCENTRA 3 NO	(M/S) 4 2 1 AT 10 CALC	(M/S) 4 2 1 0R 10 MADE	(M) 1280 640 10000 BEYOND 3200 (CONC	HT 49.8 16.24 27.49 39.36 1 8.62 =	(M) 16.01 31.44 32.67 M: 6.81 0.0)	Y 14.16 27.93 22.19 6.23	(M) NO NO NO NO
(M) 1 100 200 300 MAXIMUM 30 DWASH= DWASH=NO	(UG/M**3) 0 4.98E-02 3.06E-02 2.50E-02 	STAB 1 4 4 6 CONCENTRA 3 NO NO	(M/S) 1 4 2 1 AT 10 CALC BUILDING	(M/S) 4 2 1 0R 10 MADE DOWNWAS	(M) 320 1280 640 10000 BEYOND 3200 (CONC USED	HT 49.8 16.24 27.49 39.36 1 8.62 =	(M) 16.01 31.44 32.67 M: 6.81 0.0)	Y 14.16 27.93 22.19 6.23	(M) NO NO NO NO
(M) 1 100 200 300 MAXIMUM 30 DWASH= DWASH=NO DWASH=HS	(UG/M**3) 0 4.98E-02 3.06E-02 2.50E-02 	STAB 1 4 4 6 CONCENTRA 3 NO NO HUBER-SNY	(M/S) 1 4 2 1 AT 10 CALC BUILDING DOWNWAS	(M/S) 1 4 2 1 0 0 R 10 MADE DOWNWAS USED	(M) 320 1280 640 10000 BEYOND 3200 (CONC USED	HT 49.8 16.24 27.49 39.36 1 8.62 =	(M) 16.01 31.44 32.67 M: 6.81 0.0)	Y 14.16 27.93 22.19 6.23	(M) NO NO NO NO
(M) 1 100 200 300 MAXIMUM 30 DWASH= DWASH=NO DWASH=HS DWASH=SS	(UG/M**3) 0 4.98E-02 3.06E-02 2.50E-02 	STAB 1 4 4 6 CONCENTR/ 3 NO NO HUBER-SNY SCHULMAN	(M/S) 1 4 2 1 AT 10 CALC BUILDING DOWNWAS DOWNWAS	(M/S) 1 4 2 1 0R 10 MADE DOWNWAS USED USED	(M) 1280 640 10000 BEYOND 3200 (CONC USED	HT 49.8 16.24 27.49 39.36 1 8.62 =	(M) 16.01 31.44 32.67 M: 6.81 0.0)	Y 0.68 14.16 27.93 22.19 6.23	(M) NO NO NO NO
(M) 1 100 200 300 MAXIMUM 30 DWASH= DWASH=NO DWASH=NS DWASH=SS DWASH=NA	(UG/M**3) 0 4.98E-02 3.06E-02 2.50E-02 	STAB 1 4 4 6 CONCENTRA 3 NO NO HUBER-SNY SCHULMAN DOWNWAS	(M/S) 1 4 2 1 AT 10 CALC BUILDING DOWNWAS DOWNWAS NOT	(M/S) 1 4 2 1 0 R 10 MADE DOWNWAS USED USED APPLICABLE	(M) 320 1280 640 10000 BEYOND 3200 (CONC USED X<3*LB	HT 49.8 16.24 27.49 39.36 1 8.62 =	(M) 16.01 31.44 32.67 M: 6.81 0.0)	Y 0.68 14.16 27.93 22.19 6.23	(M) NO NO NO NO
(M) 1 100 200 300 MAXIMUM 30 DWASH= DWASH=NO DWASH=NS DWASH=SS DWASH=NA	(UG/M**3) 0 4.98E-02 3.06E-02 2.50E-02 2.50E-02 1-HR 7.91E-02 MEANS MEANS MEANS MEANS MEANS MEANS	STAB 1 4 4 6 CONCENTRA 3 NO NO NO HUBER-SNY SCHULMAN DOWNWAS	(M/S) 1 4 2 1 AT 10 CALC BUILDING DOWNWAS DOWNWAS NOT	(M/S) 1 4 2 1 0 R 10 MADE DOWNWAS USED USED APPLICABLE	(M) 320 1280 640 10000 BEYOND 3200 (CONC USED X<3*LB	HT 49.8 16.24 27.49 39.36 1 8.62 =	(M) 16.01 31.44 32.67 M: 6.81 0.0)	Y 0.68 14.16 27.93 22.19 6.23	(M) NO NO NO NO
(M) 1 100 200 300 MAXIMUM 30 DWASH= DWASH=NO DWASH=HS DWASH=SS DWASH=SS DWASH=NA	(UG/M**3) 0 4.98E-02 3.06E-02 2.50E-02 1-HR 7.91E-02 MEANS MEANS MEANS MEANS MEANS MEANS	STAB 1 4 4 6 CONCENTR/ 3 NO NO HUBER-SNY SCHULMAN DOWNWAS	(M/S) 1 4 2 1 MT CALC BUILDING DOWNWAS DOWNWAS NOT	(M/S) 1 4 2 1 0 MADE DOWNWAS USED USED APPLICABLE	(M) 1280 640 10000 BEYOND 3200 (CONC USED X<3*LB	HT 49.8 16.24 27.49 39.36 1 8.62 =	(M) 16.01 31.44 32.67 M: 6.81 0.0)	Y 0.68 14.16 27.93 22.19 6.23	(M) NO NO NO NO
(M) 1 100 200 300 MAXIMUM 30 DWASH= DWASH=NO DWASH=NS DWASH=NS DWASH=NA ************************************	(UG/M**3) 0 4.98E-02 3.06E-02 2.50E-02 1-HR 7.91E-02 MEANS MEANS MEANS MEANS MEANS MEANS MEANS	STAB 1 4 4 6 CONCENTRA 3 NO NO NO HUBER-SNY SCHULMAN DOWNWAS	(M/S) 1 4 2 1 AT 10 CALC BUILDING DOWNWAS DOWNWAS DOWNWAS NOT	(M/S) 1 4 2 1 0 MADE DOWNWAS USED USED APPLICABLE MODEL	(M) 320 1280 640 10000 BEYOND 3200 (CONC USED X<3*LB RESULTS	HT 49.8 16.24 27.49 39.36 1 8.62 =	(M) 16.01 31.44 32.67 M: 6.81 0.0)	Y 14.16 27.93 22.19 6.23	(M) NO NO NO NO
(M) 1 100 200 300 MAXIMUM 30 DWASH= DWASH=NO DWASH=NS DWASH=SS DWASH=NA ************************************	(UG/M**3) 0 4.98E-02 3.06E-02 2.50E-02 1-HR 7.91E-02 MEANS MEANS MEANS MEANS MEANS MEANS MEANS SMEANS	STAB 1 4 4 6 CONCENTRA 3 NO NO HUBER-SNY SCHULMAN DOWNWAS 	(M/S) 1 4 2 1 AT 10 CALC BUILDING DOWNWAS DOWNWAS DOWNWAS NOT	(M/S) 1 4 2 1 0 R 10 MADE DOWNWAS USED USED APPLICABLE MODEL	(M) 320 1280 640 10000 BEYOND 3200 (CONC USED X<3*LB RESULTS	HT 49.8 16.24 27.49 39.36 1 8.62 =	(M) 16.01 31.44 32.67 M: 6.81 0.0)	Y 0.68 14.16 27.93 22.19 6.23	(M) NO NO NO NO
(M) 1 100 200 300 MAXIMUM 30 DWASH= DWASH=NO DWASH=NS DWASH=SS DWASH=NA ************************************	(UG/M**3) 0 4.98E-02 3.06E-02 2.50E-02 1-HR 7.91E-02 MEANS MEANS MEANS MEANS MEANS MEANS MEANS SUMMARY	STAB 1 4 4 6 CONCENTR/ 3 NO NO HUBER-SNY SCHULMAN DOWNWAS	(M/S) 1 4 2 1 AT 10 CALC BUILDING DOWNWAS DOWNWAS DOWNWAS NOT ******	(M/S) 1 4 2 1 OR 10 MADE DOWNWAS USED USED APPLICABLE MODEL	(M) 320 640 10000 BEYOND 3200 (CONC USED X<3*LB RESULTS	HT 49.8 16.24 27.49 39.36 1 8.62 = ****	(M) 16.01 31.44 32.67 M: 6.81 0.0)	Y 14.16 27.93 22.19 6.23	(M) NO NO NO NO
(M) 1 100 200 300 MAXIMUM 30 DWASH= DWASH=NO DWASH=NS DWASH=SS DWASH=SS DWASH=NA ************************************	(UG/M**3) 0 4.98E-02 3.06E-02 2.50E-02 1-HR 7.91E-02 MEANS MEANS MEANS MEANS MEANS MEANS MEANS MEANS MEANS MEANS MEANS MEANS MEANS MEANS	STAB 1 4 4 6 CONCENTRA 3 NO NO HUBER-SNY SCHULMAN DOWNWAS ************************************	(M/S) 1 4 2 1 AT 10 CALC BUILDING DOWNWAS DOWNWAS DOWNWAS NOT ****** SCREEN ****** DIST	(M/S) 1 4 2 1 0 MADE DOWNWAS USED USED USED APPLICABLE MODEL	(M) 320 1280 640 10000 BEYOND 3200 (CONC USED X<3*LB RESULTS	HT 49.8 16.24 27.49 39.36 1 8.62 =	(M) 16.01 31.44 32.67 M: 6.81 0.0)	Y 14.16 27.93 22.19 6.23	(M) NO NO NO NO
(M) 1 100 200 300 MAXIMUM 30 DWASH= DWASH=NO DWASH=NO DWASH=HS DWASH=SS DWASH=SS DWASH=NA ***** CALCULATION PROCEDURE	(UG/M**3) 0 4.98E-02 3.06E-02 2.50E-02 1-HR 7.91E-02 MEANS MEANS MEANS MEANS MEANS MEANS MEANS MEANS SUMMARY ***********	STAB 1 4 6 CONCENTR/ 3 NO NO HUBER-SNY SCHULMAN DOWNWAS ************************************	(M/S) 1 4 2 1 AT CALC BUILDING DOWNWAS DOWNWAS DOWNWAS NOT ****** SCREEN ****** DIST (M)	(M/S) 1 4 2 1 0 MADE DOWNWAS USED USED APPLICABLE MODEL TO HT	(M) 320 1280 640 10000 BEYOND 3200 (CONC USED X<3*LB RESULTS TERRAIN (M)	HT 49.8 16.24 27.49 39.36 1 8.62 =	(M) 16.01 31.44 32.67 M: 6.81 0.0)	Y 0.68 14.16 27.93 22.19 6.23	(M) NO NO NO NO
(M) 1 100 200 300 MAXIMUM 30 DWASH= DWASH=NO DWASH=NO DWASH=NS DWASH=SS DWASH=SS DWASH=SS DWASH=NA ************************************	(UG/M**3) 0 4.98E-02 3.06E-02 2.50E-02 1-HR 7.91E-02 MEANS MEANS MEANS MEANS MEANS MEANS MEANS MEANS MEANS MEANS MEANS MEANS MEANS MEANS MEANS MEANS MEANS	STAB 1 4 6 CONCENTRA 3 NO NO HUBER-SNY SCHULMAN DOWNWAS ************************************	(M/S) 1 4 2 1 AT 10 CALC BUILDING DOWNWAS DOWNWAS NOT ****** SCREEN ****** DIST (M) 	(M/S) 1 4 2 1 OR 10 MADE DOWNWAS USED USED APPLICABLE MODEL TO HT	(M) 320 1280 640 10000 BEYOND 3200 (CONC USED X<3*LB RESULTS TERRAIN (M)	HT 49.8 16.24 27.49 39.36 1 8.62 = ****	(M) 0.71 16.01 31.44 32.67 M: 6.81 0.0)	Y 0.68 14.16 27.93 22.19 6.23	(M) NO NO NO NO

Natural Gas HAPs Emissions Modeling

All input parameters remained the same except the emissions rate shown below: EMISSION RATE (Gram/Second) = 4.67E-04 MAXIMUM 1-HR CONCENTRATION AT OR BEYOND 5 Meters: 1.35E-01 ug/m3 at 30 meters.

RISK ASESSMENT

Although no pollutants for which emissions factors are established exceeded the levels specified in Table 1 or Table 2 of ARM 17.8.770, the Department conducted a full risk assessment. The Department determined that the calculated Cancer Risks demonstrate a negligible risk to human health and the environment. As documented in the table below and in accordance with the Department's negligible risk requirement, no single HAP concentration results in a Cancer Risk greater than 1.00E-06 and the sum of all Cancer Risks are less than 1.00E-05. Further, the sum of the Chronic Non-cancer Reference Exposure Level (CNCREL) hazard quotients is less than 1.0 as required to demonstrate compliance with the negligible risk requirement.

HAP	Modeled		Cancer	Cancer	CNCREL ⁽⁶⁾	CNCREL	Notes
			URF ⁽²⁾				
Crematorium Process	HAP		(µg/m3) ⁻¹	Risk ⁽³⁾	(µg/m3)	Quotient ⁽⁷⁾	
Emissions	Concent	ration					
Bromoform	8.45E-06	µg/m³	1.10E-06	9.29E-	ND	NA	(AFSSCC 5-
		2		12			02-005-05)
Carbon Tetrachloride	1.67E-05	µg/m³	6.00E-06	1.00E-	1.00E+02	1.67E-07	(AFSSCC 5-
				10			02-005-05)
Chloroform	1.59E-05	µg/m³	ND	ND	9.80E+01	1.62E-07	(AFSSCC 5-
							02-005-05)
1,2-Dichloropropane(4)	3.85E-04	µg/m²	1.90E-05	7.31E-	4.00E+00	9.62E-05	(AFSSCC 5-
				09			02-005-05)
Ethyl Benzene	4.69E-04	µg/m³	2.50E-06	1.17E-	1.00E+03	4.69E-07	(AFSSCC 5-
0		2		09			02-005-05)
Naphthalene ⁸	3.38E-03	µg/m³	3.40E-05	1.15E-	3.00E+00	1.13E-03	(AFSSCC 5-
				07			02-005-05)
Tetrachloroethylene(5)	1.17E-05	µg/m³	5.90E-06	6.93E-	2.70E+02	4.35E-08	(AFSSCC 5-
				11			02-005-05)
1,1,2,2-Tetrachloroethane	3.21E-05	µg/m³	5.80E-05	1.86E-	ND	NA	(AFSSCC 5-
				09			02-005-05)
Toluene ⁹	1.35E-03	µg/m³	ND	ND	5.00E+03	2.69E-07	(AFSSCC 5-
							02-005-05)
Vinylidine Chloride	2.07E-05	µg/m³	ND	ND	2.00E+02	1.03E-07	(AFSSCC 5-
							02-005-05)
Xylene	6.41E-04	µg/m³	ND	ND	1.00E+02	6.41E-06	(AFSSCC 5-
							02-005-05)
Natural Gas Emissions							
2-Methylnaphthalene	1.71E-07	$\mu g/m^3$	ND	ND	ND	ND	Table 1.
		,					Prioritized
							Chronic
							Dose-
							Response
							Values

3-Methylchloranthrene	1.28E-08	µg/m³	0.0063	8.09E- 11	ND	ND	Same as
7,12-	1.14E-07	μg/m ³	0.071	8.11E-	ND	ND	Same as
Dimethylbenz(a)anthracene		1.0/		09			above
Acenaphthene	1.28E-08	µg/m³	ND	ND	ND	ND	Same as
							above
Acenaphthylene	1.28E-08	µg/m³	ND	ND	ND	ND	Same as
							above
Anthracene	1.71E-08	µg/m³	ND	ND	ND	ND	Same as
		2					above
Benzene	1.50E-05	µg/m³	0.0000078	1.17E-	3.00E+01	5.00E-07	Same as
				10			above
Benzo(a)anthracene	1.28E-08	µg/m²	0.00011	1.41E-	ND	ND	Same as
		, 3		12			above
Benzo(a)pyrene	8.57E-09	µg/m°	0.0011	9.42E-	ND	ND	Same as
	1 205 00	, 3	0.00011	12			above
Benzo(b)fluoranthene	1.28E-08	µg/m°	0.00011	1.41E-	ND	ND	Same as
	4 205 00	, 3	0.00011	12	ND		above
Benzo(k)fluoranthene	1.28E-08	µg/m	0.00011	1.41E-	ND	ND	Same as
Develop (a. h. i) a sur develop	0.575.00	···· 3	ND	12	ND	ND	above
Benzo(g,n,i)perviene	8.57E-09	µg/m	ND	ND	ND	ND	Same as
Chrysone	1 205 00		0.000011	1 41 5		ND	Sama ac
Chrysene	1.28E-08	µg/m	0.000011	1.41E-	ND	ND	Same as
Dihanz(a h)anthracana	9 575 00		0.0012	13		ND	Sama ac
Dibenz(a,n)anthracene	8.57E-09	µg/m	0.0012	1.03E-	ND	ND	Same as
	0.575.00		0.000011	11	0.005.02	1 075 00	above
1,4-Dichlorobenzene(p)	8.57E-06	µg/m	0.000011	9.42E-	8.00E+02	1.07E-08	Same as
Eluoranthono	2 1/15 09	ug/m ³	ND		ND	ND	Samo ac
Fluorantinene	2.146-00	μg/11	ND		ND	ND	above
Fluorene	2 00F-08	ug/m ³	ND	ND	ND	ND	Same as
	2.002.00	M9/	ND				above
Formaldehvde	5.35E-04	ug/m ³	0.000013	6.96E-	9.80E+00	5.46E-05	Same as
		P'0/ ···		09			above
Hexane	1.28E-02	$\mu g/m^3$	ND	ND	7.00E+02	1.84E-05	Same as
		10,					above
Indeno(1,2,3,c,d)pyrene	1.28E-08	µg/m³	0.00011	1.41E-	ND	ND	Same as
				12			above
Naphthalene	4.35E-06	µg/m³	0.000034	1.48E-	ND	ND	Same as
				10			above
Phenanthrene	1.21E-07	µg/m³	ND	ND	ND	ND	Same as
							above
Pyrene	3.57E-08	µg/m³	ND	ND	ND	ND	Same as
							above
Toluene	2.43E-05	µg/m³	ND	ND	5.00E+03	4.85E-09	Same as
		. 3					above
Arsenic	1.43E-06	µg/m³	0.0043	6.14E-	1.50E-02	9.52E-05	Same as
		, 3		09			above
Beryllium	8.57E-08	µg/m°	0.0024	2.06E-	2.00E-02	4.28E-06	Same as
		, 3	0.0010	10	4 005 00		above
Cadmium	7.85E-06	µg/m²	0.0018	1.41E-	1.00E-02	7.85E-04	Same as
							2001/0
Characterize testal	0.005.00		0.012	08	4 005 04	0.255.05	
Chromium, total	9.99E-06	µg/m³	0.012	08 1.20E- 07	1.08E-01	9.25E-05	Same as
Chromium, total	9.99E-06	µg/m³	0.012	08 1.20E- 07	1.08E-01	9.25E-05	Same as above

Cobalt	6.00E-07	μg/m ³	ND	ND	1.00E-01	6.00E-06	Same as
							above
Lead	3.57E-06	µg/m³	ND	ND	1.50E-01	2.38E-05	Same as
							above
Manganese	2.71E-06	µg/m³	ND	ND	5.00E-02	5.42E-05	Same as
							above
Mercury	1.86E-06	µg/m³	ND	ND	3.00E-01	6.19E-06	Same as
							above
Nickel	1.50E-05	µg/m³	ND	ND	9.00E-02	1.67E-04	Same as
							above
Selenium	1.71E-07	µg/m³	ND	ND	2.00E+01	8.57E-09	Same as
							above
TOTAL RISK				2.82E-		2.54E-03	
				07			
(1) Source of chronic dose-res	sponse value	es is from	Table 1: Pric	oritized Ch	ronic Dose-R	esponse Valu	es
for Screening Risk Assessmen	ts (4/27/201	L0), from	www.epa.gov	/ttn/atw/	'toxsource/ta	able1.pdf.	
(2) Cancer Chronic Inhalation	ı Unit Risk Fa	actor fron	n reference ":	1", units 1,	/ug/m3		
(3) Cancer Risk is unitless and	d is calculate	d by mul	tiplying the p	redicted co	oncentration	by the URF.	1
(4) Also known as Propylene	dichloride						
(5) Also known as Tetrachlor	oethene, pe	rchloroet	hylene.				
(6) Chronic Noncancer Refere	ence Exposu	re Level f	rom referenc	e "1".			
(7) CNCREL Quotient Value is	calculated l	oy dividin	g the modele	d HAP cor	centration b	y the CNCREL	
(8) Naphthalene contribution	n from natur	al gas is s	ummed in th	e cremato	rium process	5.	
(9) Toluene contribution from	n natural ga	s is summ	ed in the cre	matorium	process.		

VIII. Taking or Damaging Implication Analysis

As required by 2-10-105, MCA, the Department conducted the following private property taking and damaging assessment.

YES	NO	
v		1. Does the action pertain to land or water management or environmental regulation affecting
Λ		private real property or water rights?
	v	2. Does the action result in either a permanent or indefinite physical occupation of private
	Λ	property?
	x	3. Does the action deny a fundamental attribute of ownership? (ex.: right to exclude others,
	Λ	disposal of property)
	X	4. Does the action deprive the owner of all economically viable uses of the property?
	x	5. Does the action require a property owner to dedicate a portion of property or to grant an
	Λ	easement? [If no, go to (6)].
		5a. Is there a reasonable, specific connection between the government requirement and legitimate
		state interests?
		5b. Is the government requirement roughly proportional to the impact of the proposed use of the
		property?
	x	6. Does the action have a severe impact on the value of the property? (consider economic
		impact, investment-backed expectations, character of government action)
	x	7. Does the action damage the property by causing some physical disturbance with respect to the
		property in excess of that sustained by the public generally?
	X	7a. Is the impact of government action direct, peculiar, and significant?
	x	7b. Has government action resulted in the property becoming practically inaccessible,
-		waterlogged or flooded?
		7c. Has government action lowered property values by more than 30% and necessitated the
	X	physical taking of adjacent property or property across a public way from the property in
		question?
		Takings or damaging implications? (Taking or damaging implications exist if YES is checked in
	Х	response to question 1 and also to any one or more of the following questions: 2, 3, 4, 6, 7a, 7b,
		7c; or if NO is checked in response to questions 5a or 5b; the shaded areas)

Based on this analysis, the Department determined there are no taking or damaging implications associated with this permit action.

IX. Environmental Assessment

An environmental assessment, required by the Montana Environmental Policy Act, was completed for this project. A copy is attached.

DEPARTMENT OF ENVIRONMENTAL QUALITY Permitting and Compliance Division Air Resources Management Bureau P.O. Box 200901, Helena, Montana 59620 (406) 444-3490

FINAL ENVIRONMENTAL ASSESSMENT (EA)

Issued To: All Montana Crematory 1022 Lyon Avenue Lake City, MN 55041

Montana Air Quality Permit Number: 4735-00

Preliminary Determination Issued: April 16, 2012 Department Decision Issued: May 17, 2012 Permit Final: June 5, 2012

- 1. Legal Description of Site: The All Montana Crematory (AMC) is located at the legal description of Section 3, Township 4, Range 11 West, Block 26, Lots 11-12 in Deer Lodge County, Montana.
- 2. Description of Project: AMC proposes to operate a 2012 U.S. Equipment Model 100 "Classic" multiple chamber human cremation unit with a maximum incineration capacity of 200 pounds per hour (lb/hr), and associated equipment. The crematory is fired on natural gas. The secondary chamber shall maintain a temperature of 1600 degrees Fahrenheit (°F), with no single reading less than 1575 °F and is managed by a programmable logic controller (PLC) that controls each cremation cycle. After the secondary chamber has been heated sufficiently, the cremator burner ignites and the cremation process is initiated.

Initial and supplementary combustion is provided by two burners fired by natural gas, one in the primary chamber and one in the secondary chamber, with a total maximum rated design capacity of 2,000,000 British thermal units per hour (Btu/hr).

- 3. *Objectives of Project*: The objective of the project is to generate revenue and provide a safe means of disposal of human remains.
- 4. Alternatives Considered: In addition to the proposed action, the Department also considered the "noaction" alternative. The "no-action" alternative would deny issuance of the air quality preconstruction permit to the proposed facility. However, the Department does not consider the "noaction" alternative to be appropriate because AMC demonstrated compliance with all applicable rules and regulations as required for permit issuance. Therefore, the "no-action" alternative was eliminated from further consideration.
- 5. *A Listing of Mitigation, Stipulations, and Other Controls*: A list of enforceable conditions, including a Best Available Control Technology (BACT) analysis, would be included in MAQP #4735-00.
- 6. *Regulatory Effects on Private Property*: The Department considered alternatives to the conditions imposed in this permit as part of the permit development. The Department determined that the permit conditions are reasonably necessary to ensure compliance with applicable requirements and demonstrate compliance with those requirements and do not unduly restrict private property rights.

7. The following table summarizes the potential physical and biological effects of the proposed project on the human environment. The "no-action" alternative was discussed previously.

		Major	Moderate	Minor	None	Unknown	Comments Included
А	Terrestrial and Aquatic Life and Habitats			Х			Yes
В	Water Quality, Quantity, and Distribution			Х			Yes
C	Geology and Soil Quality, Stability and Moisture			Х			Yes
D	Vegetation Cover, Quantity, and Quality			Х			Yes
Е	Aesthetics			Х			Yes
F	Air Quality			X			Yes
G	Unique Endangered, Fragile, or Limited Environmental Resources			Х			Yes
Н	Demands on Environmental Resource of Water, Air and Energy			Х			Yes
Ι	Historical and Archaeological Sites			Х			Yes
J	Cumulative and Secondary Impacts			Х			Yes

SUMMARY OF COMMENTS ON POTENTIAL PHYSICAL AND BIOLOGICAL EFFECTS: The following comments have been prepared by the Department.

A. Terrestrial and Aquatic Life and Habitats

Emissions from the proposed project would affect terrestrial and aquatic life and habitats in the proposed project area. However, as detailed in Section V and Section VI of the permit analysis, any emissions and resulting impacts from the project would be minor due to the low concentration of those pollutants emitted.

Further, the proposed crematorium would operate within a building addition located in an area zoned as commercial and currently used as a mortuary. Overall, any impact to the terrestrial and aquatic life and habitats of the proposed project area would be minor.

B. Water Quality, Quantity and Distribution

The project would not be expected to affect water quantity or distribution in the project area. The crematorium operates within a building and does not discharge or use water during operation.

Emissions from the project may affect water quality in the project area due to air pollutant deposition. Warm Springs Creek is approximately 1200 feet north of the project site which flows into the Clark Fork as it migrates to the north and east. However, any emissions and resulting deposition impacts from the project would be very minor due to the low concentration of those pollutants emitted.

C. Geology and Soil Quality, Stability and Moisture

The project would not be expected to affect the geology, stability, and moisture of the project area. The proposed crematorium would be located in a building expansion to an existing facility and would operate within the building addition.

Proper crematorium operation would result in minor air pollution emissions to the ambient environment. These pollutants would deposit on the soils in the surrounding area. However, any impact from deposition of these pollutants would be very minor due to dispersion characteristics and the low concentration of those pollutants emitted.

D. Vegetation Cover, Quantity, and Quality

Air emissions from the project may affect vegetation cover, quantity, and quality in the project area. However, any emissions and resulting impacts from the project would be minor due to the dispersion characteristics and the low concentration of those pollutants emitted.

Further, the crematorium would operate in a building addition to an existing building. Overall, any impact to the vegetation cover, quantity, and quality of the proposed project area would be minor.

E. Aesthetics

The project would result in a minor impact to the aesthetic nature of the project area. The crematorium would operate within a building addition. Further, visible emissions from the source would be limited to 10% opacity. Therefore, the project would result in only a minor impact to aesthetics of the area.

F. Air Quality

The project would result in the emissions of various criteria pollutants and HAPs to the ambient air in the project area. However, it has been demonstrated by air dispersion modeling that any air quality impacts from the project would be minor and would constitute negligible risk to human health and the environment.

The Department conducted air dispersion modeling to determine the ambient air quality impacts from HAPs that would be generated by the crematorium. The SCREEN3 model was selected for the air dispersion modeling. The full meteorology option was selected to provide a conservative result. Receptors were placed in a simple terrain array and the maximum concentration identified from the source stack.

Stack parameters and emission rates used in the SCREEN3 model are contained in Section V of the permit analysis and are on file with the Department. Stack velocity and gas temperature were taken from data provided by the manufacturer of the crematorium. Due to the dispersion characteristics and low levels of pollutants that would be emitted from the proposed project the Department determined that any impacts to air quality would be minor.

G. Unique Endangered, Fragile, or Limited Environmental Resources

The current permit action could result in minor impacts to any existing unique endangered, fragile, or limited environmental resource in the proposed area of operation. However, the proposed crematorium would require only a limited amount of construction and would operate within a building addition located in an area zoned as commercial thereby limiting the potential for impact to any unique endangered, fragile, or limited environmental resource in the proposed location.

The Department, in an effort to assess any potential impacts to any unique endangered, fragile, or limited environmental resources in the initial proposed area of operations, contacted the Montana Natural Heritage Program (MNHP) to identify any species of concern associated with the proposed site location. Search results concluded there are six species of concern within the defined area. These include the Westslope Cutthroat Trout, Bull Trout, Hoary Bat, Fisher, Wolverine, and the Clark's Nutcracker.

The Clark's Nutcracker, Fisher, and the Hoary Bat are each listed as state conservation status of S3, signifying a state-level rank of vulnerable. The global conservation status is G5, signifying a global-level rank of secure. Secure is defined by NatureServe.org as common; widespread and abundant. The Westslope Cutthroat Trout is listed as S2, and G4T3. The Bull Trout is listed as S2 and G3 with the Wolverine at S3 and G4. The S2 classification indicates imperiled with S3 indicating vulnerable. The G3 and G4 ranks are nearly synonymous with the state rank and indicate vulnerable and apparently secure, respectively.

Emissions from the proposed project could impact any existing unique endangered, fragile, or limited environmental resource located in the proposed project area. However, as detailed in Section VI of the permit analysis, any emissions and resulting impacts from the project would be minor due to the low concentration of those pollutants emitted. Overall, any impact to the unique endangered, fragile, or limited environmental resources of the proposed project area would be minor. Additionally, the species of concern report is generated for the survey section plus an additional one mile buffer which incorporates the foothills surrounding the town of Anaconda. Since the new incinerator will be constructed within an existing building, located within the town of Anaconda, the impact to the species of concern would be considered minor.

H. Demands on Environmental Resource of Water, Air and Energy

The proposed project would result in minor demands on environmental resources of water and air as discussed in Section 7.B and 7.F, respectively, of this EA. Further, as detailed in Section V and Section VI of the permit analysis, project impacts on air resources in the proposed project area would be minor due to dispersion characteristics and the low concentration of those pollutants emitted. Finally, because the project is small by industrial standards, little energy would be required for operation and the resulting impact on energy resources would be minor.

I. Historical and Archaeological Sites

The Department contacted the Montana Historical Society - State Historical Preservation Office (SHPO) in an effort to identify any historical and/or archaeological sites that may be present in the proposed area of construction/operation. Search results concluded there are many previously recorded sites within the general area proposed for the project as the town of Anaconda has many historic buildings continuing to be used as both residences and places of business. However, it is understood this particular building is not one of the historic buildings included in the Cultural Resource Inventory. As the proposed project is not to be constructed within or as an addition to a recognized historic structure, any impact to the historical buildings of the area would be considered minor.

J. Cumulative and Secondary Impacts

Overall, the cumulative and secondary impacts from this project on the environment in the immediate area would be minor. The Department believes that this facility could be expected to operate in compliance with all applicable rules and regulations as outlined in Permit #4735-00.

		Major	Moderate	Minor	None	Unknown	Comments Included
А	Social Structures and Mores			Х			Yes
В	Cultural Uniqueness and Diversity			Х			Yes
C	Local and State Tax Base and Tax Revenue			Х			Yes
D	Agricultural or Industrial Production				Х		Yes
Е	Human Health			Х			Yes
F	Access to and Quality of Recreational and Wilderness Activities			Х			Yes
G	Quantity and Distribution of Employment				Х		Yes
Н	Distribution of Population				Х		Yes
Ι	Demands for Government Services			Х			Yes
J	Industrial and Commercial Activity			Х			Yes
K	Locally Adopted Environmental Plans and Goals					Х	Yes
L	Cumulative and Secondary Impacts			Х			Yes

8. The following table summarizes the potential economic and social effects of the proposed project on the human environment. The "no-action" alternative was discussed previously.

SUMMARY OF COMMENTS ON POTENTIAL ECONOMIC AND SOCIAL EFFECTS: The following comments have been prepared by the Department.

A. Social Structures and Mores

The proposed project is to install a 200 lb/hr cremation incinerator for human remains at an existing mortuary business. The incinerator's emissions would be extremely low on an industrial scale and opacity limitations of MAQP #4735-00 would require 10% or less opacity while operating. Any change to social structures or mores would be minor, if any.

B. Cultural Uniqueness and Diversity

The proposed project would cause a minor change in the cultural uniqueness and diversity of the area because the proposed incinerator is new but would be installed as part of an existing mortuary.

C. Local and State Tax Base and Tax Revenue

The proposed project may provide additional revenue for AMC, however; no need for additional employees would be expected as a result of this project. Therefore, minimal, if any, impacts to the local and state tax base and tax revenue are anticipated from this project except for the construction portion of the project which will require minor resources for the building addition.

D. Agricultural or Industrial Production

The proposed project would result in no reduction of available acreage of any agricultural land as the building addition footprint is located on the site of a previous parking lot. Furthermore, the potential-to-emit of the proposed project is extremely small. Based on the small amount of emissions and the dispersion of those emissions, no discernible impact would be expected to agricultural or industrial production in the area.

E. Human Health

As described in Section VI of the Permit Analysis, modeling and analysis of hazardous air pollutants showed negligible risk to human health. Furthermore, the potential-to-emit of conventional pollutants would be extremely small. Impacts to human health would be minor, if any discernible amount at all.

F. Access to and Quality of Recreational and Wilderness Activities

The proposed project is to install the incinerator at an existing place of business. No change to access of recreational and wilderness activities would be expected. Permit conditions would require opacity of the emissions to be 10% or less while operating. The potential-to-emit of the proposed incinerator would be very small. The town of Anaconda is approximately 14 air miles from the north-eastern boundary of the Anaconda-Pintler Wilderness. Therefore, minor, if any impact to the quality of recreational and wilderness activities would be expected as a result of this project.

G. Quantity and Distribution of Employment

No need for a change in the number of employees would be expected as a result of this project. Therefore, no impacts to the quantity and distribution of employment would be expected. Employees would be utilized from a separate local location.

H. Distribution of Population

No need for a change in the number of employees would be expected and no other factors affecting distribution of population would be expected to be present as a result of this project. The project proposes to install the incinerator in a building addition at an existing mortuary, yet utilize existing local employees' place of business. Furthermore, opacity limitations in the permit would require a 10% or less opacity of emissions. Therefore, no impacts to the distribution of population would be expected.

I. Demands for Government Services

Government services would be required for acquiring the appropriate permits from government agencies. In addition, the permitted source of emissions would be subject to periodic inspections by government personnel. Overall, demands for government services would be minor.

J. Industrial and Commercial Activity

The proposed project would result in only a minor impact on local industrial and commercial activity because the crematorium would require only a limited amount of new construction, would operate within a building and would not result in additional industrial production. Overall, any impacts to industrial and commercial activity in the proposed area of operation would be minor.

K. Locally Adopted Environmental Plans and Goals

The Department is not aware of any locally adopted environmental plans and goals this project may impact. The state standards would be protective of the proposed project area.

L. Cumulative and Secondary Impacts

Overall, cumulative and secondary impacts from this project would result in minor impacts to the economic and social environment in the immediate area due to the relatively small size of the operation. The Department believes that this facility could be expected to operate in compliance with all applicable rules and regulations as would be outlined in MAQP #4735-00.

Recommendation: No Environmental Impact Statement (EIS) is required.

If an EIS is not required, explain why the EA is an appropriate level of analysis: The current permitting action is for the construction and operation of a crematorium (incinerator). MAQP #4735-00 includes conditions and limitations to ensure the facility will operate in compliance with all applicable rules and regulations. In addition, there are no significant impacts associated with this proposal.

- Other groups or agencies contacted or which may have overlapping jurisdiction: Montana Historical Society – State Historic Preservation Office, Natural Resource Information System – Montana Natural Heritage Program
- Individuals or groups contributing to this EA: Department of Environmental Quality Air Resources Management Bureau

EA prepared by: Craig Henrikson Date: 03/29/2012